

Package ‘GInSARCorW’

June 26, 2020

Type Package

Title GACOS InSAR Correction Workflow

Version 1.15.6

Date 2020-06-24

Author Subhadip Datta

Maintainer Subhadip Datta <subhadipdatta007@gmail.com>

Description A workflow for correction of Differential Interferometric Synthetic Aperture Radar (DInSAR) atmospheric delay base on Generic Atmospheric Correction Online Service for InSAR (GACOS) data and correction algorithms proposed by Chen Yu. You can find atmospheric delay data here: <<http://ceg-research.ncl.ac.uk/v2/gacos>>. This package calculate the Both Zenith and LOS direction (User Depend). You have to just download GACOS product on your area and preprocessed D-InSAR unwrapped images. Cite those references and this package in your work, when using this framework.

References:

Yu, C., N. T. Penna, and Z. Li (2017) <[doi:10.1016/j.rse.2017.10.038](https://doi.org/10.1016/j.rse.2017.10.038)>.

Yu, C., Li, Z., & Penna, N. T. (2017) <[doi:10.1016/j.rse.2017.10.038](https://doi.org/10.1016/j.rse.2017.10.038)>.

Yu, C., Penna, N. T., and Li, Z. (2017) <[doi:10.1002/2016JD025753](https://doi.org/10.1002/2016JD025753)>.

License GPL-3

URL <<https://subhadipdatta007.wixsite.com/profile/post/ginsarcorw-gacos-insar-correction-workflow>>

Repository CRAN

Depends raster, circular

Imports rgdal, rgeos, sp

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

NeedsCompilation no

Date/Publication 2020-06-26 12:00:06 UTC

R topics documented:

coh.mask	2
d.ztd	3
d.ztd.resample	4
GACOS.Import	4
GACOS.PhCor	5
Phase.to.disp	6
Phase.to.height	7
Index	8

coh.mask	<i>Mask image with coherence threshold</i>
----------	--

Description

Mask image with coherence threshold

Usage

```
coh.mask(img, coh_band, threshold = 0.2, noData_as_NA = TRUE)
```

Arguments

img	Any image (i.e Phase,Displacement,GACOS imported image)
coh_band	coherence band
threshold	A value from coherence band above which the mask will be process.(within 0-1)
noData_as_NA	If TRUE, it convert noData to NA or 0

Author(s)

Subhadip Datta

Examples

```
library(raster)
library(GInSARCorW)
library(circular)
noDataAsNA<-FALSE
i1m<-system.file("td","20170317.ztd.rsc",package = "GInSARCorW")
i2m<-system.file("td","20170410.ztd.rsc",package = "GInSARCorW")
GACOS_ZTD_T1<-GACOS.Import(i1m,noDataAsNA)
GACOS_ZTD_T2<-GACOS.Import(i2m,noDataAsNA)
dztd<-d.ztd(GACOS_ZTD_T1,GACOS_ZTD_T2)
unw pha<-raster(system.file("td","Unw_Phase_ifg_17Mar2017_10Apr2017_VV.img",package = "GInSARCorW"))
crs(unw pha)<-CRS("+proj=longlat +datum=WGS84 +no_defs")
re_dztd<-d.ztd.resample(unw pha,dztd)
unw_phase<-GACOS.PhCor(unw pha,re_dztd,0.055463,inc_ang=39.16362,ref_lat=NA,ref_lon=NA)
```

```
disp<-Phase.to.disp(unw_phase,0.055463,unit="m",39.16362)
coh_band<-raster(system.file("td","coh_IW2_VV_17Mar2017_10Apr2017.img",package = "GInSARCorW"))
crs(coh_band)<-CRS("+proj=longlat +datum=WGS84 +no_defs")
coh.mask(disp,coh_band,threshold=0.4)
```

d.ztd

Calculate ZTD difference between times

Description

Calculate ZTD difference between times

Usage

```
d.ztd(GACOS_ZTD_T1, GACOS_ZTD_T2)
```

Arguments

GACOS_ZTD_T1	ZTD time 1
GACOS_ZTD_T2	ZTD time 2

Author(s)

Subhadip Datta

Examples

```
library(raster)
library(GInSARCorW)
library(circular)
noDataAsNA<-FALSE
i1m<-system.file("td","20170317.ztd.rsc",package = "GInSARCorW")
i2m<-system.file("td","20170410.ztd.rsc",package = "GInSARCorW")
GACOS_ZTD_T1<-GACOS.Import(i1m,noDataAsNA)
GACOS_ZTD_T2<-GACOS.Import(i2m,noDataAsNA)
d.ztd(GACOS_ZTD_T1,GACOS_ZTD_T2)
```

d.ztd.resample	<i>Resample Di-ZTD to phase cell resolution and match raster extents.</i>
----------------	---

Description

Resample Di-ZTD to phase cell resolution and match raster extents.

Usage

```
d.ztd.resample(unw pha, dztd, method = "bilinear")
```

Arguments

unw pha	Un-wrapped InSAR tile/raster.
dztd	Di-ZTD.
method	Raster resampling method "ngb" for nearest neighbor or "bilinear" for bilinear interpolation

Author(s)

Subhadip Datta

Examples

```
library(raster)
library(GInSARCorW)
library(circular)
noDataAsNA<-FALSE
i1m<-system.file("td", "20170317.ztd.rsc", package = "GInSARCorW")
i2m<-system.file("td", "20170410.ztd.rsc", package = "GInSARCorW")
GACOS_ZTD_T1<-GACOS.Import(i1m, noDataAsNA)
GACOS_ZTD_T2<-GACOS.Import(i2m, noDataAsNA)
dztd<-d.ztd(GACOS_ZTD_T1, GACOS_ZTD_T2)
unw pha<-raster(system.file("td", "Unw_Phase_ifg_17Mar2017_10Apr2017_VV.img", package = "GInSARCorW"))
crs(unw pha)<-CRS("+proj=longlat +datum=WGS84 +no_defs")
d.ztd.resample(unw pha, dztd)
```

GACOS.Import	<i>Import GACOS product in R</i>
--------------	----------------------------------

Description

Import GACOS product in R

Usage

```
GACOS.Import(rscFile.path, noDataAsNA = FALSE)
```

Arguments

rscFile.path Path of the GACOS .ztd.rsc file
 noDataAsNA If true it convert 0 values to NA

Author(s)

Subhadip Datta

Examples

```
library(raster)
library(GInSARCorW)
library(circular)
rscFile.path<-system.file("td","20170317.ztd.rsc",package = "GInSARCorW")
noDataAsNA<-FALSE
GACOS.Import(rscFile.path,noDataAsNA)
```

GACOS.PhCor

GACOS Atmospheric Phase delay correction

Description

GACOS Atmospheric Phase delay correction

Usage

```
GACOS.PhCor(
  unw pha,
  re_dztd,
  wavelength = "in meter",
  inc_ang = 90,
  ref_lat = NA,
  ref_lon = NA
)
```

Arguments

unw pha Un-wrapped InSAR tile/raster.
 re_dztd Resampled Di-ZTD.
 wavelength SAR wavelength in meter.
 inc_ang SAR incident angle (to get output in LOS direction, don't use if not needed).
 ref_lat A reference point for correction, If NA, It use the tile center latitude.
 ref_lon A reference point for correction, If NA, It use the tile center longitude.

Author(s)

Subhadip Datta

Examples

```

library(raster)
library(GInSARCorW)
library(circular)
noDataAsNA<-FALSE
i1m<-system.file("td","20170317.ztd.rsc",package = "GInSARCorW")
i2m<-system.file("td","20170410.ztd.rsc",package = "GInSARCorW")
GACOS_ZTD_T1<-GACOS.Import(i1m,noDataAsNA)
GACOS_ZTD_T2<-GACOS.Import(i2m,noDataAsNA)
dztd<-d.ztd(GACOS_ZTD_T1,GACOS_ZTD_T2)
unw pha<-raster(system.file("td","Unw_Phase_ifg_17Mar2017_10Apr2017_VV.img",package = "GInSARCorW"))
crs(unw pha)<-CRS("+proj=longlat +datum=WGS84 +no_defs")
re_dztd<-d.ztd.resample(unw pha,dztd)
GACOS.PhCor(unw pha,re_dztd,0.055463,inc_ang=39.16362,ref_lat=NA,ref_lon=NA)

```

Phase.to.disp

InSAR Unw-Phase to displacement

Description

InSAR Unw-Phase to displacement

Usage

```
Phase.to.disp(unw_phase, wavelength = "in meter", unit = "m", inc_ang = 0)
```

Arguments

unw_phase	Un-wrapped InSAR tile/raster.After/before correction.
wavelength	SAR wavelength in meter.
unit	output unit meter , centimeter or milimeter ("m", "cm" or "mm").
inc_ang	SAR incident angle (to get output in LOS direction, don't use if not needed).

Author(s)

Subhadip Datta

Examples

```

library(raster)
library(GInSARCorW)
library(circular)
noDataAsNA<-FALSE
i1m<-system.file("td","20170317.ztd.rsc",package = "GInSARCorW")
i2m<-system.file("td","20170410.ztd.rsc",package = "GInSARCorW")
GACOS_ZTD_T1<-GACOS.Import(i1m,noDataAsNA)
GACOS_ZTD_T2<-GACOS.Import(i2m,noDataAsNA)
dztd<-d.ztd(GACOS_ZTD_T1,GACOS_ZTD_T2)

```

```

unw pha<-raster(system.file("td", "Unw_Phase_ifg_17Mar2017_10Apr2017_VV.img", package = "GInSARCorW"))
crs(unw pha)<-CRS("+proj=longlat +datum=WGS84 +no_defs")
re_dztd<-d.ztd.resample(unw pha,dztd)
unw pha<-GACOS.PhCor(unw pha,re_dztd,0.055463,inc_ang=39.16362,ref_lat=NA,ref_lon=NA)
Phase.to.disp(unw pha,0.055463,unit="m",39.16362)

```

Phase.to.height *InSAR Unw-Phase to height*

Description

InSAR Unw-Phase to height

Usage

```
Phase.to.height(unw pha, wavelength = "in meter", unit = "m")
```

Arguments

unw pha	Un-wrapped InSAR tile/raster.After/before corrction.
wavelength	SAR wavelength in meter.
unit	output unit meter , centimeter or milimeter ("m", "cm" or "mm").

Author(s)

Subhadip Datta

Examples

```

library(raster)
library(GInSARCorW)
library(circular)
noDataAsNA<-FALSE
i1m<-system.file("td", "20170317.ztd.rsc", package = "GInSARCorW")
i2m<-system.file("td", "20170410.ztd.rsc", package = "GInSARCorW")
GACOS_ZTD_T1<-GACOS.Import(i1m,noDataAsNA)
GACOS_ZTD_T2<-GACOS.Import(i2m,noDataAsNA)
dztd<-d.ztd(GACOS_ZTD_T1,GACOS_ZTD_T2)
unw pha<-raster(system.file("td", "Unw_Phase_ifg_17Mar2017_10Apr2017_VV.img", package = "GInSARCorW"))
crs(unw pha)<-CRS("+proj=longlat +datum=WGS84 +no_defs")
re_dztd<-d.ztd.resample(unw pha,dztd)
unw pha<-GACOS.PhCor(unw pha,re_dztd,0.055463,inc_ang=39.16362,ref_lat=NA,ref_lon=NA)
Phase.to.height(unw pha,0.055463,unit="m")

```

Index

coh.mask, [2](#)

d.ztd, [3](#)

d.ztd.resample, [4](#)

GACOS.Import, [4](#)

GACOS.PhCor, [5](#)

Phase.to.disp, [6](#)

Phase.to.height, [7](#)