

# Package ‘RClimatecell’

March 23, 2021

**Title** R Wrapper for the 'Climatecell' API

**Version** 0.1.4

**Description** 'Climatecell' is a weather platform that provides hyper-local forecasts and weather data. This package enables the user to query the core layers of the time line interface of the 'Climatecell' v4 API <<https://www.climatecell.co/weather-api/>>. This package requires a valid API key. See vignettes for instructions on use.

**License** MIT + file LICENSE

**URL** <https://nikdata.github.io/RClimatecell/>

**BugReports** <https://github.com/nikdata/RClimatecell/issues>

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.1

**Imports** dplyr (>= 1.0.0), magrittr (>= 2.0.1), stringr (>= 1.4.0),  
tibble (>= 3.0.6), httr (>= 1.4.2), lubridate (>= 1.7.9.2),  
rlang (>= 0.4.10), tidyr (>= 1.1.2), assertthat (>= 0.2.1),  
tidyselect

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**Depends** R (>= 2.10)

**NeedsCompilation** no

**Author** Nikhil Agarwal [aut, cre] (<<https://orcid.org/0000-0003-1470-7472>>)

**Maintainer** Nikhil Agarwal <[gitnik@niks.me](mailto:gitnik@niks.me)>

**Repository** CRAN

**Date/Publication** 2021-03-23 19:00:03 UTC

## R topics documented:

climatecell_celestial . . . . .	2
climatecell_core . . . . .	3

climacell_precip . . . . .	4
climacell_temperature . . . . .	6
climacell_wind . . . . .	7
dict_moonphase . . . . .	9
dict_preciptype . . . . .	9
dict_weathercode . . . . .	9

## Index 10

---

climacell_celestial	<i>Sunrise, Sunset, and Moon Phase Readings from Climacell</i>
---------------------	--

---

### Description

This function will make a call to the Climacell API and retrieve sunrise, sunset times and moon phase variables.

### Usage

```
climacell_celestial(
  api_key,
  lat,
  long,
  timestep = "1d",
  start_time = NULL,
  end_time = NULL
)
```

### Arguments

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. For the climacell_celestial function, the only acceptable value (per the limitations of the Climacell API) is '1d'.
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time. For this function, the start_time cannot be less than 6 hours from the current time.

`end_time` the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. For this function, the `end_time` cannot be greater than 15 days from the current date/time.

### Details

`climacell_celestial` returns a tibble that consists of sunrise/sunset times along with the moon phase (code & description).

### Value

a tibble

### Examples

```
## Not run:
climacell_celestial(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = '1d',
  start_time = lubridate::now(),
  end_time = lubridate::now() + lubridate::days(5))

## End(Not run)
```

---

climacell\_core

*Climacell Core Layer Data*

---

### Description

`climacell_core` returns a tibble that contains all of the Core Layer data from the Climacell version 4 API using the Timelines interface. The intent of this function is to retrieve all of the Core Layer data in a single API call. This is especially handy when using the free API as it limits the usage of the API based on hourly rate and daily usage.

### Usage

```
climacell_core(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)
```

**Arguments**

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time. For this function, the start_time cannot be less than 6 hours from the current time.
end_time	the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if timestep is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

**Value**

a tibble

**Examples**

```
## Not run:
climacell_core(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = '1d',
  start_time = lubridate::now(),
  end_time = lubridate::now + lubridate::days(5))

## End(Not run)
```

---

climacell\_precip

*Precipitation Readings from Climacell*


---

**Description**

This function will make a call to the Climacell API and retrieve precipitation related (including cloud cover & pressure) values.

**Usage**

```
climacell_precip(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)
```

**Arguments**

<code>api_key</code>	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
<code>lat</code>	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
<code>long</code>	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
<code>timestep</code>	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
<code>start_time</code>	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the <code>lubridate::now()</code> function or <code>Sys.time()</code> be used to define the <code>start_time</code> . For this function, the <code>start_time</code> cannot be less than 6 hours from the current time.
<code>end_time</code>	the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if <code>timestep</code> is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

**Details**

`climacell_precip` returns a tibble that consists of precipitation related variables (returned values are in metric units) using the Climacell API. These variables consist of precipitation intensity, precipitation probability, precipitation description, visibility, surface & sea level pressure, cloud cover & ceiling, and a weather description.

**Value**

a tibble

**Examples**

```
## Not run:
```

```

climacell_precip(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = 'current')

## End(Not run)

```

---

climacell\_temperature *Temperature Readings from Climacell*

---

### Description

This function will make a call to the Climacell API and retrieve temperature related variables.

### Usage

```

climacell_temperature(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)

```

### Arguments

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time. For this function, the start_time cannot be less than 6 hours from the current time.

`end_time` the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if timestep is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

### Details

`climacell_temperature` returns a tibble that consists of temperature related variables (returned values are in metric units) using the Climacell API. These variables consist of temperature, a "feels like" temperature, dewpoint, and humidity.

### Value

a tibble

### Examples

```
## Not run:
climacell_temperature(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = 'current')

## End(Not run)
```

---

<code>climacell_wind</code>	<i>Wind Readings from Climacell</i>
-----------------------------	-------------------------------------

---

### Description

This function will make a call to the Climacell API and retrieve wind related variables.

### Usage

```
climacell_wind(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)
```

**Arguments**

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time. For this function, the start_time cannot be less than 6 hours from the current time.
end_time	the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if timestep is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

**Details**

climacell\_wind returns a tibble that consists of wind related variables (returned values are in metric units) using the Climacell API. These variables consist of wind speed, wind gust, and wind direction.

**Value**

a tibble

**Examples**

```
## Not run:
climacell_wind(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = 'current')

## End(Not run)
```



---

dict_moonphase	<i>Moonphase Dictionary</i>
----------------	-----------------------------

---

**Description**

this is a helper function that returns the moon phase tibble containing the moon phase codes (which are returned by Climacell API) and their appropriate description.

**Usage**

```
dict_moonphase()
```

**Value**

a tibble

---

dict_preciptype	<i>Precipitation Type Dictionary</i>
-----------------	--------------------------------------

---

**Description**

this is a helper function that returns the precipitation type tibble containing the precipitation type codes (which are returned by Climacell API) and their appropriate description.

**Usage**

```
dict_preciptype()
```

**Value**

a tibble

---

dict_weathercode	<i>Weather Dictionary</i>
------------------	---------------------------

---

**Description**

this is a helper function that returns the weather code tibble containing the weather codes (which are returned by Climacell API) and their appropriate description.

**Usage**

```
dict_weathercode()
```

**Value**

a tibble

# Index

climacell\_celestial, [2](#)  
climacell\_core, [3](#)  
climacell\_precip, [4](#)  
climacell\_temperature, [6](#)  
climacell\_wind, [7](#)  
  
dict\_moonphase, [9](#)  
dict\_preciptype, [9](#)  
dict\_weathercode, [9](#)