

Package ‘brassica’

August 13, 2022

Type Package

Title 1970s BASIC Interpreter

Version 1.0.0

Date 2022-08-11

Author Mike Lee

Maintainer Mike Lee <random.deviante@gmail.com>

Description Executes BASIC programs from the 1970s, for historical and educational purposes. This enables famous examples of early machine learning, artificial intelligence, natural language processing, cellular automata, and so on, to be run in their original form.

License GPL-3

Depends R (>= 3.3.0)

NeedsCompilation no

Repository CRAN

Date/Publication 2022-08-13 12:30:08 UTC

R topics documented:

| | |
|----------------------------|---|
| brassica-package | 2 |
| LIST | 2 |
| LowerCode | 3 |
| NotRun | 4 |
| RUN | 4 |
| UpperCode | 6 |

| | |
|--------------|----------|
| Index | 8 |
|--------------|----------|

brassica-package *BASIC Interpreter*

Description

Runs 1970s BASIC programs.

Details

Interprets and executes a subset of early (1975) Altair/Microsoft BASIC, plus some generalisations and extensions. Enables various programs of historical interest to be run in their primal form. A selection of public-domain examples are included.

Author(s)

Mike Lee

See Also

[RUN](#)

Examples

```
require(brassica)

## Not run:
# Load and run the 'Wumpus' program.
RUN("WUMPUS")

## End(Not run)
```

LIST *List BASIC Programs*

Description

Lists whichever BASIC program is loaded.

Usage

```
LIST()
```

Value

Returns a character vector, containing the complete listing of whichever BASIC program is in memory at the time.

See Also[NotRun](#)**Examples**

```
# List the current BASIC program.  
LIST()
```

LowerCode

Convert to Lower Case

Description

Converts a BASIC program to lower case, except for any string literals.

Usage

LowerCode(p)

Arguments

p A BASIC program listing, as a character vector.

Value

Returns the converted listing, as a character vector.

See Also[UpperCode](#)**Examples**

```
# Convert a program to lower case.  
LowerCode(c('10 LET X=X+1', '20 PRINT "Hello, World!"))
```

NotRun

Check BASIC Programs

Description

Returns a data frame of any BASIC program lines that have not yet been run. Used with repeated calls of RUN(), this provides a test of code syntax and accessibility.

Usage

```
NotRun(pretty = FALSE)
```

Arguments

`pretty` A single logical value. If TRUE, formatted output is printed before the data frame is returned invisibly. If FALSE (the default), the data frame is returned normally (visibly), without any other output being printed.

Value

Returns a data frame of any lines from the currently-loaded BASIC program that have not been successfully run in their entirety. Lines are listed with both their BASIC line numbers and the corresponding file line numbers of the source script. An appearance here might signify a problem with the line, or simply that one or more statements on it have not yet been executed.

See Also

[RUN](#)

Examples

```
# Peruse which lines have not yet been run.  
NotRun()
```

RUN

Run BASIC Programs

Description

Loads and runs BASIC programs.

Usage

```
RUN(program = NULL, ttx = 0, tty = 0, up = FALSE)
```

Arguments

| | |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| program | A character string, containing the name or file path of a BASIC program. Omitting this re-runs the currently-loaded program. |
| ttx | Aesthetic teletype option. A delay, of not more than 200 milliseconds, to be applied after printing each character. In practice, the actual delay will be this time plus however long it takes to flush the console, plus interpreter overheads. Depending on the model, a real teletype could manage around ten characters per second. Making this negative imposes no delay, but flushes the console after each completed line (not after each character). |
| tty | Aesthetic teletype option. A delay, of not more than 2000 milliseconds, to be applied after each line of printing. Making this negative imposes no delay, but still flushes the console after each completed line. |
| up | Aesthetic teletype option. Making this TRUE forces all BASIC output to upper case. |

Details

List of bundled example programs (from the references):

| | | |
|------------------------|--------------------------|-----------------------|
| <i>Camel</i> | by the Heath Users Group | (random walk) |
| <i>Chase</i> | by Mac Oglesby | (robots) |
| <i>Eliza</i> | by Jeff Shrager | (language processing) |
| <i>Flip</i> | by John S. James | (machine learning) |
| <i>Inkblot</i> | by Scott Costello | (projection) |
| <i>Life</i> | by Clark Baker | (cellular automaton) |
| <i>Maze</i> | by Richard Schaal | (depth-first search) |
| <i>Seabattle</i> | by Vincent Erickson | (monsters) |
| <i>Super Star Trek</i> | by Richard Leedon | (vector space) |
| <i>Wumpus</i> | by Gregory Yob | (graph topology) |

All of these are in the public domain.

Value

Returns an invisible NULL, after printing to standard output.

Note

Many BASIC programs ask for user input after printing a custom prompt. When `ttx` is greater than zero, some R sessions may incorrectly position the cursor at the beginning of the line, or on the next. Neither occurrence is fatal. Known to be affected: Windows R terminal ('R' and 'Rterm', but the 'Rgui' console is fine), Mac R console (but the Bash terminal is fine), RStudio. Additionally, double buffering, or the like, may interfere with the effect at higher speeds (Mac R console, again). Printing against the right-hand margin may result in additional blank lines of output, if the terminal applies hard-wrapping of its own.

References

1. David H. Ahl & Steve North, *BASIC Computer Games* (1978)
2. David H. Ahl & Steve North, *More BASIC Computer Games* (1979)

See Also

[LIST](#)

Examples

```
## Not run:
# Load and run 'Wumpus'.
RUN("wumpus")

# Load and run 'Chase', flushing the
# console after every line of output.
RUN("chase", -1)

# Load and run 'Camel', with full
# retro-style teletypewriter effects.
RUN("camel", 20, 300, TRUE)

# Load and run your program.
RUN("myprogram.bas")

# Re-run the last program
# (without re-loading it).
RUN()

## End(Not run)
```

UpperCode

Convert to Upper Case

Description

Converts a BASIC program to upper case, except for any string literals.

Usage

UpperCode(p)

Arguments

p A BASIC program listing, as a character vector.

Value

Returns the converted listing, as a character vector.

See Also

[LowerCode](#)

Examples

```
# Convert a program to upper case.  
UpperCode(c('10 let x=x+1', '20 print "Hello, World!"'))
```

Index

- * **BASIC**

- brassica-package, [2](#)

- * **interpreter**

- brassica-package, [2](#)

- * **package**

- brassica-package, [2](#)

brassica (brassica-package), [2](#)

brassica-package, [2](#)

LIST, [2](#), [6](#)

LowerCode, [3](#), [7](#)

NotRun, [3](#), [4](#)

RUN, [2](#), [4](#), [4](#)

UpperCode, [3](#), [6](#)