

Package ‘broom’

July 1, 2022

Type Package

Title Convert Statistical Objects into Tidy Tibbles

Version 1.0.0

Description Summarizes key information about statistical objects in tidy tibbles. This makes it easy to report results, create plots and consistently work with large numbers of models at once. Broom provides three verbs that each provide different types of information about a model. `tidy()` summarizes information about model components such as coefficients of a regression. `glance()` reports information about an entire model, such as goodness of fit measures like AIC and BIC. `augment()` adds information about individual observations to a dataset, such as fitted values or influence measures.

License MIT + file LICENSE

URL <https://broom.tidymodels.org/>, <https://github.com/tidymodels/broom>

BugReports <https://github.com/tidymodels/broom/issues>

Depends R (>= 3.1)

Imports backports, dplyr (>= 1.0.0), ellipsis, generics (>= 0.0.2), glue, methods, purrr, rlang, stringr, tibble (>= 3.0.0), tidyr (>= 1.0.0), ggplot2

Suggests AER, AUC, bbmle, betareg, biglm, binGroup, boot, btergm (>= 1.10.6), car, caret, cluster, cmprsk, coda, covr, drc, e1071, emmeans, epiR, ergm (>= 3.10.4), fixest (>= 0.9.0), gam (>= 1.15), gee, geopack, glmnet, glmnetUtils, gmm, Hmisc, irlba, interp, joineRML, Kendall, knitr, ks, Lahman, lavaan, leaps, lfe, lm.beta, lme4, lmodel2, lmtest (>= 0.9.38), lsmeans, maps, maptools, margins, MASS, Matrix, mclust, mediation, metafor, mfx, mgcv, mlogit, modeldata, modeltests, muhaz, multcomp, network, nnet, orcutt (>= 2.2), ordinal, plm, poLCA, psych, quantreg, rgeos, rmarkdown, robust, robustbase, rsample, sandwich, sp, spdep (>= 1.1), spatialreg, speedglm, spelling, survey, survival, systemfit, testthat (>= 2.1.0), tseries, vars, zoo

VignetteBuilder knitr

Config/Needs/website tidyverse/tidytemplate

Encoding UTF-8

RoxygenNote 7.2.0

Language en-US

Collate 'aaa-documentation-helper.R' 'null-and-default-tidiers.R'
 'aer-tidiers.R' 'auc-tidiers.R' 'base-tidiers.R'
 'bbmle-tidiers.R' 'betareg-tidiers.R' 'biglm-tidiers.R'
 'bingroup-tidiers.R' 'boot-tidiers.R' 'broom-package.R'
 'broom.R' 'btergm-tidiers.R' 'car-tidiers.R' 'caret-tidiers.R'
 'cluster-tidiers.R' 'cmprsk-tidiers.R' 'data-frame-tidiers.R'
 'deprecated-0-7-0.R' 'drc-tidiers.R' 'emmeans-tidiers.R'
 'epiR-tidiers.R' 'ergm-tidiers.R' 'fixest-tidiers.R'
 'gam-tidiers.R' 'geepack-tidiers.R'
 'glmnet-cv-glmnet-tidiers.R' 'glmnet-glmnet-tidiers.R'
 'gmm-tidiers.R' 'hmisc-tidiers.R' 'joinerml-tidiers.R'
 'kendall-tidiers.R' 'ks-tidiers.R' 'lavaan-tidiers.R'
 'leaps-tidiers.R' 'lfe-tidiers.R' 'list-irlba.R'
 'list-optim-tidiers.R' 'list-svd-tidiers.R' 'list-tidiers.R'
 'list-xyz-tidiers.R' 'lm-beta-tidiers.R' 'lmodel2-tidiers.R'
 'lmtest-tidiers.R' 'maps-tidiers.R' 'margins-tidiers.R'
 'mass-fitdistr-tidiers.R' 'mass-negbin-tidiers.R'
 'mass-polr-tidiers.R' 'mass-ridgelm-tidiers.R'
 'stats-lm-tidiers.R' 'mass-rlm-tidiers.R' 'matrix-tidiers.R'
 'mclust-tidiers.R' 'mediation-tidiers.R' 'metafor-tidiers.R'
 'mfx-tidiers.R' 'mgcv-tidiers.R' 'mlogit-tidiers.R'
 'muhaz-tidiers.R' 'multcomp-tidiers.R' 'nnet-tidiers.R'
 'nobs.R' 'orcutt-tidiers.R' 'ordinal-clm-tidiers.R'
 'ordinal-clmm-tidiers.R' 'plm-tidiers.R' 'polca-tidiers.R'
 'psych-tidiers.R' 'stats-nls-tidiers.R'
 'quantreg-nlrq-tidiers.R' 'quantreg-rq-tidiers.R'
 'quantreg-rqs-tidiers.R' 'robust-glmrob-tidiers.R'
 'robust-lmrob-tidiers.R' 'robustbase-glmrob-tidiers.R'
 'robustbase-lmrob-tidiers.R' 'sp-tidiers.R' 'spdep-tidiers.R'
 'speedglm-speedglm-tidiers.R' 'speedglm-speedlm-tidiers.R'
 'stats-anova-tidiers.R' 'stats-arima-tidiers.R'
 'stats-decompose-tidiers.R' 'stats-factanal-tidiers.R'
 'stats-glm-tidiers.R' 'stats-htest-tidiers.R'
 'stats-kmeans-tidiers.R' 'stats-loess-tidiers.R'
 'stats-mlm-tidiers.R' 'stats-prcomp-tidiers.R'
 'stats-smooth.spline-tidiers.R' 'stats-summary-lm-tidiers.R'
 'stats-time-series-tidiers.R' 'survey-tidiers.R'
 'survival-aareg-tidiers.R' 'survival-cch-tidiers.R'
 'survival-coxph-tidiers.R' 'survival-pyears-tidiers.R'
 'survival-survdiff-tidiers.R' 'survival-survexp-tidiers.R'
 'survival-survfit-tidiers.R' 'survival-survreg-tidiers.R'
 'systemfit-tidiers.R' 'tseries-tidiers.R' 'utilities.R'

'vars-tidiers.R' 'zoo-tidiers.R' 'zzz.R'

NeedsCompilation no

Author David Robinson [aut],

Alex Hayes [aut] (<<https://orcid.org/0000-0002-4985-5160>>),

Simon Couch [aut, cre] (<<https://orcid.org/0000-0001-5676-5107>>),

RStudio [cph, fnd],

Indrajeet Patil [ctb] (<<https://orcid.org/0000-0003-1995-6531>>),

Derek Chiu [ctb],

Matthieu Gomez [ctb],

Boris Demeshev [ctb],

Dieter Menne [ctb],

Benjamin Nutter [ctb],

Luke Johnston [ctb],

Ben Bolker [ctb],

Francois Briatte [ctb],

Jeffrey Arnold [ctb],

Jonah Gabry [ctb],

Luciano Selzer [ctb],

Gavin Simpson [ctb],

Jens Preussner [ctb],

Jay Hesselberth [ctb],

Hadley Wickham [ctb],

Matthew Lincoln [ctb],

Alessandro Gasparini [ctb],

Lukasz Komsta [ctb],

Frederick Novometsky [ctb],

Wilson Freitas [ctb],

Michelle Evans [ctb],

Jason Cory Brunson [ctb],

Simon Jackson [ctb],

Ben Whalley [ctb],

Karissa Whiting [ctb],

Yves Rosseel [ctb],

Michael Kuehn [ctb],

Jorge Cimentada [ctb],

Erle Holgersen [ctb],

Karl Dunkle Werner [ctb] (<<https://orcid.org/0000-0003-0523-7309>>),

Ethan Christensen [ctb],

Steven Pav [ctb],

Paul PJ [ctb],

Ben Schneider [ctb],

Patrick Kennedy [ctb],

Lily Medina [ctb],

Brian Fannin [ctb],

Jason Muhlenkamp [ctb],

Matt Lehman [ctb],

Bill Denney [ctb] (<<https://orcid.org/0000-0002-5759-428X>>),

Nic Crane [ctb],

Andrew Bates [ctb],
Vincent Arel-Bundock [ctb] (<<https://orcid.org/0000-0003-2042-7063>>),
Hideaki Hayashi [ctb],
Luis Tobalina [ctb],
Annie Wang [ctb],
Wei Yang Tham [ctb],
Clara Wang [ctb],
Abby Smith [ctb] (<<https://orcid.org/0000-0002-3207-0375>>),
Jasper Cooper [ctb] (<<https://orcid.org/0000-0002-8639-3188>>),
E Auden Krauska [ctb] (<<https://orcid.org/0000-0002-1466-5850>>),
Alex Wang [ctb],
Malcolm Barrett [ctb] (<<https://orcid.org/0000-0003-0299-5825>>),
Charles Gray [ctb] (<<https://orcid.org/0000-0002-9978-011X>>),
Jared Wilber [ctb],
Vilmantas Gegzna [ctb] (<<https://orcid.org/0000-0002-9500-5167>>),
Eduard Szoecs [ctb],
Frederik Aust [ctb] (<<https://orcid.org/0000-0003-4900-788X>>),
Angus Moore [ctb],
Nick Williams [ctb],
Marius Barth [ctb] (<<https://orcid.org/0000-0002-3421-6665>>),
Bruna Wundervald [ctb] (<<https://orcid.org/0000-0001-8163-220X>>),
Joyce Cahoon [ctb] (<<https://orcid.org/0000-0001-7217-4702>>),
Grant McDermott [ctb] (<<https://orcid.org/0000-0001-7883-8573>>),
Kevin Zarca [ctb],
Shiro Kuriwaki [ctb] (<<https://orcid.org/0000-0002-5687-2647>>),
Lukas Wallrich [ctb] (<<https://orcid.org/0000-0003-2121-5177>>),
James Martherus [ctb] (<<https://orcid.org/0000-0002-8285-3300>>),
Chuliang Xiao [ctb] (<<https://orcid.org/0000-0002-8466-9398>>),
Joseph Larmarange [ctb],
Max Kuhn [ctb],
Michal Bojanowski [ctb],
Hakon Malmedal [ctb],
Clara Wang [ctb],
Sergio Oller [ctb],
Luke Sonnet [ctb],
Jim Hester [ctb],
Cory Brunson [ctb],
Ben Schneider [ctb],
Bernie Gray [ctb] (<<https://orcid.org/0000-0001-9190-6032>>),
Mara Averick [ctb],
Aaron Jacobs [ctb],
Andreas Bender [ctb],
Sven Templer [ctb],
Paul-Christian Buerkner [ctb],
Matthew Kay [ctb],
Erwan Le Pennec [ctb],
Johan Junkka [ctb],
Hao Zhu [ctb],

Benjamin Soltoff [ctb],
 Zoe Wilkinson Saldana [ctb],
 Tyler Littlefield [ctb],
 Charles T. Gray [ctb],
 Shabbh E. Banks [ctb],
 Serina Robinson [ctb],
 Roger Bivand [ctb],
 Riinu Ots [ctb],
 Nicholas Williams [ctb],
 Nina Jakobsen [ctb],
 Michael Weylandt [ctb],
 Lisa Lendway [ctb],
 Karl Hailperin [ctb],
 Josue Rodriguez [ctb],
 Jenny Bryan [ctb],
 Chris Jarvis [ctb],
 Greg Macfarlane [ctb],
 Brian Mannakee [ctb],
 Drew Tyre [ctb],
 Shreyas Singh [ctb],
 Laurens Geffert [ctb],
 Hong Ooi [ctb],
 Henrik Bengtsson [ctb],
 Eduard Szocs [ctb],
 David Hugh-Jones [ctb],
 Matthieu Stigler [ctb],
 Hugo Tavares [ctb] (<<https://orcid.org/0000-0001-9373-2726>>),
 R. Willem Vervoort [ctb],
 Brenton M. Wiernik [ctb],
 Josh Yamamoto [ctb],
 Jasme Lee [ctb],
 Taren Sanders [ctb] (<<https://orcid.org/0000-0002-4504-6008>>),
 Ilaria Prosdocimi [ctb] (<<https://orcid.org/0000-0001-8565-094X>>),
 Daniel D. Sjoberg [ctb] (<<https://orcid.org/0000-0003-0862-2018>>)

Maintainer Simon Couch <simonpatrickcouch@gmail.com>

Repository CRAN

Date/Publication 2022-07-01 09:20:02 UTC

R topics documented:

augment.betamfx	10
augment.betareg	13
augment.clm	15
augment.coxph	17
augment.decomposed.ts	20
augment.drc	23
augment.factanal	25

augment.felm	27
augment.fixest	29
augment.gam	31
augment.glm	34
augment.glmRob	36
augment.glmrob	37
augment.htest	39
augment.ivreg	41
augment.kmeans	43
augment.lm	45
augment.lmRob	49
augment.lmrob	51
augment.loess	53
augment.Mclust	55
augment.mfx	57
augment.mjoint	60
augment.mlogit	63
augment.nlrq	65
augment.nls	66
augment.pam	68
augment.plm	70
augment.poLCA	72
augment.polr	75
augment.prcomp	77
augment.rlm	79
augment.rma	81
augment.rq	83
augment.rqs	85
augment.sarlm	88
augment.smooth.spline	90
augment.speedlm	91
augment.stl	93
augment.survreg	95
augment_columns	97
bootstrap	98
confint_tidy	99
data.frame_tidiers	100
durbinWatsonTest_tidiers	102
finish_glance	103
fix_data_frame	104
glance.aareg	104
glance.anova	106
glance.aov	107
glance.Arima	109
glance.betamfx	110
glance.betareg	112
glance.biglm	114
glance.binDesign	115

glance.cch	117
glance.clm	119
glance.clmm	121
glance.coefest	122
glance.coxph	124
glance.crr	127
glance.cv.glmnet	128
glance.drc	130
glance.ergm	132
glance.factanal	133
glance.felm	135
glance.ftdistr	137
glance.fixest	139
glance.Gam	140
glance.gam	142
glance.garch	143
glance.geeglm	144
glance.glm	146
glance.glmnet	148
glance.glmRob	149
glance.gmm	151
glance.ivreg	153
glance.kmeans	155
glance.lavaan	157
glance.lm	159
glance.lmodel2	161
glance.lmRob	163
glance.lmrob	165
glance.margins	166
glance.Mclust	168
glance.mfx	170
glance.mjoint	172
glance.mlogit	174
glance.muham	176
glance.multinom	177
glance.negbin	179
glance.nlrq	180
glance.nls	182
glance.orcutt	184
glance.pam	185
glance.plm	187
glance.poLCA	188
glance.polr	191
glance.pyears	192
glance.ridgelm	194
glance.rlm	196
glance.rma	197
glance.rq	199

glance.sarlm	201
glance.smooth.spline	203
glance.speedglm	204
glance.speedlm	206
glance.summary.lm	208
glance.survdiff	211
glance.survexp	212
glance.survfit	214
glance.survreg	216
glance.svyglm	218
glance.svyolr	220
glance.varest	221
glance_optim	223
levneTest_tidiers	224
list_tidiers	225
null_tidiers	226
sparse_tidiers	226
sp_tidiers	227
summary_tidiers	228
tidy.aareg	230
tidy.acf	231
tidy.anova	232
tidy.aov	234
tidy.aovlist	235
tidy.Arima	236
tidy.betamfx	238
tidy.betareg	240
tidy.biglm	241
tidy.binDesign	243
tidy.binWidth	245
tidy.boot	246
tidy.btergm	248
tidy.cch	250
tidy.cld	252
tidy.clm	253
tidy.clmm	255
tidy.coefstest	257
tidy.confint.glht	259
tidy.confusionMatrix	260
tidy.coxph	262
tidy.crr	264
tidy.cv.glmnet	266
tidy.density	268
tidy.dist	269
tidy.drc	270
tidy.emmGrid	271
tidy.epi.2by2	274
tidy.ergm	275

tidy.factanal	277
tidy.felm	278
tidy.fidistr	281
tidy.fixest	282
tidy.ftable	284
tidy.Gam	285
tidy.gam	286
tidy.garch	288
tidy.geeglm	289
tidy.glht	291
tidy.glm	293
tidy.glmnet	294
tidy.glmRob	296
tidy.glmrob	297
tidy.gmm	299
tidy.htest	301
tidy.ivreg	303
tidy.kappa	305
tidy.kde	306
tidy.Kendall	308
tidy.kmeans	309
tidy.lavaan	311
tidy.lm	312
tidy.lm.beta	315
tidy.lmodel2	317
tidy.lmRob	318
tidy.lmrob	319
tidy.lsmobj	321
tidy.manova	323
tidy.map	324
tidy.margins	326
tidy.Mclust	328
tidy.mediate	330
tidy.mfx	331
tidy.mjoint	334
tidy.mle2	336
tidy.mlm	338
tidy.mlogit	339
tidy.muhamad	341
tidy.multinom	342
tidy.negbin	343
tidy.nlrq	345
tidy.nls	346
tidy.numeric	348
tidy.orcutt	349
tidy.pairwise.htest	350
tidy.pam	351
tidy.plm	353

tidy.poLCA	355
tidy.polr	357
tidy.power.htest	359
tidy.pcomp	360
tidy.pyears	362
tidy.rcorr	364
tidy.ref.grid	366
tidy.regsubsets	368
tidy.ridgelm	369
tidy.rlm	371
tidy.rma	372
tidy.roc	373
tidy.rq	375
tidy.rqs	377
tidy.sarlm	379
tidy.spec	381
tidy.speedglm	382
tidy.speedlm	383
tidy.summary.glm	385
tidy.summary.lm	386
tidy.summary_emm	388
tidy.survdiff	390
tidy.survexp	392
tidy.survfit	393
tidy.survreg	395
tidy.svyglm	397
tidy.svyolr	398
tidy.systemfit	399
tidy.table	401
tidy.ts	402
tidy.TukeyHSD	403
tidy.varest	405
tidy.zoo	406
tidy_irlba	408
tidy_optim	410
tidy_svd	411
tidy_xyz	413

Index**415**

augment.betamfx

Augment data with information from a(n) betamfx object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures) that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'betamfx'
augment(
  x,
  data = model.frame(x$fit),
  newdata = NULL,
  type.predict = c("response", "link", "precision", "variance", "quantile"),
  type.residuals = c("sweighted2", "deviance", "pearson", "response", "weighted",
    "sweighted"),
  ...
)
```

Arguments

<code>x</code>	A <code>betamfx</code> object.
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>Augment</code> will report information such as influence and

	cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Character indicating type of prediction to use. Passed to the type argument of <code>betareg::predict.betareg()</code> . Defaults to "response".
type.residuals	Character indicating type of residuals to use. Passed to the type argument of <code>betareg::residuals.betareg()</code> . Defaults to "sweighted2".
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

This augment method wraps `augment.betareg()` for `mfx::betamfx()` objects.

Value

A `tibble::tibble()` with columns:

<code>.cooksd</code>	Cooks distance.
<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

`augment.betareg()`, `mfx::betamfx()`

Other mfx tidiers: `augment.mfx()`, `glance.betamfx()`, `glance.mfx()`, `tidy.betamfx()`, `tidy.mfx()`

Examples

```
library(mfx)

# Simulate some data
set.seed(12345)
n = 1000
x = rnorm(n)

# Beta outcome
```

```

y = rbeta(n, shape1 = plogis(1 + 0.5 * x), shape2 = (abs(0.2*x)))
# Use Smithson and Verkuilen correction
y = (y*(n-1)+0.5)/n

d = data.frame(y,x)
mod_betamfx = betamfx(y ~ x | x, data = d)

tidy(mod_betamfx, conf.int = TRUE)

# Compare with the naive model coefficients of the equivalent betareg call (not run)
# tidy(betamfx(y ~ x | x, data = d), conf.int = TRUE)

augment(mod_betamfx)
glance(mod_betamfx)

```

augment.betareg

Augment data with information from a(n) betareg object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'betareg'
augment(
  x,
  data = model.frame(x),
  newdata = NULL,
  type.predict,
  type.residuals,
  ...
)
```

Arguments

x	A betareg object produced by a call to <code>betareg::betareg()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Character indicating type of prediction to use. Passed to the type argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
type.residuals	Character indicating type of residuals to use. Passed to the type argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For additional details on Cook's distance, see `stats::cooks.distance()`.

Value

A `tibble::tibble()` with columns:

.cooksd	Cooks distance.
.fitted	Fitted or predicted value.
.resid	The difference between observed and fitted values.

See Also

[augment\(\)](#), [betareg::betareg\(\)](#)

Examples

```
# load libraries for models and data
library(betareg)

# load dats
data("GasolineYield", package = "betareg")

# fit model
mod <- betareg(yield ~ batch + temp, data = GasolineYield)

mod

# summarize model fit with tidiers
tidy(mod)
tidy(mod, conf.int = TRUE)
tidy(mod, conf.int = TRUE, conf.level = .99)

augment(mod)

glance(mod)
```

augment.clm

Augment data with information from a(n) clm object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether data or newdata is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'clm'
augment(
  x,
  data = model.frame(x),
  newdata = NULL,
  type.predict = c("prob", "class"),
  ...
)
```

Arguments

x	A <code>clm</code> object returned from <code>ordinal::clm()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to <code>NULL</code> , indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Which type of prediction to compute, either "prob" or "class", passed to <code>ordinal::predict.clm()</code> . Defaults to "prob".
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored.

- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

See Also

`tidy`, `ordinal::clm()`, `ordinal::predict.clm()`

Other ordinal tidiers: `augment.polr()`, `glance.clmm()`, `glance.clm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clmm()`, `tidy.clm()`, `tidy.polr()`, `tidy.svyolr()`

Examples

```
# load libraries for models and data
library(ordinal)

# fit model
fit <- clm(rating ~ temp * contact, data = wine)

# summarize model fit with tidiers
tidy(fit)
tidy(fit, conf.int = TRUE, conf.level = 0.9)
tidy(fit, conf.int = TRUE, conf.type = "Wald", exponentiate = TRUE)

glance(fit)
augment(fit, type.predict = "prob")
augment(fit, type.predict = "class")

# ...and again with another model specification
fit2 <- clm(rating ~ temp, nominal = ~contact, data = wine)

tidy(fit2)
glance(fit2)
```

augment.coxph

Augment data with information from a(n) coxph object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome

variable used to fit the model is not included in newdata, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether data or newdata is given. This is because there is often information associated with training observations (such as influences or related measures) that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'coxph'
augment(
  x,
  data = NULL,
  newdata = NULL,
  type.predict = "lp",
  type.residuals = "martingale",
  ...
)
```

Arguments

<code>x</code>	A coxph object returned from <code>survival::coxph()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
<code>type.predict</code>	Character indicating type of prediction to use. Passed to the type argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
<code>type.residuals</code>	Character indicating type of residuals to use. Passed to the type argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.

- ...
- Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.

See Also

`stats::na.action`

`augment()`, `survival::coxph()`

Other coxph tidiers: `glance.coxph()`, `tidy.coxph()`

Other survival tidiers: `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# fit model
cfit <- coxph(Surv(time, status) ~ age + sex, lung)

# summarize model fit with tidiers
```

```

tidy(cfit)
tidy(cfit, exponentiate = TRUE)

lp <- augment(cfit, lung)
risks <- augment(cfit, lung, type.predict = "risk")
expected <- augment(cfit, lung, type.predict = "expected")

glance(cfit)

# also works on clogit models
resp <- levels(logan$occupation)
n <- nrow(logan)
indx <- rep(1:n, length(resp))
logan2 <- data.frame(
  logan[indx, ],
  id = indx,
  tocc = factor(rep(resp, each = n))
)

logan2$case <- (logan2$occupation == logan2$tocc)

cl <- clogit(case ~ tocc + tocc:education + strata(id), logan2)

tidy(cl)
glance(cl)

library(ggplot2)

ggplot(lp, aes(age, .fitted, color = sex)) +
  geom_point()

ggplot(risks, aes(age, .fitted, color = sex)) +
  geom_point()

ggplot(expected, aes(time, .fitted, color = sex)) +
  geom_point()

```

augment.decomposed.ts *Augment data with information from a(n) decomposed.ts object*

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object.

Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'decomposed.ts'
augment(x, ...)
```

Arguments

<code>x</code>	A <code>decomposed.ts</code> object returned from <code>stats::decompose()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautious note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble` with one row for each observation in the original times series:

<code>.seasonal</code>	The seasonal component of the decomposition.
<code>.trend</code>	The trend component of the decomposition.
<code>.remainder</code>	The remainder, or "random" component of the decomposition.
<code>.weight</code>	The final robust weights (<code>stl</code> only).
<code>.seasadj</code>	The seasonally adjusted (or "deseasonalised") series.

See Also

[augment\(\)](#), [stats::decompose\(\)](#)

Other decompose tidiers: [augment.stl\(\)](#)

Examples

```
# time series of temperatures in Nottingham, 1920-1939:
nottem

# perform seasonal decomposition on the data with both decompose
# and stl:
d1 <- decompose(nottem)
d2 <- stl(nottem, s.window = "periodic", robust = TRUE)

# compare the original series to its decompositions.

cbind(
  tidy(nottem), augment(d1),
  augment(d2)
)

# visually compare seasonal decompositions in tidy data frames.

library(tibble)
library(dplyr)
library(tidyr)
library(ggplot2)

decomps <- tibble(
  # turn the ts objects into data frames.
  series = list(as.data.frame(nottem), as.data.frame(nottem)),
  # add the models in, one for each row.
  decomp = c("decompose", "stl"),
  model = list(d1, d2)
) %>%
  rowwise() %>%
  # pull out the fitted data using broom::augment.
  mutate(augment = list(broom::augment(model))) %>%
  ungroup() %>%
  # unnest the data frames into a tidy arrangement of
  # the series next to its seasonal decomposition, grouped
  # by the method (stl or decompose).
  group_by(decomp) %>%
  unnest(c(series, augment)) %>%
  mutate(index = 1:n()) %>%
  ungroup() %>%
  select(decomp, index, x, adjusted = .seasadj)

ggplot(decomps) +
  geom_line(aes(x = index, y = x), colour = "black") +
  geom_line(aes(
```

```

    x = index, y = adjusted, colour = decomp,
    group = decomp
  ))

```

 augment.drc

Augment data with information from a(n) drc object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```

## S3 method for class 'drc'
augment(
  x,
  data = NULL,
  newdata = NULL,
  se_fit = FALSE,
  conf.int = FALSE,
  conf.level = 0.95,
  ...
)

```

Arguments

x	A drc object produced by a call to <code>drc::drm()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
se_fit	Logical indicating whether or not a <code>.se.fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to FALSE.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.cooks</code>	Cooks distance.
<code>.fitted</code>	Fitted or predicted value.
<code>.lower</code>	Lower bound on interval for fitted values.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.
<code>.upper</code>	Upper bound on interval for fitted values.

See Also

`augment()`, `drc::drm()`

Other drc tidiers: `glance.drc()`, `tidy.drc()`

Examples

```
# load libraries for models and data
library(drc)

# fit model
mod <- drm(dead / total ~ conc, type,
  weights = total, data = selenium, fct = LL.2(), type = "binomial"
)

# summarize model fit with tidiers
tidy(mod)
tidy(mod, conf.int = TRUE)

glance(mod)

augment(mod, selenium)
```

`augment.factanal`*Augment data with information from a(n) factanal object*

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'factanal'
augment(x, data, ...)
```

Arguments

<code>x</code>	A factanal object created by <code>stats::factanal()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

When data is not supplied `augment.factanal` returns one row for each observation, with a factor score column added for each factor `X`, (`.fsX`). This is because `stats::factanal()`, unlike other stats methods like `stats::lm()`, does not retain the original data.

When data is supplied, `augment.factanal` returns one row for each observation, with a factor score column added for each factor `X`, (`.fsX`).

See Also

`augment()`, `stats::factanal()`

Other factanal tidiers: `glance.factanal()`, `tidy.factanal()`

augment.felm

Augment data with information from a(n) felm object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'felm'
augment(x, data = model.frame(x), ...)
```

Arguments

<code>x</code>	A <code>felm</code> object returned from <code>lfe::felm()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

`augment()`, `lfe::felm()`

Other `felm` tidiers: `tidy.felm()`

Examples

```
# load libraries for models and data
library(lfe)

# use built-in `airquality` dataset
head(airquality)

# no FEs; same as lm()
est0 <- felm(Ozone ~ Temp + Wind + Solar.R, airquality)

# summarize model fit with tidiers
tidy(est0)
augment(est0)

# add month fixed effects
est1 <- felm(Ozone ~ Temp + Wind + Solar.R | Month, airquality)

# summarize model fit with tidiers
tidy(est1)
tidy(est1, fe = TRUE)
augment(est1)
glance(est1)

# the "se.type" argument can be used to switch out different standard errors
# types on the fly. In turn, this can be useful exploring the effect of
# different error structures on model inference.
```

```

tidy(est1, se.type = "iid")
tidy(est1, se.type = "robust")

# add clustered SEs (also by month)
est2 <- feIm(Ozone ~ Temp + Wind + Solar.R | Month | 0 | Month, airquality)

# summarize model fit with tidiers
tidy(est2, conf.int = TRUE)
tidy(est2, conf.int = TRUE, se.type = "cluster")
tidy(est2, conf.int = TRUE, se.type = "robust")
tidy(est2, conf.int = TRUE, se.type = "iid")

```

augment.fixest

Augment data with information from a(n) fixest object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'fixest'
augment(
  x,
  data = NULL,
  newdata = NULL,
  type.predict = c("link", "response"),
  type.residuals = c("response", "deviance", "pearson", "working"),
  ...
)
```

Arguments

x	A <code>fixest</code> object returned from any of the <code>fixest</code> estimators
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>augment</code> will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
type.predict	Passed to <code>predict.fixest</code> type argument. Defaults to "link" (like <code>predict.glm</code>).
type.residuals	Passed to <code>predict.fixest</code> type argument. Defaults to "response" (like <code>residuals.lm</code> , but unlike <code>residuals.glm</code>).
...	Additional arguments passed to <code>summary</code> and <code>confint</code> . Important arguments are <code>se</code> and <code>cluster</code> . Other arguments are <code>dof</code> , <code>exact_dof</code> , <code>forceCovariance</code> , and <code>keepBounded</code> . See summary.fixest .

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

Note

Important note: `fixest` models do not include a copy of the input data, so you must provide it manually.

`augment.fixest` only works for `fixest::feols()`, `fixest::feglm()`, and `fixest::femlm()` models. It does not work with results from `fixest::fenegbin()`, `fixest::feNmlm()`, or `fixest::fepois()`.

See Also

`augment()`, `fixest::feglm()`, `fixest::femlm()`, `fixest::feols()`

Other `fixest` tidiers: `tidy.fixest()`

Examples

```
# load libraries for models and data
library(fixest)

gravity <-
  feols(
    log(Euros) ~ log(dist_km) | Origin + Destination + Product + Year, trade
  )

tidy(gravity)
glance(gravity)
augment(gravity, trade)

# to get robust or clustered SEs, users can either:

# 1) specify the arguments directly in the `tidy()` call
tidy(gravity, conf.int = TRUE, cluster = c("Product", "Year"))

tidy(gravity, conf.int = TRUE, se = "threeway")

# 2) or, feed tidy() a summary.fixest object that has already accepted
# these arguments

gravity_summ <- summary(gravity, cluster = c("Product", "Year"))

tidy(gravity_summ, conf.int = TRUE)

# approach (1) is preferred.
```

augment.gam

Augment data with information from a(n) gam object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether data or newdata is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'gam'
augment(
  x,
  data = model.frame(x),
  newdata = NULL,
  type.predict,
  type.residuals,
  ...
)
```

Arguments

<code>x</code>	A gam object returned from a call to <code>mgcv::gam()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>type.predict</code>	Character indicating type of prediction to use. Passed to the <code>type</code> argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
<code>type.residuals</code>	Character indicating type of residuals to use. Passed to the <code>type</code> argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

For additional details on Cook's distance, see [stats::cooks.distance\(\)](#).

Value

A `tibble::tibble()` with columns:

<code>.cooks_d</code>	Cooks distance.
<code>.fitted</code>	Fitted or predicted value.
<code>.hat</code>	Diagonal of the hat matrix.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se_fit</code>	Standard errors of fitted values.
<code>.sigma</code>	Estimated residual standard deviation when corresponding observation is dropped from model.

See Also

[augment\(\)](#), [mgcv::gam\(\)](#)

Examples

```
# load libraries for models and data
library(mgcv)

# fit model
g <- gam(mpg ~ s(hp) + am + qsec, data = mtcars)

# summarize model fit with tidiers
tidy(g)
tidy(g, parametric = TRUE)
glance(g)
augment(g)
```

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'glm'
augment(
  x,
  data = model.frame(x),
  newdata = NULL,
  type.predict = c("link", "response", "terms"),
  type.residuals = c("deviance", "pearson"),
  se_fit = FALSE,
  ...
)
```

Arguments

x	A glm object returned from <code>stats::glm()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Passed to <code>stats::predict.glm()</code> type argument. Defaults to "link".
type.residuals	Passed to <code>stats::residuals.glm()</code> and to <code>stats::rstandard.glm()</code> type arguments. Defaults to "deviance".
se_fit	Logical indicating whether or not a <code>.se.fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

If the weights for any of the observations in the model are 0, then columns ".infl" and ".hat" in the result will be 0 for those observations.

A `.resid` column is not calculated when data is specified via the `newdata` argument.

Value

A `tibble::tibble()` with columns:

<code>.cooks</code>	Cooks distance.
<code>.fitted</code>	Fitted or predicted value.
<code>.hat</code>	Diagonal of the hat matrix.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.
<code>.sigma</code>	Estimated residual standard deviation when corresponding observation is dropped from model.
<code>.std.resid</code>	Standardised residuals.

See Also

`stats::glm()`

Other lm tidiers: `augment.lm()`, `glance.glm()`, `glance.lm()`, `glance.summary.lm()`, `glance.svyglm()`, `tidy.glm()`, `tidy.lm.beta()`, `tidy.lm()`, `tidy.mlm()`, `tidy.summary.lm()`

augment.glmRob

Augment data with information from a(n) glmRob object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'glmRob'
augment(x, ...)
```

Arguments

<code>x</code>	Unused.
<code>...</code>	Unused.

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'glmrob'
augment(
  x,
  data = model.frame(x),
  newdata = NULL,
  type.predict = c("link", "response"),
  type.residuals = c("deviance", "pearson"),
  se_fit = FALSE,
  ...
)
```

Arguments

x	A <code>glmrob</code> object returned from <code>robustbase::glmrob()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Character indicating type of prediction to use. Passed to the type argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
type.residuals	Character indicating type of residuals to use. Passed to the type argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.
se_fit	Logical indicating whether or not a <code>.se.fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

`robustbase::glmrob()`

Other robustbase tidiers: `augment.lmrob()`, `glance.lmrob()`, `tidy.glmrob()`, `tidy.lmrob()`

Examples

```

if (requireNamespace("robustbase", quietly = TRUE)) {

# load libraries for models and data
library(robustbase)

data(coleman)
set.seed(0)

m <- lmrob(Y ~ ., data = coleman)
tidy(m)
augment(m)
glance(m)

data(carrots)

Rfit <- glmrob(cbind(success, total - success) ~ logdose + block,
  family = binomial, data = carrots, method = "Mqle",
  control = glmrobMqle.control(tcc = 1.2)
)

tidy(Rfit)
augment(Rfit)

}

```

augment.htest

Augment data with information from a(n) htest object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'htest'
augment(x, ...)
```

Arguments

`x` An `htest` objected, such as those created by `stats::cor.test()`, `stats::t.test()`, `stats::wilcox.test()`, `stats::chisq.test()`, etc.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

See `stats::chisq.test()` for more details on how residuals are computed.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>.observed</code>	Observed count.
<code>.prop</code>	Proportion of the total.
<code>.row.prop</code>	Row proportion (2 dimensions table only).
<code>.col.prop</code>	Column proportion (2 dimensions table only).
<code>.expected</code>	Expected count under the null hypothesis.
<code>.resid</code>	Pearson residuals.
<code>.std.resid</code>	Standardized residual.

See Also

`augment()`, `stats::chisq.test()`

Other `htest` tidiers: `tidy.htest()`, `tidy.pairwise.htest()`, `tidy.power.htest()`

Examples

```
tt <- t.test(rnorm(10))

tidy(tt)

# the glance output will be the same for each of the below tests
glance(tt)

tt <- t.test(mpg ~ am, data = mtcars)

tidy(tt)

wt <- wilcox.test(mpg ~ am, data = mtcars, conf.int = TRUE, exact = FALSE)

tidy(wt)

ct <- cor.test(mtcars$wt, mtcars$mpg)

tidy(ct)

chit <- chisq.test(xtabs(Freq ~ Sex + Class, data = as.data.frame(Titanic)))

tidy(chit)
augment(chit)
```

augment.ivreg

Augment data with information from a(n) ivreg object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'ivreg'
augment(x, data = model.frame(x), newdata = NULL, ...)
```

Arguments

<code>x</code>	An ivreg object created by a call to <code>AER::ivreg()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

This tidier currently only supports `ivreg`-class objects outputted by the `AER` package. The `ivreg` package also outputs objects of class `ivreg`, and will be supported in a later release.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also[augment\(\)](#), [AER::ivreg\(\)](#)Other ivreg tidiers: [glance.ivreg\(\)](#), [tidy.ivreg\(\)](#)**Examples**

```
# load libraries for models and data
library(AER)

# load data
data("CigarettesSW", package = "AER")

# fit model
ivr <- ivreg(
  log(packs) ~ income | population,
  data = CigarettesSW,
  subset = year == "1995"
)

# summarize model fit with tidiers
tidy(ivr)
tidy(ivr, conf.int = TRUE)
tidy(ivr, conf.int = TRUE, instruments = TRUE)

augment(ivr)
augment(ivr, data = CigarettesSW)
augment(ivr, newdata = CigarettesSW)

glance(ivr)
```

`augment.kmeans`*Augment data with information from a(n) kmeans object*

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether data or newdata is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'kmeans'
augment(x, data, ...)
```

Arguments

- | | |
|------|---|
| x | A kmeans object created by <code>stats::kmeans()</code> . |
| data | A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data. |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with columns:

.cluster	Cluster assignment.
----------	---------------------

See Also[augment\(\)](#), [stats::kmeans\(\)](#)Other kmeans tidiers: [glance.kmeans\(\)](#), [tidy.kmeans\(\)](#)**Examples**

```
library(cluster)
library(modeldata)
library(dplyr)

data(hpc_data)

x <- hpc_data[, 2:5]

fit <- pam(x, k = 4)

tidy(fit)
glance(fit)
augment(fit, x)
```

`augment.lm`*Augment data with information from a(n) lm object*

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a [tibble::tibble](#) with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do

not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'lm'
augment(
  x,
  data = model.frame(x),
  newdata = NULL,
  se_fit = FALSE,
  interval = c("none", "confidence", "prediction"),
  ...
)
```

Arguments

<code>x</code>	An <code>lm</code> object created by <code>stats::lm()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>se_fit</code>	Logical indicating whether or not a <code>.se.fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to <code>FALSE</code> .
<code>interval</code>	Character indicating the type of confidence interval columns to be added to the augmented output. Passed on to <code>predict()</code> and defaults to <code>"none"</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Some unusual `lm` objects, such as `r1m` from MASS, may omit `.cooks` and `.std.resid`. `gam` from `mgcv` omits `.sigma`.

When `newdata` is supplied, only returns `.fitted`, `.resid` and `.se.fit` columns.

Value

A `tibble::tibble()` with columns:

<code>.cooks</code>	Cooks distance.
<code>.fitted</code>	Fitted or predicted value.
<code>.hat</code>	Diagonal of the hat matrix.
<code>.lower</code>	Lower bound on interval for fitted values.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.
<code>.sigma</code>	Estimated residual standard deviation when corresponding observation is dropped from model.
<code>.std.resid</code>	Standardised residuals.
<code>.upper</code>	Upper bound on interval for fitted values.

See Also

[stats::na.action](#)

[augment\(\)](#), [stats::predict.lm\(\)](#)

Other `lm` tidiers: [augment.glm\(\)](#), [glance.glm\(\)](#), [glance.lm\(\)](#), [glance.summary.lm\(\)](#), [glance.svyglm\(\)](#), [tidy.glm\(\)](#), [tidy.lm.beta\(\)](#), [tidy.lm\(\)](#), [tidy.mlm\(\)](#), [tidy.summary.lm\(\)](#)

Examples

```
library(ggplot2)
library(dplyr)

mod <- lm(mpg ~ wt + qsec, data = mtcars)

tidy(mod)
glance(mod)

# coefficient plot
d <- tidy(mod, conf.int = TRUE)
```

```

ggplot(d, aes(estimate, term, xmin = conf.low, xmax = conf.high, height = 0)) +
  geom_point() +
  geom_vline(xintercept = 0, lty = 4) +
  geom_errorbarh()

# aside: There are tidy() and glance() methods for lm.summary objects too.
# this can be useful when you want to conserve memory by converting large lm
# objects into their leaner summary.lm equivalents.
s <- summary(mod)
tidy(s, conf.int = TRUE)
glance(s)

augment(mod)
augment(mod, mtcars, interval = "confidence")

# predict on new data
newdata <- mtcars %>%
  head(6) %>%
  mutate(wt = wt + 1)
augment(mod, newdata = newdata)

# ggplot2 example where we also construct 95% prediction interval

# simpler bivariate model since we're plotting in 2D
mod2 <- lm(mpg ~ wt, data = mtcars)

au <- augment(mod2, newdata = newdata, interval = "prediction")

ggplot(au, aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted)) +
  geom_ribbon(aes(ymin = .lower, ymax = .upper), col = NA, alpha = 0.3)

# predict on new data without outcome variable. Output does not include .resid
newdata <- newdata %>%
  select(-mpg)

augment(mod, newdata = newdata)

au <- augment(mod, data = mtcars)

ggplot(au, aes(.hat, .std.resid)) +
  geom_vline(size = 2, colour = "white", xintercept = 0) +
  geom_hline(size = 2, colour = "white", yintercept = 0) +
  geom_point() +
  geom_smooth(se = FALSE)

plot(mod, which = 6)

ggplot(au, aes(.hat, .cooks)) +
  geom_vline(xintercept = 0, colour = NA) +
  geom_abline(slope = seq(0, 3, by = 0.5), colour = "white") +

```



```

    geom_smooth(se = FALSE) +
    geom_point()

# column-wise models
a <- matrix(rnorm(20), nrow = 10)
b <- a + rnorm(length(a))
result <- lm(b ~ a)

tidy(result)

```

augment.lmRob

Augment data with information from a(n) lmRob object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```

## S3 method for class 'lmRob'
augment(x, data = model.frame(x), newdata = NULL, ...)

```

Arguments

x	A <code>lmRob</code> object returned from <code>robust::lmRob()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

See Also

`robust::lmRob()`

Other robust tidiers: `glance.glmRob()`, `glance.lmRob()`, `tidy.glmRob()`, `tidy.lmRob()`

Examples

```
# load modeling library
library(robust)

# fit model
m <- lmRob(mpg ~ wt, data = mtcars)

# summarize model fit with tidiers
tidy(m)
augment(m)
glance(m)
```

augment.lmrob

Augment data with information from a(n) lmrob object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'lmrob'
augment(x, data = model.frame(x), newdata = NULL, se_fit = FALSE, ...)
```

Arguments

<code>x</code>	A <code>lmrob</code> object returned from <code>robustbase::lmrob()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>se_fit</code>	Logical indicating whether or not a <code>.se_fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to <code>FALSE</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

`robustbase::lmrob()`

Other robustbase tidiers: `augment.glmrob()`, `glance.lmrob()`, `tidy.glmrob()`, `tidy.lmrob()`

Examples

```
if (requireNamespace("robustbase", quietly = TRUE)) {

# load libraries for models and data
library(robustbase)

data(coleman)
set.seed(0)

m <- lmrob(Y ~ ., data = coleman)
tidy(m)
augment(m)
glance(m)

data(carrots)
```

```
Rfit <- glmrob(cbind(success, total - success) ~ logdose + block,
  family = binomial, data = carrots, method = "Mqle",
  control = glmrobMqle.control(tcc = 1.2)
)

tidy(Rfit)
augment(Rfit)

}
```

augment.loess	<i>Tidy a(n) loess object</i>
---------------	-------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'loess'
augment(x, data = model.frame(x), newdata = NULL, se_fit = FALSE, ...)
```

Arguments

x	A loess objects returned by <code>stats::loess()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
se_fit	Logical indicating whether or not a <code>.se.fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Note that loess objects by default will not predict on data outside of a bounding hypercube defined by the training data unless the original loess object was fit with `control = loess.control(surface = "direct")`. See `stats::predict.loess()` for details.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.

See Also

`stats::na.action`
`augment()`, `stats::loess()`, `stats::predict.loess()`

Examples

```
lo <- loess(
  mpg ~ hp + wt,
  mtcars,
  control = loess.control(surface = "direct")
)

augment(lo)

# with all columns of original data
augment(lo, mtcars)

# with a new dataset
augment(lo, newdata = head(mtcars))
```

augment.Mclust

Augment data with information from a(n) Mclust object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'Mclust'
augment(x, data = NULL, ...)
```

Arguments

<code>x</code>	An Mclust object return from <code>mclust::Mclust()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.class</code>	Predicted class.
<code>.uncertainty</code>	The uncertainty associated with the classification. Equal to one minus the model class probability.

See Also

`augment()`, `mclust::Mclust()`

Other mclust tidiers: `tidy.Mclust()`

Examples

```
# load library for models and data
library(mclust)

# load data manipulation libraries
library(dplyr)
library(tibble)
library(purrr)
library(tidyr)

set.seed(27)

centers <- tibble(
  cluster = factor(1:3),
  # number points in each cluster
  num_points = c(100, 150, 50),
  # x1 coordinate of cluster center
  x1 = c(5, 0, -3),
  # x2 coordinate of cluster center
  x2 = c(-1, 1, -2)
)

points <- centers %>%
  mutate(
    x1 = map2(num_points, x1, rnorm),
```



```
      x2 = map2(num_points, x2, rnorm)
    ) %>%
  select(-num_points, -cluster) %>%
  unnest(c(x1, x2))

# fit model
m <- Mclust(points)

# summarize model fit with tidiers
tidy(m)
augment(m, points)
glance(m)
```

`augment.mfx`*Augment data with information from a(n) mfx object*

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures) that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'mfx'
augment(
  x,
  data = model.frame(x$fit),
  newdata = NULL,
  type.predict = c("link", "response", "terms"),
  type.residuals = c("deviance", "pearson"),
  se_fit = FALSE,
  ...
)

## S3 method for class 'logitmfx'
augment(
  x,
  data = model.frame(x$fit),
  newdata = NULL,
  type.predict = c("link", "response", "terms"),
  type.residuals = c("deviance", "pearson"),
  se_fit = FALSE,
  ...
)

## S3 method for class 'negbinmfx'
augment(
  x,
  data = model.frame(x$fit),
  newdata = NULL,
  type.predict = c("link", "response", "terms"),
  type.residuals = c("deviance", "pearson"),
  se_fit = FALSE,
  ...
)

## S3 method for class 'poissonmfx'
augment(
  x,
  data = model.frame(x$fit),
  newdata = NULL,
  type.predict = c("link", "response", "terms"),
  type.residuals = c("deviance", "pearson"),
  se_fit = FALSE,
  ...
)

## S3 method for class 'probitmfx'
augment(
  x,
```

```

  data = model.frame(x$fit),
  newdata = NULL,
  type.predict = c("link", "response", "terms"),
  type.residuals = c("deviance", "pearson"),
  se_fit = FALSE,
  ...
)

```

Arguments

x	A <code>logitmfx</code> , <code>negbinmfx</code> , <code>poissonmfx</code> , or <code>probitmfx</code> object. (Note that <code>betamfx</code> objects receive their own set of tidiers.)
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
type.predict	Passed to <code>stats::predict.glm()</code> type argument. Defaults to "link".
type.residuals	Passed to <code>stats::residuals.glm()</code> and to <code>stats::rstandard.glm()</code> type arguments. Defaults to "deviance".
se_fit	Logical indicating whether or not a <code>.se.fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to <code>FALSE</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

This generic `augment` method wraps `augment.glm()` for applicable objects from the `mfx` package.

Value

A `tibble::tibble()` with columns:

<code>.cooks</code>	Cooks distance.
<code>.fitted</code>	Fitted or predicted value.

.hat	Diagonal of the hat matrix.
.resid	The difference between observed and fitted values.
.se.fit	Standard errors of fitted values.
.sigma	Estimated residual standard deviation when corresponding observation is dropped from model.
.std.resid	Standardised residuals.

See Also

`augment.glm()`, `mfxf::logitmfx()`, `mfxf::negbinmfx()`, `mfxf::poissonmfx()`, `mfxf::probitmfx()`

Other mfx tidiers: `augment.betamfx()`, `glance.betamfx()`, `glance.mfx()`, `tidy.betamfx()`, `tidy.mfx()`

Examples

```
# load libraries for models and data
library(mfx)

# get the marginal effects from a logit regression
mod_logmfx <- logitmfx(am ~ cyl + hp + wt, atmean = TRUE, data = mtcars)

tidy(mod_logmfx, conf.int = TRUE)

# compare with the naive model coefficients of the same logit call
tidy(
  glm(am ~ cyl + hp + wt, family = binomial, data = mtcars), conf.int = TRUE
)

augment(mod_logmfx)
glance(mod_logmfx)

# another example, this time using probit regression
mod_probmfx <- probitmfx(am ~ cyl + hp + wt, atmean = TRUE, data = mtcars)

tidy(mod_probmfx, conf.int = TRUE)
augment(mod_probmfx)
glance(mod_probmfx)
```

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'mjoint'
augment(x, data = x$data, ...)
```

Arguments

<code>x</code>	An <code>mjoint</code> object returned from <code>joineRML::mjoint()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are:

- tidy() methods will warn when supplied an exponentiate argument if it will be ignored.
- augment() methods will warn when supplied a newdata argument if it will be ignored.

Details

See `joineRML::fitted.mjoint()` and `joineRML::residuals.mjoint()` for more information on the difference between population-level and individual-level fitted values and residuals.

If fitting a joint model with a single longitudinal process, make sure you are using a named list to define the formula for the fixed and random effects of the longitudinal submodel.

Value

A `tibble::tibble()` with one row for each original observation with addition columns:

<code>.fitted_j_0</code>	population-level fitted values for the j-th longitudinal process
<code>.fitted_j_1</code>	individuals-level fitted values for the j-th longitudinal process
<code>.resid_j_0</code>	population-level residuals for the j-th longitudinal process
<code>.resid_j_1</code>	individual-level residuals for the j-th longitudinal process

Examples

```
# broom only skips running these examples because the example models take a
# while to generatethey should run just fine, though!
## Not run:
```

```
# load libraries for models and data
library(joineRML)
```

```
# fit a joint model with bivariate longitudinal outcomes
data(heart.valve)
```

```
hvd <- heart.valve[!is.na(heart.valve$log.grad) &
  !is.na(heart.valve$log.lvmi) &
  heart.valve$num <= 50, ]
```

```
fit <- mjoint(
  formLongFixed = list(
    "grad" = log.grad ~ time + sex + hs,
    "lvmi" = log.lvmi ~ time + sex
  ),
  formLongRandom = list(
    "grad" = ~ 1 | num,
    "lvmi" = ~ time | num
  ),
  formSurv = Surv(fuyrs, status) ~ age,
```

```

    data = hvd,
    inits = list("gamma" = c(0.11, 1.51, 0.80)),
    timeVar = "time"
  )

# extract the survival fixed effects
tidy(fit)

# extract the longitudinal fixed effects
tidy(fit, component = "longitudinal")

# extract the survival fixed effects with confidence intervals
tidy(fit, ci = TRUE)

# extract the survival fixed effects with confidence intervals based
# on bootstrapped standard errors
bSE <- bootSE(fit, nboot = 5, safe.boot = TRUE)
tidy(fit, boot_se = bSE, ci = TRUE)

# augment original data with fitted longitudinal values and residuals
hvd2 <- augment(fit)

# extract model statistics
glance(fit)

## End(Not run)

```

augment.mlogit

Augment data with information from a(n) mlogit object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'mlogit'
augment(x, data = x$model, ...)
```

Arguments

<code>x</code>	an object returned from <code>mlogit::mlogit()</code> .
<code>data</code>	Not currently used
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

At the moment this only works on the estimation dataset. Need to set it up to predict on another dataset.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.probability</code>	Class probability of modal class.
<code>.resid</code>	The difference between observed and fitted values.

See Also

`augment()`

Other mlogit tidiers: `glance.mlogit()`, `tidy.mlogit()`

Examples

```
# load libraries for models and data
library(mlogit)

data("Fishing", package = "mlogit")
Fish <- dfidx(Fishing, varying = 2:9, shape = "wide", choice = "mode")

# fit model
m <- mlogit(mode ~ price + catch | income, data = Fish)

# summarize model fit with tidiers
tidy(m)
augment(m)
glance(m)
```

augment.nlrq

Tidy a(n) nlrq object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'nlrq'
augment(x, data = NULL, newdata = NULL, ...)
```

Arguments

x	A nlrq object returned from <code>quantreg::nlrq()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

See Also

[augment\(\)](#), [quantreg::nlrq\(\)](#)

Other `quantreg` tidiers: [augment.rqs\(\)](#), [augment.rq\(\)](#), [glance.nlrq\(\)](#), [glance.rq\(\)](#), [tidy.nlrq\(\)](#), [tidy.rqs\(\)](#), [tidy.rq\(\)](#)

Examples

```
# fit model
n <- nls(mpg ~ k * e^wt, data = mtcars, start = list(k = 1, e = 2))

# summarize model fit with tidiers + visualization
tidy(n)
augment(n)
glance(n)

library(ggplot2)

ggplot(augment(n), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))

newdata <- head(mtcars)
newdata$wt <- newdata$wt + 1

augment(n, newdata = newdata)
```

augment.nls

Augment data with information from a(n) nls object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures) that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'nls'
augment(x, data = NULL, newdata = NULL, ...)
```

Arguments

<code>x</code>	An <code>nls</code> object returned from <code>stats::nls()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>Augment</code> will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

augment.nls does not currently support confidence intervals due to a lack of support in stats::predict.nls().

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

[tidy](#), [stats::nls\(\)](#), [stats::predict.nls\(\)](#)

Other nls tidiers: [glance.nls\(\)](#), [tidy.nls\(\)](#)

Examples

```
# fit model
n <- nls(mpg ~ k * e^wt, data = mtcars, start = list(k = 1, e = 2))

# summarize model fit with tidiers + visualization
tidy(n)
augment(n)
glance(n)

library(ggplot2)

ggplot(augment(n), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))

newdata <- head(mtcars)
newdata$wt <- newdata$wt + 1

augment(n, newdata = newdata)
```

augment.pam

Augment data with information from a(n) pam object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures) that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'pam'
augment(x, data = NULL, ...)
```

Arguments

<code>x</code>	An <code>pam</code> object returned from <code>cluster::pam()</code>
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>Augment</code> will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.cluster</code>	Cluster assignment.
<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

`augment()`, `cluster::pam()`

Other pam tidiers: `glance.pam()`, `tidy.pam()`

Examples

```
# load libraries for models and data
library(dplyr)
library(ggplot2)
library(cluster)
library(modeldata)
data(hpc_data)

x <- hpc_data[, 2:5]
p <- pam(x, k = 4)

# summarize model fit with tidiers + visualization
tidy(p)
glance(p)
augment(p, x)

augment(p, x) %>%
  ggplot(aes(compounds, input_fields)) +
  geom_point(aes(color = .cluster)) +
  geom_text(aes(label = cluster), data = tidy(p), size = 10)
```

augment.plm

Augment data with information from a(n) plm object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures) that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'plm'
augment(x, data = model.frame(x), ...)
```

Arguments

<code>x</code>	A <code>plm</code> object returned by <code>plm::plm()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>Augment</code> will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

`augment()`, `plm::plm()`

Other plm tidiers: `glance.plm()`, `tidy.plm()`

Examples

```
# load libraries for models and data
library(plm)

# load data
data("Produc", package = "plm")

# fit model
zz <- plm(log(gsp) ~ log(pcap) + log(pc) + log(emp) + unemp,
  data = Produc, index = c("state", "year")
)

# summarize model fit with tidiers
summary(zz)

tidy(zz)
tidy(zz, conf.int = TRUE)
tidy(zz, conf.int = TRUE, conf.level = 0.9)

augment(zz)
glance(zz)
```

augment.poLCA

Augment data with information from a(n) poLCA object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object.

Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'poLCA'
augment(x, data = NULL, ...)
```

Arguments

<code>x</code>	A <code>poLCA</code> object returned from <code>poLCA::poLCA()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

If the `data` argument is given, those columns are included in the output (only rows for which predictions could be made). Otherwise, the `y` element of the `poLCA` object, which contains the manifest variables used to fit the model, are used, along with any covariates, if present, in `x`.

Note that while the probability of all the classes (not just the predicted modal class) can be found in the posterior element, these are not included in the augmented output.

Value

A `tibble::tibble()` with columns:

<code>.class</code>	Predicted class.
<code>.probability</code>	Class probability of modal class.

See Also

`augment()`, `poLCA::poLCA()`

Other poLCA tidiers: `glance.poLCA()`, `tidy.poLCA()`

Examples

```
# load libraries for models and data
library(poLCA)
library(dplyr)

# generate data
data(values)

f <- cbind(A, B, C, D) ~ 1

# fit model
M1 <- poLCA(f, values, nclass = 2, verbose = FALSE)

M1

# summarize model fit with tidiers + visualization
tidy(M1)
augment(M1)
glance(M1)

library(ggplot2)

ggplot(tidy(M1), aes(factor(class), estimate, fill = factor(outcome))) +
  geom_bar(stat = "identity", width = 1) +
  facet_wrap(~variable)

# three-class model with a single covariate.
data(election)

f2a <- cbind(
  MORALG, CARESG, KNOWG, LEADG, DISHONG, INTELG,
  MORALB, CARESB, KNOWB, LEADB, DISHONB, INTELB
) ~ PARTY
```

```

nes2a <- polCA(f2a, election, nclass = 3, nrep = 5, verbose = FALSE)

td <- tidy(nes2a)
td

ggplot(td, aes(outcome, estimate, color = factor(class), group = class)) +
  geom_line() +
  facet_wrap(~variable, nrow = 2) +
  theme(axis.text.x = element_text(angle = 90, hjust = 1))

au <- augment(nes2a)

au

count(au, .class)

# if the original data is provided, it leads to NAs in new columns
# for rows that weren't predicted
au2 <- augment(nes2a, data = election)

au2

dim(au2)

```

augment.polr

Augment data with information from a(n) polr object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do

not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'polr'
augment(
  x,
  data = model.frame(x),
  newdata = NULL,
  type.predict = c("class"),
  ...
)
```

Arguments

<code>x</code>	A <code>polr</code> object returned from <code>MASS::polr()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>type.predict</code>	Which type of prediction to compute, passed to <code>MASS::predict.polr()</code> . Only supports "class" at the moment.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

See Also

`tidy()`, `MASS::polr()`

Other ordinal tidiers: `augment.clm()`, `glance.clmm()`, `glance.clm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clmm()`, `tidy.clm()`, `tidy.polr()`, `tidy.svyolr()`

Examples

```
# load libraries for models and data
library(MASS)

# fit model
fit <- polr(Sat ~ Infl + Type + Cont, weights = Freq, data = housing)

# summarize model fit with tidiers
tidy(fit, exponentiate = TRUE, conf.int = TRUE)

glance(fit)
augment(fit, type.predict = "class")

fit2 <- polr(factor(gear) ~ am + mpg + qsec, data = mtcars)

tidy(fit, p.values = TRUE)
```

 augment.prcomp

Augment data with information from a(n) prcomp object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'prcomp'
augment(x, data = NULL, newdata, ...)
```

Arguments

<code>x</code>	A <code>prcomp</code> object returned by <code>stats::prcomp()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble` containing the original data along with additional columns containing each observation's projection into PCA space.

See Also

`stats::prcomp()`, `svd_tidiers`

Other svd tidiers: `tidy.prcomp()`, `tidy_irlba()`, `tidy_svd()`

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'rlm'
augment(x, data = model.frame(x), newdata = NULL, se_fit = FALSE, ...)
```

Arguments

<code>x</code>	An <code>rlm</code> object returned by <code>MASS::rlm()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>se_fit</code>	Logical indicating whether or not a <code>.se.fit</code> column should be added to the augmented output. For some models, this calculation can be somewhat time-consuming. Defaults to <code>FALSE</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.hat</code>	Diagonal of the hat matrix.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.
<code>.sigma</code>	Estimated residual standard deviation when corresponding observation is dropped from model.

See Also

`MASS::rlm()`

Other rlm tidiers: `glance.rlm()`, `tidy.rlm()`

Examples

```
# load libraries for models and data
library(MASS)

# fit model
r <- rlm(stack.loss ~ ., stackloss)

# summarize model fit with tidiers
tidy(r)
augment(r)
glance(r)
```

 augment.rma

Augment data with information from a(n) rma object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'rma'
augment(x, interval = c("prediction", "confidence"), ...)
```

Arguments

<code>x</code>	An <code>rma</code> object such as those created by <code>metafor::rma()</code> , <code>metafor::rma.uni()</code> , <code>metafor::rma.glm()</code> , <code>metafor::rma.mh()</code> , <code>metafor::rma.mv()</code> , or <code>metafor::rma.peto()</code> .
<code>interval</code>	For <code>rma.mv</code> models, should prediction intervals ("prediction", default) or confidence intervals ("confidence") intervals be returned? For <code>rma.uni</code> models, prediction intervals are always returned. For <code>rma.mh</code> and <code>rma.peto</code> models, confidence intervals are always returned.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.lower</code>	Lower bound on interval for fitted values.
<code>.moderator</code>	In meta-analysis, the moderators used to calculate the predicted values.
<code>.moderator.level</code>	In meta-analysis, the level of the moderators used to calculate the predicted values.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.
<code>.upper</code>	Upper bound on interval for fitted values.
<code>.observed</code>	The observed values for the individual studies

Examples

```
# load modeling library
library(metafor)

# generate data and fit
df <-
  escalc(
    measure = "RR",
    ai = tpos,
    bi = tneg,
    ci = cpos,
    di = cneg,
    data = dat.bcg
  )

meta_analysis <- rma(yi, vi, data = df, method = "EB")

# summarize model fit with tidiers
augment(meta_analysis)
```

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'rq'
augment(x, data = model.frame(x), newdata = NULL, ...)
```

Arguments

<code>x</code>	An <code>rq</code> object returned from <code>quantreg::rq()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Arguments passed on to <code>quantreg::predict.rq</code>
<code>object</code>	object of class <code>rq</code> or <code>rqs</code> or <code>rq.process</code> produced by <code>rq</code>
<code>interval</code>	type of interval desired: default is <code>'none'</code> , when set to <code>'confidence'</code> the function returns a matrix predictions with point predictions for each of the <code>'newdata'</code> points as well as lower and upper confidence limits.
<code>level</code>	convergence probability for the <code>'confidence'</code> intervals.
<code>type</code>	For <code>predict.rq</code> , the method for <code>'confidence'</code> intervals, if desired. If <code>'percentile'</code> then one of the bootstrap methods is used to generate percentile intervals for each prediction, if <code>'direct'</code> then a version of the Portnoy and Zhou (1998) method is used, and otherwise an estimated covariance matrix for the parameter estimates is used. Further arguments to determine the choice of bootstrap method or covariance matrix estimate can be passed via the <code>...</code> argument. For <code>predict.rqs</code> and <code>predict.rq.process</code> when <code>stepfun = TRUE</code> , <code>type</code> is <code>"Qhat"</code> , <code>"Fhat"</code> or <code>"fhat"</code> depending on whether the user would like to have estimates of the conditional quantile, distribution or density functions respectively. As noted below the two former estimates can be monotonized with the function <code>rearrange</code> . When the <code>"fhat"</code> option is invoked, a list of conditional density functions is returned based on Silverman's adaptive kernel method as implemented in <code>akj</code> and <code>approxfun</code> .
<code>na.action</code>	function determining what should be done with missing values in <code>'newdata'</code> . The default is to predict <code>'NA'</code> .

Details

Depending on the arguments passed on to `predict.rq` via `...`, a confidence interval is also calculated on the fitted values resulting in columns `.lower` and `.upper`. Does not provide confidence intervals when data is specified via the `newdata` argument.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.
<code>.tau</code>	Quantile.

See Also

`augment`, `quantreg::rq()`, `quantreg::predict.rq()`

Other `quantreg` tidiers: `augment.nlrq()`, `augment.rqs()`, `glance.nlrq()`, `glance.rq()`, `tidy.nlrq()`, `tidy.rqs()`, `tidy.rq()`

Examples

```
# load modeling library and data
library(quantreg)

data(stackloss)

# median (l1) regression fit for the stackloss data.
mod1 <- rq(stack.loss ~ stack.x, .5)

# weighted sample median
mod2 <- rq(rnorm(50) ~ 1, weights = runif(50))

# summarize model fit with tidiers
tidy(mod1)
glance(mod1)
augment(mod1)

tidy(mod2)
glance(mod2)
augment(mod2)

# varying tau to generate an rqs object
mod3 <- rq(stack.loss ~ stack.x, tau = c(.25, .5))

tidy(mod3)
augment(mod3)

# glance cannot handle rqs objects like `mod3`--use a purrr
# `map`-based workflow instead
```

 augment.rqs

Augment data with information from a(n) rqs object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether data or newdata is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'rqs'
augment(x, data = model.frame(x), newdata, ...)
```

Arguments

<code>x</code>	An rqs object returned from <code>quantreg::rq()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Arguments passed on to <code>quantreg::predict.rq</code>
<code>object</code>	object of class <code>rq</code> or <code>rqs</code> or <code>rq.process</code> produced by <code>rq</code>
<code>interval</code>	type of interval desired: default is 'none', when set to 'confidence' the function returns a matrix predictions with point predictions for each of the 'newdata' points as well as lower and upper confidence limits.
<code>level</code>	convergence probability for the 'confidence' intervals.
<code>type</code>	For <code>predict.rq</code> , the method for 'confidence' intervals, if desired. If 'percentile' then one of the bootstrap methods is used to generate percentile intervals for each prediction, if 'direct' then a version of the Portnoy and Zhou (1998) method is used, and otherwise an estimated covariance matrix for the parameter estimates is used. Further arguments to determine the choice of bootstrap method or covariance matrix estimate can be passed via the <code>...</code> argument. For <code>predict.rqs</code> and <code>predict.rq.process</code> when <code>stepfun = TRUE</code> , type is "Qhat", "Fhat" or "fhat" depending on whether the

user would like to have estimates of the conditional quantile, distribution or density functions respectively. As noted below the two former estimates can be monotonized with the function `rearrange`. When the "fhat" option is invoked, a list of conditional density functions is returned based on Silverman's adaptive kernel method as implemented in `akj` and `approxfun`.

`na.action` function determining what should be done with missing values in 'newdata'. The default is to predict 'NA'.

Details

Depending on the arguments passed on to `predict.rq` via `...`, a confidence interval is also calculated on the fitted values resulting in columns `.lower` and `.upper`. Does not provide confidence intervals when data is specified via the `newdata` argument.

See Also

`augment`, `quantreg::rq()`, `quantreg::predict.rqs()`

Other quantreg tidiers: `augment.nlrq()`, `augment.rq()`, `glance.nlrq()`, `glance.rq()`, `tidy.nlrq()`, `tidy.rqs()`, `tidy.rq()`

Examples

```
# load modeling library and data
library(quantreg)

data(stackloss)

# median (l1) regression fit for the stackloss data.
mod1 <- rq(stack.loss ~ stack.x, .5)

# weighted sample median
mod2 <- rq(rnorm(50) ~ 1, weights = runif(50))

# summarize model fit with tidiers
tidy(mod1)
glance(mod1)
augment(mod1)

tidy(mod2)
glance(mod2)
augment(mod2)

# varying tau to generate an rqs object
mod3 <- rq(stack.loss ~ stack.x, tau = c(.25, .5))

tidy(mod3)
augment(mod3)

# glance cannot handle rqs objects like `mod3`--use a purrr
```

```
# `map`-based workflow instead
```

```
augment.sarlm
```

```
Augment data with information from a(n) spatialreg object
```

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'sarlm'
augment(x, data = x$X, ...)
```

Arguments

<code>x</code>	An object returned from <code>spatialreg::lagsarlm()</code> or <code>spatialreg::errorsarlm()</code> .
<code>data</code>	Ignored, but included for internal consistency. See the details below.

- ...
- Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

The `predict` method for `sarlm` objects assumes that the response is known. See `?predict.sarlm` for more discussion. As a result, since the original data can be recovered from the fit object, this method currently does not take in `data` or `newdata` arguments.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

[augment\(\)](#)

Other spatialreg tidiers: [glance.sarlm\(\)](#), [tidy.sarlm\(\)](#)

Examples

```
# load libraries for models and data
library(spatialreg)
library(spdep)

# load data
data(oldcol, package = "spdep")

listw <- nb2listw(COL.nb, style = "W")

# fit model
crime_sar <-
lagsarlm(CRIME ~ INC + HOVAL,
          data = COL.OLD,
          listw = listw,
          method = "eigen")

# summarize model fit with tidiers
```

```

tidy(crime_sar)
tidy(crime_sar, conf.int = TRUE)
glance(crime_sar)
augment(crime_sar)

# fit another model
crime_sem <- errorsarlm(CRIME ~ INC + HOVAL, data = COL.OLD, listw)

# summarize model fit with tidiers
tidy(crime_sem)
tidy(crime_sem, conf.int = TRUE)
glance(crime_sem)
augment(crime_sem)

# fit another model
crime_sac <- sacsarlm(CRIME ~ INC + HOVAL, data = COL.OLD, listw)

# summarize model fit with tidiers
tidy(crime_sac)
tidy(crime_sac, conf.int = TRUE)
glance(crime_sac)
augment(crime_sac)

```

augment.smooth.spline *Tidy a(n) smooth.spline object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'smooth.spline'
augment(x, data = x$data, ...)

```

Arguments

x	A <code>smooth.spline</code> object returned from <code>stats::smooth.spline()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

[augment\(\)](#), [stats::smooth.spline\(\)](#), [stats::predict.smooth.spline\(\)](#)

Other smoothing spline tidiers: [glance.smooth.spline\(\)](#)

Examples

```
# fit model
spl <- smooth.spline(mtcars$wt, mtcars$mpg, df = 4)

# summarize model fit with tidiers
augment(spl, mtcars)

# calls original columns x and y
augment(spl)

library(ggplot2)
ggplot(augment(spl, mtcars), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))
```

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'speedlm'
augment(x, data = model.frame(x), newdata = NULL, ...)
```

Arguments

<code>x</code>	A <code>speedlm</code> object returned from <code>speedglm::speedlm()</code> .
<code>data</code>	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be

used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.

See Also

[speedglm::speedlm\(\)](#)

Other speedlm tidiers: [glance.speedglm\(\)](#), [glance.speedlm\(\)](#), [tidy.speedglm\(\)](#), [tidy.speedlm\(\)](#)

Examples

```
# load modeling library
library(speedglm)

# fit model
mod <- speedlm(mpg ~ wt + qsec, data = mtcars, fitted = TRUE)

# summarize model fit with tidiers
tidy(mod)
glance(mod)
augment(mod)
```

augment.stl

Augment data with information from a(n) stl object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires

that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

Augment will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures) that is not meaningfully defined for new observations.

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, augment tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'stl'
augment(x, data = NULL, weights = TRUE, ...)
```

Arguments

<code>x</code>	An <code>stl</code> object returned from <code>stats::stl()</code> .
<code>data</code>	Ignored, included for consistency with the augment generic signature only.
<code>weights</code>	Logical indicating whether or not to include the robust weights in the output.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble` with one row for each observation in the original times series:

<code>.seasonal</code>	The seasonal component of the decomposition.
<code>.trend</code>	The trend component of the decomposition.
<code>.remainder</code>	The remainder, or "random" component of the decomposition.
<code>.weight</code>	The final robust weights, if requested.
<code>.seasadj</code>	The seasonally adjusted (or "deseasonalised") series.

See Also[augment\(\)](#), [stats::stl\(\)](#)Other decompose tidiers: [augment.decomposed.ts\(\)](#)

`augment.survreg`*Augment data with information from a(n) survreg object*

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that at least all predictor variable columns used to fit the model are present. If the original outcome variable used to fit the model is not included in `newdata`, then no `.resid` column will be included in the output.

`Augment` will often behave differently depending on whether `data` or `newdata` is given. This is because there is often information associated with training observations (such as influences or related measures that is not meaningfully defined for new observations).

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases, `augment` tries to reconstruct the original data based on the model object with varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'survreg'
augment(
  x,
  data = NULL,
  newdata = NULL,
  type.predict = "response",
  type.residuals = "response",
  ...
)
```

Arguments

x	An survreg object returned from <code>survival::survreg()</code> .
data	A <code>base::data.frame</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>base::data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Character indicating type of prediction to use. Passed to the type argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
type.residuals	Character indicating type of residuals to use. Passed to the type argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>.fitted</code>	Fitted or predicted value.
<code>.resid</code>	The difference between observed and fitted values.
<code>.se.fit</code>	Standard errors of fitted values.

See Also

`augment()`, `survival::survreg()`

Other survreg tidiers: `glance.survreg()`, `tidy.survreg()`

Other survival tidiers: `augment.coxph()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```

# load libraries for models and data
library(survival)

# fit model
sr <- survreg(
  Surv(futime, fustat) ~ ecog.ps + rx,
  ovarian,
  dist = "exponential"
)

# summarize model fit with tidiers + visualization
tidy(sr)
augment(sr, ovarian)
glance(sr)

# coefficient plot
td <- tidy(sr, conf.int = TRUE)

library(ggplot2)

ggplot(td, aes(estimate, term)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high), height = 0) +
  geom_vline(xintercept = 0)

```

augment_columns	<i>Add fitted values, residuals, and other common outputs to an augment call</i>
-----------------	--

Description

augment_columns is intended for use in the internals of augment methods only and is exported for developers extending the broom package. Please instead use [augment\(\)](#) to appropriately make use of the functionality in augment_columns().

Usage

```

augment_columns(
  x,
  data,
  newdata = NULL,
  type,
  type.predict = type,
  type.residuals = type,
  se.fit = TRUE,

```

```
    ...
  )
```

Arguments

<code>x</code>	a model
<code>data</code>	original data onto which columns should be added
<code>newdata</code>	new data to predict on, optional
<code>type</code>	Type of prediction and residuals to compute
<code>type.predict</code>	Type of prediction to compute; by default same as <code>type</code>
<code>type.residuals</code>	Type of residuals to compute; by default same as <code>type</code>
<code>se.fit</code>	Value to pass to <code>predict</code> 's <code>se.fit</code> , or <code>NULL</code> for no value
<code>...</code>	extra arguments (not used)

Details

Note that, in the case that a `residuals()` or `influence()` generic is not implemented for the supplied model `x`, the function will fail quietly.

bootstrap

Set up bootstrap replicates of a dplyr operation

Description

The `bootstrap()` function is deprecated and will be removed from an upcoming release of broom. For tidy resampling, please use the `rsample` package instead. Functionality is no longer supported for this method.

Usage

```
bootstrap(df, m, by_group = FALSE)
```

Arguments

<code>df</code>	a data frame
<code>m</code>	number of bootstrap replicates to perform
<code>by_group</code>	If <code>TRUE</code> , then bootstrap within each group if <code>df</code> is a grouped tibble.

Details

This code originates from Hadley Wickham (with a few small corrections) here: <https://github.com/tidyverse/dplyr/issues/269>

See Also

Other deprecated: `confint_tidy()`, `data.frame_tidiers`, `finish_glance()`, `fix_data_frame()`, `summary_tidiers`, `tidy.density()`, `tidy.dist()`, `tidy.ftable()`, `tidy.numeric()`

confint_tidy	<i>(Deprecated)</i> Calculate confidence interval as a tidy data frame
--------------	--

Description

This function is now deprecated and will be removed from a future release of broom.

Usage

```
confint_tidy(x, conf.level = 0.95, func = stats::confint, ...)
```

Arguments

x	a model object for which <code>confint()</code> can be calculated
conf.level	confidence level
func	A function to compute a confidence interval for x. Calling <code>func(x, level = conf.level, ...)</code> must return an object coercible to a tibble. This dataframe like object should have to columns corresponding the lower and upper bounds on the confidence interval.
...	extra arguments passed on to <code>confint</code>

Details

Return a confidence interval as a tidy data frame. This directly wraps the `confint()` function, but ensures it follows broom conventions: column names of `conf.low` and `conf.high`, and no row names.

```
confint_tidy
```

Value

A tibble with two columns: `conf.low` and `conf.high`.

See Also

Other deprecated: [bootstrap\(\)](#), [data.frame_tidiers](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#), [tidy.numeric\(\)](#)

data.frame_tidiers *Tidiers for data.frame objects*

Description

Data frame tidiers are deprecated and will be removed from an upcoming release of broom.

Usage

```
## S3 method for class 'data.frame'
tidy(x, ..., na.rm = TRUE, trim = 0.1)

## S3 method for class 'data.frame'
augment(x, data, ...)

## S3 method for class 'data.frame'
glance(x, ...)
```

Arguments

x	A data.frame
...	Additional arguments for other methods.
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
trim	the fraction (0 to 0.5) of observations to be trimmed from each end of x before the mean is computed. Passed to the trim argument of mean
data	data, not used

Details

These perform tidy summaries of data.frame objects. tidy produces summary statistics about each column, while glance simply reports the number of rows and columns. Note that augment.data.frame will throw an error.

Value

tidy.data.frame produces a data frame with one row per original column, containing summary statistics of each:

column	name of original column
n	Number of valid (non-NA) values
mean	mean
sd	standard deviation
median	median
trimmed	trimmed mean, with trim defaulting to .1

mad	median absolute deviation (from the median)
min	minimum value
max	maximum value
range	range
skew	skew
kurtosis	kurtosis
se	standard error
glance returns a one-row data.frame with	
nrow	number of rows
ncol	number of columns
complete.obs	number of rows that have no missing values
na.fraction	fraction of values across all rows and columns that are missing

Author(s)

David Robinson, Benjamin Nutter

Source

Skew and Kurtosis functions are adapted from implementations in the moments package:
 Lukasz Komsta and Frederick Novomestky (2015). moments: Moments, cumulants, skewness, kurtosis and related tests. R package version 0.14.
<https://CRAN.R-project.org/package=moments>

See Also

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#), [tidy.numeric\(\)](#)

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#), [tidy.numeric\(\)](#)

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#), [tidy.numeric\(\)](#)

Examples

```
td <- tidy(mtcars)
td

glance(mtcars)

library(ggplot2)
# compare mean and standard deviation
ggplot(td, aes(mean, sd)) + geom_point() +
  geom_text(aes(label = column), hjust = 1, vjust = 1) +
  scale_x_log10() + scale_y_log10() + geom_abline()
```

 durbinWatsonTest_tidiers

Tidy/glance a(n) durbinWatsonTest object

Description

For models that have only a single component, the `tidy()` and `glance()` methods are identical. Please see the documentation for both of those methods.

Usage

```
## S3 method for class 'durbinWatsonTest'
tidy(x, ...)
```

```
## S3 method for class 'durbinWatsonTest'
glance(x, ...)
```

Arguments

<code>x</code>	An object of class <code>durbinWatsonTest</code> created by a call to <code>car::durbinWatsonTest()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>alternative</code>	Alternative hypothesis (character).
<code>autocorrelation</code>	Autocorrelation.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	Test statistic for Durbin-Watson test.
<code>method</code>	Always 'Durbin-Watson Test'.

See Also

`tidy()`, `glance()`, `car::durbinWatsonTest()`

Other car tidiers: `leveneTest_tidiers`

Examples

```
# load modeling library
library(car)

# fit model
dw <- durbinWatsonTest(lm(mpg ~ wt, data = mtcars))

# summarize model fit with tidiers
tidy(dw)

# same output for all durbinWatsonTests
glance(dw)
```

finish_glance	<i>(Deprecated) Add logLik, AIC, BIC, and other common measurements to a glance of a prediction</i>
---------------	---

Description

This function is now deprecated in favor of using custom logic and the appropriate `nobs()` method.

Usage

```
finish_glance(ret, x)
```

Arguments

ret	a one-row data frame (a partially complete glance)
x	the prediction model

Value

a one-row data frame with additional columns added, such as

logLik	log likelihoods
AIC	Akaike Information Criterion
BIC	Bayesian Information Criterion
deviance	deviance
df.residual	residual degrees of freedom

See Also

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [data.frame_tidiers](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#), [tidy.numeric\(\)](#)

fix_data_frame	<i>Ensure an object is a data frame, with rownames moved into a column</i>
----------------	--

Description

This function is deprecated as of broom 0.7.0 and will be removed from a future release. Please see `tibble::as_tibble`.

Usage

```
fix_data_frame(x, newnames = NULL, newcol = "term")
```

Arguments

x	a data.frame or matrix
newnames	new column names, not including the rownames
newcol	the name of the new rownames column

Value

a data.frame, with rownames moved into a column and new column names assigned

See Also

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [data.frame_tidiers](#), [finish_glance\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#), [tidy.numeric\(\)](#)

glance.aareg	<i>Glance at a(n) aareg object</i>
--------------	------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'aareg'
glance(x, ...)
```

Arguments

x	An aareg object returned from <code>survival::aareg()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

df	Degrees of freedom used by the model.
nobs	Number of observations used.
p.value	P-value corresponding to the test statistic.
statistic	Test statistic.

See Also

`glance()`, `survival::aareg()`

Other aareg tidiers: `tidy.aareg()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# fit model
afit <- aareg(
  Surv(time, status) ~ age + sex + ph.ecog,
  data = lung,
  dfbeta = TRUE
)
```

```
# summarize model fit with tidiers
tidy(afit)
```

glance.anova

Glance at a(n) anova object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'anova'
glance(x, ...)
```

Arguments

- | | |
|-----|---|
| x | An anova object, such as those created by <code>stats::anova()</code> , <code>car::Anova()</code> , <code>car::leveneTest()</code> , or <code>car::linearHypothesis()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

deviance	Deviance of the model.
df.residual	Residual degrees of freedom.

Note

Note that the output of `glance.anova()` will vary depending on the initializing `anova` call. In some cases, it will just return an empty data frame. In other cases, `glance.anova()` may return columns that are also common to `tidy.anova()`. This is partly to preserve backwards compatibility with early versions of `broom`, but also because the underlying `anova` model yields components that could reasonably be interpreted as goodness-of-fit summaries too.

See Also

[glance\(\)](#)

Other `anova` tidiers: [glance.aov\(\)](#), [tidy.TukeyHSD\(\)](#), [tidy.anova\(\)](#), [tidy.aovlist\(\)](#), [tidy.aov\(\)](#), [tidy.manova\(\)](#)

Examples

```
# fit models
a <- lm(mpg ~ wt + qsec + disp, mtcars)
b <- lm(mpg ~ wt + qsec, mtcars)

mod <- anova(a, b)

# summarize model fit with tidiers
tidy(mod)
glance(mod)

# car::linearHypothesis() example
library(car)
mod_lht <- linearHypothesis(a, "wt - disp")
tidy(mod_lht)
glance(mod_lht)
```

`glance.aov`

Glance at a(n) lm object

Description

`Glance` accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

`Glance` never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

`Glance` does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'aov'
glance(x, ...)
```

Arguments

<code>x</code>	An aov object, such as those created by <code>stats::aov()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.

Note

Note that `tidy.aov()` now contains the numerator and denominator degrees of freedom, which were included in the output of `glance.aov()` in some previous versions of the package.

See Also

[glance\(\)](#)

Other anova tidiers: [glance.anova\(\)](#), [tidy.TukeyHSD\(\)](#), [tidy.anova\(\)](#), [tidy.aovlist\(\)](#), [tidy.aov\(\)](#), [tidy.manova\(\)](#)

Examples

```
a <- aov(mpg ~ wt + qsec + disp, mtcars)
tidy(a)
```

glance.Arima

Glance at a(n) Arima object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'Arima'
glance(x, ...)
```

Arguments

<code>x</code>	An object of class <code>Arima</code> created by <code>stats::arima()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
sigma	Estimated standard error of the residuals.

See Also

`stats::arima()`

Other Arima tidiers: `tidy.Arima()`

Examples

```
# fit model
fit <- arima(lh, order = c(1, 0, 0))

# summarize model fit with tidiers
tidy(fit)
glance(fit)
```

glance.betamfx

Glance at a(n) betamfx object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'betamfx'
glance(x, ...)
```

Arguments

`x` A betamfx object.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

This glance method wraps `glance.betareg()` for `mfx::betamfx()` objects.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
df.null	Degrees of freedom used by the null model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
pseudo.r.squared	Like the R squared statistic, but for situations when the R squared statistic isn't defined.

See Also

`glance.betareg()`, `mfx::betamfx()`

Other mfx tidiers: `augment.betamfx()`, `augment.mfx()`, `glance.mfx()`, `tidy.betamfx()`, `tidy.mfx()`

Examples

```
library(mfx)

# Simulate some data
set.seed(12345)
n = 1000
x = rnorm(n)

# Beta outcome
y = rbeta(n, shape1 = plogis(1 + 0.5 * x), shape2 = (abs(0.2*x)))
# Use Smithson and Verkuilen correction
y = (y*(n-1)+0.5)/n

d = data.frame(y,x)
mod_betamfx = betamfx(y ~ x | x, data = d)

tidy(mod_betamfx, conf.int = TRUE)
```

```
# Compare with the naive model coefficients of the equivalent betareg call (not run)
# tidy(betamfx(y ~ x | x, data = d), conf.int = TRUE)

augment(mod_betamfx)
glance(mod_betamfx)
```

glance.betareg	<i>Glance at a(n) betareg object</i>
----------------	--------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'betareg'
glance(x, ...)
```

Arguments

- | | |
|-----|---|
| x | A betareg object produced by a call to <code>betareg::betareg()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
df.null	Degrees of freedom used by the null model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
pseudo.r.squared	Like the R squared statistic, but for situations when the R squared statistic isn't defined.

See Also

[glance\(\)](#), [betareg::betareg\(\)](#)

Examples

```
# load libraries for models and data
library(betareg)

# load data
data("GasolineYield", package = "betareg")

# fit model
mod <- betareg(yield ~ batch + temp, data = GasolineYield)

mod

# summarize model fit with tidiers
tidy(mod)
tidy(mod, conf.int = TRUE)
tidy(mod, conf.int = TRUE, conf.level = .99)

augment(mod)

glance(mod)
```

glance.biglm	<i>Glance at a(n) biglm object</i>
--------------	------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'biglm'
glance(x, ...)
```

Arguments

x	A biglm object created by a call to <code>biglm::biglm()</code> or <code>biglm::bigglm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
deviance	Deviance of the model.
df.residual	Residual degrees of freedom.
nobs	Number of observations used.
r.squared	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.

See Also

`glance()`, `biglm::biglm()`, `biglm::bigglm()`

Other biglm tidiers: `tidy.biglm()`

Examples

```
# load modeling library
library(biglm)

# fit model -- linear regression
bfit <- biglm(mpg ~ wt + disp, mtcars)

# summarize model fit with tidiers
tidy(bfit)
tidy(bfit, conf.int = TRUE)
tidy(bfit, conf.int = TRUE, conf.level = .9)

glance(bfit)

# fit model -- logistic regression
bgfit <- bigglm(am ~ mpg, mtcars, family = binomial())

# summarize model fit with tidiers
tidy(bgfit)
tidy(bgfit, exponentiate = TRUE)
tidy(bgfit, conf.int = TRUE)
tidy(bgfit, conf.int = TRUE, conf.level = .9)
tidy(bgfit, conf.int = TRUE, conf.level = .9, exponentiate = TRUE)

glance(bgfit)
```

glance.binDesign

Glance at a(n) binDesign object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'binDesign'
glance(x, ...)
```

Arguments

x	A <code>binGroup::binDesign</code> object.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

power	Power achieved by the analysis.
n	Sample size used to achieve this power.
power.reached	Whether the desired power was reached.
maxit	Number of iterations performed.

See Also

`glance()`, `binGroup::binDesign()`

Other bingroup tidiers: `tidy.binDesign()`, `tidy.binWidth()`

Examples

```
# load libraries for models and data
library(binGroup)

des <- binDesign(
  nmax = 300, delta = 0.06,
  p.hyp = 0.1, power = .8
)

glance(des)
```

```

tidy(des)

library(ggplot2)

ggplot(tidy(des), aes(n, power)) +
  geom_line()

```

glance.cch

Glance at a(n) cch object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'cch'
glance(x, ...)

```

Arguments

- | | |
|-----|---|
| x | An cch object returned from <code>survival::cch()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

<code>iter</code>	Iterations of algorithm/fitting procedure completed.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>rscore</code>	Robust log-rank statistic
<code>score</code>	Score.
<code>n</code>	number of predictions
<code>nevent</code>	number of events

See Also

`glance()`, `survival::cch()`

Other cch tidiers: `glance.survfit()`, `tidy.cch()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# examples come from cch documentation
subcoh <- nwtco$in.subcohort
selccoh <- with(nwtco, rel == 1 | subcoh == 1)
ccoh.data <- nwtco[selccoh, ]
ccoh.data$subcohort <- subcoh[selccoh]

# central-lab histology
ccoh.data$histol <- factor(ccoh.data$histol, labels = c("FH", "UH"))

# tumour stage
ccoh.data$stage <- factor(ccoh.data$stage, labels = c("I", "II", "III", "IV"))
ccoh.data$age <- ccoh.data$age / 12 # age in years

# fit model
fit.ccP <- cch(Surv(edrel, rel) ~ stage + histol + age,
  data = ccoh.data,
  subcoh = ~subcohort, id = ~seqno, cohort.size = 4028
)

# summarize model fit with tidiers + visualization
tidy(fit.ccP)

# coefficient plot
```

```
library(ggplot2)

ggplot(tidy(fit.ccP), aes(x = estimate, y = term)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high), height = 0) +
  geom_vline(xintercept = 0)
```

glance.clm

Glance at a(n) clm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'clm'
glance(x, ...)
```

Arguments

- | | |
|-----|---|
| x | A <code>clm</code> object returned from <code>ordinal::clm()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
df.residual	Residual degrees of freedom.
edf	The effective degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.

See Also

`tidy, ordinal::clm()`

Other ordinal tidiers: `augment.clm()`, `augment.polr()`, `glance.clmm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clmm()`, `tidy.clm()`, `tidy.polr()`, `tidy.svyolr()`

Examples

```
# load libraries for models and data
library(ordinal)

# fit model
fit <- clm(rating ~ temp * contact, data = wine)

# summarize model fit with tidiers
tidy(fit)
tidy(fit, conf.int = TRUE, conf.level = 0.9)
tidy(fit, conf.int = TRUE, conf.type = "Wald", exponentiate = TRUE)

glance(fit)
augment(fit, type.predict = "prob")
augment(fit, type.predict = "class")

# ...and again with another model specification
fit2 <- clm(rating ~ temp, nominal = ~contact, data = wine)

tidy(fit2)
glance(fit2)
```

glance.clmm	<i>Glance at a(n) clmm object</i>
-------------	-----------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'clmm'
glance(x, ...)
```

Arguments

x	A <code>clmm</code> object returned from <code>ordinal::clmm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
edf	The effective degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.

See Also

`tidy, ordinal::clmm()`

Other ordinal tidiers: `augment.clm()`, `augment.polr()`, `glance.clm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clmm()`, `tidy.clm()`, `tidy.polr()`, `tidy.svyolr()`

Examples

```
# load libraries for models and data
library(ordinal)

# fit model
fit <- clmm(rating ~ temp + contact + (1 | judge), data = wine)

# summarize model fit with tidiers
tidy(fit)
tidy(fit, conf.int = TRUE, conf.level = 0.9)
tidy(fit, conf.int = TRUE, exponentiate = TRUE)

glance(fit)

# ...and again with another model specification
fit2 <- clmm(rating ~ temp + (1 | judge), nominal = ~contact, data = wine)

tidy(fit2)
glance(fit2)
```

`glance.coefstest`

Glance at a(n) coefstest object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'coefest'
glance(x, ...)
```

Arguments

`x` A `coefest` object returned from `lmtest::coefest()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>adj.r.squared</code>	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
<code>AIC</code>	Akaike's Information Criterion for the model.
<code>BIC</code>	Bayesian Information Criterion for the model.
<code>deviance</code>	Deviance of the model.
<code>df</code>	Degrees of freedom used by the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
<code>nobs</code>	Number of observations used.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>sigma</code>	Estimated standard error of the residuals.
<code>statistic</code>	Test statistic.

Note

Because of the way that `lmtest::coefest()` retains information about the underlying model object, the returned columns for `glance.coefest()` will vary depending on the arguments. Specifically, four columns are returned regardless: "Loglik", "AIC", "BIC", and "nobs". Users can obtain additional columns (e.g. "r.squared", "df") by invoking the `save = TRUE` argument as part of `lmtest::coefest()`. See examples.

As an aside, goodness-of-fit measures such as R-squared are unaffected by the presence of heteroskedasticity. For further discussion see, e.g. chapter 8.1 of Wooldridge (2016).

References

Wooldridge, Jeffrey M. (2016) *Introductory econometrics: A modern approach*. (6th edition). Nelson Education.

See Also

[glance\(\)](#), [lmtest::coefstest\(\)](#)

Examples

```
# load libraries for models and data
library(lmtest)

m <- lm(dist ~ speed, data = cars)

coefstest(m)
tidy(coefstest(m))
tidy(coefstest(m, conf.int = TRUE))

# a very common workflow is to combine lmtest::coefstest with alternate
# variance-covariance matrices via the sandwich package. The lmtest
# tidiers support this workflow too, enabling you to adjust the standard
# errors of your tidied models on the fly.
library(sandwich)

# "HC3" (default) robust SEs
tidy(coefstest(m, vcov = vcovHC))

# "HC2" robust SEs
tidy(coefstest(m, vcov = vcovHC, type = "HC2"))

# N-W HAC robust SEs
tidy(coefstest(m, vcov = NeweyWest))

# the columns of the returned tibble for glance.coefstest() will vary
# depending on whether the coefstest object retains the underlying model.
# Users can control this with the "save = TRUE" argument of coefstest().
glance(coefstest(m))
glance(coefstest(m, save = TRUE))
```

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'coxph'
glance(x, ...)
```

Arguments

<code>x</code>	A coxph object returned from <code>survival::coxph()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
n	The total number of observations.
nevent	Number of events.
nobs	Number of observations used.

See `survival::coxph.object` for additional column descriptions.

See Also

[glance\(\)](#), [survival::coxph\(\)](#)

Other coxph tidiers: [augment.coxph\(\)](#), [tidy.coxph\(\)](#)

Other survival tidiers: [augment.coxph\(\)](#), [augment.survreg\(\)](#), [glance.aareg\(\)](#), [glance.cch\(\)](#), [glance.pyyears\(\)](#), [glance.survdiff\(\)](#), [glance.survexp\(\)](#), [glance.survfit\(\)](#), [glance.survreg\(\)](#), [tidy.aareg\(\)](#), [tidy.cch\(\)](#), [tidy.coxph\(\)](#), [tidy.pyyears\(\)](#), [tidy.survdiff\(\)](#), [tidy.survexp\(\)](#), [tidy.survfit\(\)](#), [tidy.survreg\(\)](#)

Examples

```
# load libraries for models and data
library(survival)

# fit model
cfit <- coxph(Surv(time, status) ~ age + sex, lung)

# summarize model fit with tidiers
tidy(cfit)
tidy(cfit, exponentiate = TRUE)

lp <- augment(cfit, lung)
risks <- augment(cfit, lung, type.predict = "risk")
expected <- augment(cfit, lung, type.predict = "expected")

glance(cfit)

# also works on clogit models
resp <- levels(logan$occupation)
n <- nrow(logan)
indx <- rep(1:n, length(resp))
logan2 <- data.frame(
  logan[indx, ],
  id = indx,
  tocc = factor(rep(resp, each = n))
)

logan2$case <- (logan2$occupation == logan2$tocc)

cl <- clogit(case ~ tocc + tocc:education + strata(id), logan2)

tidy(cl)
glance(cl)

library(ggplot2)

ggplot(lp, aes(age, .fitted, color = sex)) +
  geom_point()

ggplot(risks, aes(age, .fitted, color = sex)) +
```

```

geom_point()

ggplot(expected, aes(time, .fitted, color = sex)) +
  geom_point()

```

glance.crr

Glance at a(n) crr object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'crr'
glance(x, ...)

```

Arguments

- | | |
|-----|---|
| x | A crr object returned from <code>cmprsk::crr()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

<code>converged</code>	Logical indicating if the model fitting procedure was succesful and converged.
<code>df</code>	Degrees of freedom used by the model.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
<code>nobs</code>	Number of observations used.
<code>statistic</code>	Test statistic.

See Also

`glance()`, `cmprsk::crr()`

Other `cmprsk` tidiers: `tidy.crr()`

Examples

```
library(cmprsk)

# time to loco-regional failure (lrf)
lrf_time <- rexp(100)
lrf_event <- sample(0:2, 100, replace = TRUE)
trt <- sample(0:1, 100, replace = TRUE)
strt <- sample(1:2, 100, replace = TRUE)

# fit model
x <- crr(lrf_time, lrf_event, cbind(trt, strt))

# summarize model fit with tidiers
tidy(x, conf.int = TRUE)
glance(x)
```

`glance.cv.glmnet`

Glance at a(n) cv.glmnet object

Description

`Glance` accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

`Glance` never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

`Glance` does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'cv.glmnet'
glance(x, ...)
```

Arguments

x	A <code>cv.glmnet</code> object returned from <code>glmnet::cv.glmnet()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

lambda.1se	The value of the penalization parameter lambda that results in the sparsest model while remaining within one standard error of the minimum loss.
lambda.min	The value of the penalization parameter lambda that achieved minimum loss as estimated by cross validation.
nobs	Number of observations used.

See Also

`glance()`, `glmnet::cv.glmnet()`

Other glmnet tidiers: `glance.glmnet()`, `tidy.cv.glmnet()`, `tidy.glmnet()`

Examples

```
# load libraries for models and data
library(glmnet)

set.seed(27)

nobs <- 100
nvar <- 50
real <- 5
```

```

x <- matrix(rnorm(nobs * nvar), nobs, nvar)
beta <- c(rnorm(real, 0, 1), rep(0, nvar - real))
y <- c(t(beta) %*% t(x)) + rnorm(nvar, sd = 3)

cvfit1 <- cv.glmnet(x, y)

tidy(cvfit1)
glance(cvfit1)

library(ggplot2)

tidied_cv <- tidy(cvfit1)
glance_cv <- glance(cvfit1)

# plot of MSE as a function of lambda
g <- ggplot(tidied_cv, aes(lambda, estimate)) +
  geom_line() +
  scale_x_log10()
g

# plot of MSE as a function of lambda with confidence ribbon
g <- g + geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)
g

# plot of MSE as a function of lambda with confidence ribbon and choices
# of minimum lambda marked
g <- g +
  geom_vline(xintercept = glance_cv$lambda.min) +
  geom_vline(xintercept = glance_cv$lambda.1se, lty = 2)
g

# plot of number of zeros for each choice of lambda
ggplot(tidied_cv, aes(lambda, nzero)) +
  geom_line() +
  scale_x_log10()

# coefficient plot with min lambda shown
tidied <- tidy(cvfit1$glmnet.fit)

ggplot(tidied, aes(lambda, estimate, group = term)) +
  scale_x_log10() +
  geom_line() +
  geom_vline(xintercept = glance_cv$lambda.min) +
  geom_vline(xintercept = glance_cv$lambda.1se, lty = 2)

```

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'drc'
glance(x, ...)
```

Arguments

<code>x</code>	A drc object produced by a call to <code>drc::drm()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
AICc	AIC corrected for small samples

See Also

`glance()`, `drc::drm()`

Other drc tidiers: `augment.drc()`, `tidy.drc()`

Examples

```

# load libraries for models and data
library(drc)

# fit model
mod <- drm(dead / total ~ conc, type,
  weights = total, data = selenium, fct = LL.2(), type = "binomial"
)

# summarize model fit with tidiers
tidy(mod)
tidy(mod, conf.int = TRUE)

glance(mod)

augment(mod, selenium)

```

glance.ergm

Glance at a(n) ergm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'ergm'
glance(x, deviance = FALSE, mcmc = FALSE, ...)

```

Arguments

x	An ergm object returned from a call to <code>ergm::ergm()</code> .
deviance	Logical indicating whether or not to report null and residual deviance for the model, as well as degrees of freedom. Defaults to FALSE.

mcmc	Logical indicating whether or not to report MCMC interval, burn-in and sample size used to estimate the model. Defaults to FALSE.
...	Additional arguments to pass to <code>ergm::summary()</code> . Cautionary note: Mis-specified arguments may be silently ignored.

Value

`glance.ergm` returns a one-row tibble with the columns

<code>independence</code>	Whether the model assumed dyadic independence
<code>iterations</code>	The number of MCMLE iterations performed before convergence
<code>logLik</code>	If applicable, the log-likelihood associated with the model
<code>AIC</code>	The Akaike Information Criterion
<code>BIC</code>	The Bayesian Information Criterion

If `deviance = TRUE`, and if the model supports it, the tibble will also contain the columns

<code>null.deviance</code>	The null deviance of the model
<code>df.null</code>	The degrees of freedom of the null deviance
<code>residual.deviance</code>	The residual deviance of the model
<code>df.residual</code>	The degrees of freedom of the residual deviance

See Also

`glance()`, `ergm::ergm()`, `ergm::summary.ergm()`

Other ergm tidiers: `tidy.ergm()`

<code>glance.factanal</code>	<i>Glance at a(n) factanal object</i>
------------------------------	---------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'factanal'
glance(x, ...)
```

Arguments

`x` A factanal object created by `stats::factanal()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>converged</code>	Logical indicating if the model fitting procedure was successful and converged.
<code>df</code>	Degrees of freedom used by the model.
<code>method</code>	Which method was used.
<code>n</code>	The total number of observations.
<code>n.factors</code>	The number of fitted factors.
<code>nobs</code>	Number of observations used.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>statistic</code>	Test statistic.
<code>total.variance</code>	Total cumulative proportion of variance accounted for by all factors.

See Also

`glance()`, `stats::factanal()`

Other factanal tidiers: `augment.factanal()`, `tidy.factanal()`

Examples

```
set.seed(123)

# generate data
library(dplyr)
library(purrr)

m1 <- tibble(
```

```

v1 = c(1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 3, 3, 3, 3, 3, 4, 5, 6),
v2 = c(1, 2, 1, 1, 1, 1, 2, 1, 2, 1, 3, 4, 3, 3, 3, 4, 6, 5),
v3 = c(3, 3, 3, 3, 3, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 5, 4, 6),
v4 = c(3, 3, 4, 3, 3, 1, 1, 2, 1, 1, 1, 1, 2, 1, 1, 5, 6, 4),
v5 = c(1, 1, 1, 1, 1, 3, 3, 3, 3, 3, 1, 1, 1, 1, 1, 6, 4, 5),
v6 = c(1, 1, 1, 2, 1, 3, 3, 3, 4, 3, 1, 1, 1, 2, 1, 6, 5, 4)
)

# new data
m2 <- map_dfr(m1, rev)

# factor analysis objects
fit1 <- factanal(m1, factors = 3, scores = "Bartlett")
fit2 <- factanal(m1, factors = 3, scores = "regression")

# tidying the object
tidy(fit1)
tidy(fit2)

# augmented dataframe
augment(fit1)
augment(fit2)

# augmented dataframe (with new data)
augment(fit1, data = m2)
augment(fit2, data = m2)

```

glance.felm

Glance at a(n) felm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'felm'
glance(x, ...)

```

Arguments

<code>x</code>	A <code>felm</code> object returned from <code>lfe::felm()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>adj.r.squared</code>	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
<code>df</code>	Degrees of freedom used by the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>nobs</code>	Number of observations used.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>sigma</code>	Estimated standard error of the residuals.
<code>statistic</code>	Test statistic.

Examples

```
# load libraries for models and data
library(lfe)

# use built-in `airquality` dataset
head(airquality)

# no FEs; same as lm()
est0 <- felm(Ozone ~ Temp + Wind + Solar.R, airquality)

# summarize model fit with tidiers
tidy(est0)
augment(est0)

# add month fixed effects
est1 <- felm(Ozone ~ Temp + Wind + Solar.R | Month, airquality)
```



```

# summarize model fit with tidiers
tidy(est1)
tidy(est1, fe = TRUE)
augment(est1)
glance(est1)

# the "se.type" argument can be used to switch out different standard errors
# types on the fly. In turn, this can be useful exploring the effect of
# different error structures on model inference.
tidy(est1, se.type = "iid")
tidy(est1, se.type = "robust")

# add clustered SEs (also by month)
est2 <- feIm(Ozone ~ Temp + Wind + Solar.R | Month | 0 | Month, airquality)

# summarize model fit with tidiers
tidy(est2, conf.int = TRUE)
tidy(est2, conf.int = TRUE, se.type = "cluster")
tidy(est2, conf.int = TRUE, se.type = "robust")
tidy(est2, conf.int = TRUE, se.type = "iid")

```

glance.fitdistr

Glance at a(n) fitdistr object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'fitdistr'
glance(x, ...)

```

Arguments

x A fitdistr object returned by `MASS::fitdistr()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.

See Also

`tidy()`, `MASS::fitdistr()`

Other fitdistr tidiers: `tidy.fitdistr()`

Examples

```
# load libraries for models and data
library(MASS)

# generate data
set.seed(2015)
x <- rnorm(100, 5, 2)

# fit models
fit <- fitdistr(x, dnorm, list(mean = 3, sd = 1))

# summarize model fit with tidiers
tidy(fit)
glance(fit)
```

glance.fixest	<i>Glance at a(n) fixest object</i>
---------------	-------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'fixest'
glance(x, ...)
```

Arguments

x	A fixest object returned from any of the fixest estimators
...	Additional arguments passed to <code>summary</code> and <code>confint</code> . Important arguments are <code>se</code> and <code>cluster</code> . Other arguments are <code>dof</code> , <code>exact_dof</code> , <code>forceCovariance</code> , and <code>keepBounded</code> . See summary.fixest .

Value

A `tibble::tibble()` with exactly one row and columns:

adj.r.squared	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
pseudo.r.squared	Like the R squared statistic, but for situations when the R squared statistic isn't defined.
r.squared	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.

sigma Estimated standard error of the residuals.
 within.r.squared R squared within fixed-effect groups.

Note

All columns listed below will be returned, but some will be NA, depending on the type of model estimated. sigma, r.squared, adj.r.squared, and within.r.squared will be NA for any model other than feols. pseudo.r.squared will be NA for feols.

Examples

```
# load libraries for models and data
library(fixest)

gravity <-
  feols(
    log(Euros) ~ log(dist_km) | Origin + Destination + Product + Year, trade
  )

tidy(gravity)
glance(gravity)
augment(gravity, trade)

# to get robust or clustered SEs, users can either:

# 1) specify the arguments directly in the `tidy()` call

tidy(gravity, conf.int = TRUE, cluster = c("Product", "Year"))

tidy(gravity, conf.int = TRUE, se = "threeway")

# 2) or, feed tidy() a summary.fixest object that has already accepted
# these arguments

gravity_summ <- summary(gravity, cluster = c("Product", "Year"))

tidy(gravity_summ, conf.int = TRUE)

# approach (1) is preferred.
```

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'Gam'
glance(x, ...)
```

Arguments

- | | |
|------------------|---|
| <code>x</code> | A Gam object returned from a call to <code>gam::gam()</code> . |
| <code>...</code> | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Details

Glance at gam objects created by calls to `mgcv::gam()` with `glance.gam()`.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df	Degrees of freedom used by the model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.

See Also

`glance()`, `gam::gam()`

Other gam tidiers: `tidy.Gam()`

`glance.gam`

Glance at a(n) gam object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'gam'
glance(x, ...)
```

Arguments

`x` A gam object returned from a call to `mgcv::gam()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC Akaike's Information Criterion for the model.
 BIC Bayesian Information Criterion for the model.

deviance	Deviance of the model.
df	Degrees of freedom used by the model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [stats::logLik()] may be a useful reference.
nobs	Number of observations used.

See Also

[glance\(\)](#), [mgcv::gam\(\)](#)

Other mgcv tidiers: [tidy.gam\(\)](#)

Examples

```
# load libraries for models and data
library(mgcv)

# fit model
g <- gam(mpg ~ s(hp) + am + qsec, data = mtcars)

# summarize model fit with tidiers
tidy(g)
tidy(g, parametric = TRUE)
glance(g)
augment(g)
```

glance.garch	<i>Tidy a(n) garch object</i>
--------------	-------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'garch'
glance(x, test = c("box-ljung-test", "jarque-bera-test"), ...)
```

Arguments

x	A garch object returned by <code>tseries::garch()</code> .
test	Character specification of which hypothesis test to use. The garch function reports 2 hypothesis tests: Jarque-Bera to residuals and Box-Ljung to squared residuals.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
method	Which method was used.
nobs	Number of observations used.
p.value	P-value corresponding to the test statistic.
statistic	Test statistic.
parameter	Parameter field in the <code>htest</code> , typically degrees of freedom.

See Also

`glance()`, `tseries::garch()`, []

Other garch tidiers: `tidy.garch()`

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'geeglm'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>geeglm</code> object returned from a call to <code>geepack::geeglm()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>alpha</code>	Estimated correlation parameter for <code>geepack::geeglm</code> .
<code>df.residual</code>	Residual degrees of freedom.
<code>gamma</code>	Estimated scale parameter for <code>geepack::geeglm</code> .
<code>max.cluster.size</code>	Max number of elements in clusters.
<code>n.clusters</code>	Number of clusters.

See Also

`glance()`, `geepack::geeglm()`

Examples

```
# load modeling library
library(geepack)

# load data
data(state)

ds <- data.frame(state.region, state.x77)

# fit model
geefit <- geeglm(Income ~ Frost + Murder,
  id = state.region,
  data = ds, family = gaussian,
  corstr = "exchangeable"
)

# summarize model fit with tidiers
tidy(geefit)
tidy(geefit, conf.int = TRUE)
```

glance.glm

Glance at a(n) glm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'glm'
glance(x, ...)
```

Arguments

x	A glm object returned from <code>stats::glm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df.null	Degrees of freedom used by the null model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
null.deviance	Deviance of the null model.

See Also

`stats::glm()`

Other lm tidiers: `augment.glm()`, `augment.lm()`, `glance.lm()`, `glance.summary.lm()`, `glance.svyglm()`, `tidy.glm()`, `tidy.lm.beta()`, `tidy.lm()`, `tidy.ml()`, `tidy.summary.lm()`

Examples

```
g <- glm(am ~ mpg, mtcars, family = "binomial")
glance(g)
```

glance.glmnet

Glance at a(n) glmnet object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'glmnet'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>glmnet</code> object returned from <code>glmnet::glmnet()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>nobs</code>	Number of observations used.
<code>npasses</code>	Total passes over the data across all lambda values.
<code>nulldev</code>	Null deviance.

See Also`glance()`, `glmnet::glmnet()`Other glmnet tidiers: `glance.cv.glmnet()`, `tidy.cv.glmnet()`, `tidy.glmnet()`**Examples**

```
# load libraries for models and data
library(glmnet)

set.seed(2014)
x <- matrix(rnorm(100 * 20), 100, 20)
y <- rnorm(100)
fit1 <- glmnet(x, y)

# summarize model fit with tidiers + visualization
tidy(fit1)
glance(fit1)

library(dplyr)
library(ggplot2)

tidied <- tidy(fit1) %>% filter(term != "(Intercept)")

ggplot(tidied, aes(step, estimate, group = term)) +
  geom_line()

ggplot(tidied, aes(lambda, estimate, group = term)) +
  geom_line() +
  scale_x_log10()

ggplot(tidied, aes(lambda, dev.ratio)) +
  geom_line()

# works for other types of regressions as well, such as logistic
g2 <- sample(1:2, 100, replace = TRUE)
fit2 <- glmnet(x, g2, family = "binomial")
tidy(fit2)
```

`glance.glmRob`*Glance at a(n) glmRob object*

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'glmRob'
glance(x, ...)
```

Arguments

x	A <code>glmRob</code> object returned from <code>robust::glmRob()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

deviance	Deviance of the model.
df.residual	Residual degrees of freedom.
nobs	Number of observations used.
null.deviance	Deviance of the null model.
sigma	Estimated standard error of the residuals.

See Also

`robust::glmRob()`

Other robust tidiers: `augment.lmRob()`, `glance.lmRob()`, `tidy.glmRob()`, `tidy.lmRob()`

Examples

```
# load libraries for models and data
library(robust)

# fit model
gm <- glmRob(am ~ wt, data = mtcars, family = "binomial")

# summarize model fit with tidiers
tidy(gm)
glance(gm)
```

glance.gmm

Glance at a(n) gmm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'gmm'
glance(x, ...)
```

Arguments

`x` A gmm object returned from `gmm::gmm()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>df</code>	Degrees of freedom used by the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>nobs</code>	Number of observations used.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>statistic</code>	Test statistic.

See Also

`glance()`, `gmm::gmm()`

Other gmm tidiers: `tidy.gmm()`

Examples

```
# load libraries for models and data
library(gmm)

# examples come from the "gmm" package
# CAPM test with GMM
data(Finance)
r <- Finance[1:300, 1:10]
rm <- Finance[1:300, "rm"]
rf <- Finance[1:300, "rf"]

z <- as.matrix(r - rf)
t <- nrow(z)
zm <- rm - rf
h <- matrix(zm, t, 1)
res <- gmm(z ~ zm, x = h)

# tidy result
tidy(res)
tidy(res, conf.int = TRUE)
tidy(res, conf.int = TRUE, conf.level = .99)

# coefficient plot
library(ggplot2)
library(dplyr)

tidy(res, conf.int = TRUE) %>%
  mutate(variable = reorder(term, estimate)) %>%
  ggplot(aes(estimate, variable)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_vline(xintercept = 0, color = "red", lty = 2)
```



```

# from a function instead of a matrix
g <- function(theta, x) {
  e <- x[, 2:11] - theta[1] - (x[, 1] - theta[1]) %*% matrix(theta[2:11], 1, 10)
  gmat <- cbind(e, e * c(x[, 1]))
  return(gmat)
}

x <- as.matrix(cbind(rm, r))
res_black <- gmm(g, x = x, t0 = rep(0, 11))

tidy(res_black)
tidy(res_black, conf.int = TRUE)

# APT test with Fama-French factors and GMM

f1 <- zm
f2 <- Finance[1:300, "hml"] - rf
f3 <- Finance[1:300, "smb"] - rf
h <- cbind(f1, f2, f3)
res2 <- gmm(z ~ f1 + f2 + f3, x = h)

td2 <- tidy(res2, conf.int = TRUE)
td2

# coefficient plot
td2 %>%
  mutate(variable = reorder(term, estimate)) %>%
  ggplot(aes(estimate, variable)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_vline(xintercept = 0, color = "red", lty = 2)

```

glance.ivreg

Glance at a(n) ivreg object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'ivreg'
glance(x, diagnostics = FALSE, ...)
```

Arguments

<code>x</code>	An ivreg object created by a call to <code>AER::ivreg()</code> .
<code>diagnostics</code>	Logical indicating whether or not to return the Wu-Hausman and Sargan diagnostic information.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

This tidier currently only supports ivreg-classed objects outputted by the AER package. The ivreg package also outputs objects of class `ivreg`, and will be supported in a later release.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>adj.r.squared</code>	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
<code>df</code>	Degrees of freedom used by the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>nobs</code>	Number of observations used.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>sigma</code>	Estimated standard error of the residuals.
<code>statistic</code>	Wald test statistic.
<code>p.value</code>	P-value for the Wald test.

Note

Beginning 0.7.0, `glance.ivreg` returns statistics for the Wu-Hausman test for endogeneity and the Sargan test of overidentifying restrictions. Sargan test values are returned as NA if the number of instruments is not greater than the number of endogenous regressors.

See Also[glance\(\)](#), [AER::ivreg\(\)](#)Other ivreg tidiers: [augment.ivreg\(\)](#), [tidy.ivreg\(\)](#)**Examples**

```
# load libraries for models and data
library(AER)

# load data
data("CigarettesSW", package = "AER")

# fit model
ivr <- ivreg(
  log(packs) ~ income | population,
  data = CigarettesSW,
  subset = year == "1995"
)

# summarize model fit with tidiers
tidy(ivr)
tidy(ivr, conf.int = TRUE)
tidy(ivr, conf.int = TRUE, instruments = TRUE)

augment(ivr)
augment(ivr, data = CigarettesSW)
augment(ivr, newdata = CigarettesSW)

glance(ivr)
```

`glance.kmeans`*Glance at a(n) kmeans object*

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'kmeans'
glance(x, ...)
```

Arguments

`x` A kmeans object created by `stats::kmeans()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>betweenss</code>	The total between-cluster sum of squares.
<code>iter</code>	Iterations of algorithm/fitting procedure completed.
<code>tot.withinss</code>	The total within-cluster sum of squares.
<code>totss</code>	The total sum of squares.

See Also

`glance()`, `stats::kmeans()`

Other kmeans tidiers: `augment.kmeans()`, `tidy.kmeans()`

Examples

```
library(cluster)
library(modeldata)
library(dplyr)

data(hpc_data)

x <- hpc_data[, 2:5]

fit <- pam(x, k = 4)

tidy(fit)
glance(fit)
augment(fit, x)
```

glance.lavaan	<i>Glance at a(n) lavaan object</i>
---------------	-------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'lavaan'
glance(x, ...)
```

Arguments

x	A lavaan object, such as those returned from <code>lavaan::cfa()</code> , and <code>lavaan::sem()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A one-row `tibble::tibble` with columns:

<code>chisq</code>	Model chi squared
<code>npar</code>	Number of parameters in the model
<code>rmsea</code>	Root mean square error of approximation
<code>rmsea.conf.high</code>	95 percent upper bound on RMSEA

<code>srmr</code>	Standardised root mean residual
<code>agfi</code>	Adjusted goodness of fit
<code>cfi</code>	Comparative fit index
<code>tli</code>	Tucker Lewis index
<code>AIC</code>	Akaike information criterion
<code>BIC</code>	Bayesian information criterion
<code>ngroups</code>	Number of groups in model
<code>nobs</code>	Number of observations included
<code>norig</code>	Number of observation in the original dataset
<code>nexcluded</code>	Number of excluded observations
<code>converged</code>	Logical - Did the model converge
<code>estimator</code>	Estimator used
<code>missing_method</code>	Method for eliminating missing data

For further recommendations on reporting SEM and CFA models see Schreiber, J. B. (2017). Update to core reporting practices in structural equation modeling. *Research in Social and Administrative Pharmacy*, 13(3), 634-643. <https://doi.org/10.1016/j.sapharm.2016.06.006>

See Also

[glance\(\)](#), [lavaan::cfa\(\)](#), [lavaan::sem\(\)](#), [lavaan::fitmeasures\(\)](#)

Other lavaan tidiers: [tidy.lavaan\(\)](#)

Examples

```
library(lavaan)

# fit model
cfa.fit <- cfa(
  "F =~ x1 + x2 + x3 + x4 + x5",
  data = HolzingerSwineford1939, group = "school"
)

# summarize model fit with tidiers
glance(cfa.fit)
```

glance.lm	<i>Glance at a(n) lm object</i>
-----------	---------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'lm'
glance(x, ...)
```

Arguments

x	An <code>lm</code> object created by <code>stats::lm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

adj.r.squared	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df.residual	Residual degrees of freedom.

logLik	The log-likelihood of the model. [stats::logLik()] may be a useful reference.
nobs	Number of observations used.
p.value	P-value corresponding to the test statistic.
r.squared	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
sigma	Estimated standard error of the residuals.
statistic	Test statistic.
df	The degrees for freedom from the numerator of the overall F-statistic. This is new in broom 0.7.0. Previously, this reported the rank of the design matrix, which is one more than the numerator degrees of freedom of the overall F-statistic.

See Also

[glance\(\)](#), [glance.summary.lm\(\)](#)

Other lm tidiers: [augment.glm\(\)](#), [augment.lm\(\)](#), [glance.glm\(\)](#), [glance.summary.lm\(\)](#), [glance.svyglm\(\)](#), [tidy.glm\(\)](#), [tidy.lm.beta\(\)](#), [tidy.lm\(\)](#), [tidy.mlmm\(\)](#), [tidy.summary.lm\(\)](#)

Examples

```
library(ggplot2)
library(dplyr)

mod <- lm(mpg ~ wt + qsec, data = mtcars)

tidy(mod)
glance(mod)

# coefficient plot
d <- tidy(mod, conf.int = TRUE)

ggplot(d, aes(estimate, term, xmin = conf.low, xmax = conf.high, height = 0)) +
  geom_point() +
  geom_vline(xintercept = 0, lty = 4) +
  geom_errorbarh()

# aside: There are tidy() and glance() methods for lm.summary objects too.
# this can be useful when you want to conserve memory by converting large lm
# objects into their leaner summary.lm equivalents.
s <- summary(mod)
tidy(s, conf.int = TRUE)
glance(s)

augment(mod)
augment(mod, mtcars, interval = "confidence")

# predict on new data
newdata <- mtcars %>%
```



```
head(6) %>%
  mutate(wt = wt + 1)
augment(mod, newdata = newdata)

# ggplot2 example where we also construct 95% prediction interval

# simpler bivariate model since we're plotting in 2D
mod2 <- lm(mpg ~ wt, data = mtcars)

au <- augment(mod2, newdata = newdata, interval = "prediction")

ggplot(au, aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted)) +
  geom_ribbon(aes(ymin = .lower, ymax = .upper), col = NA, alpha = 0.3)

# predict on new data without outcome variable. Output does not include .resid
newdata <- newdata %>%
  select(-mpg)

augment(mod, newdata = newdata)

au <- augment(mod, data = mtcars)

ggplot(au, aes(.hat, .std.resid)) +
  geom_vline(size = 2, colour = "white", xintercept = 0) +
  geom_hline(size = 2, colour = "white", yintercept = 0) +
  geom_point() +
  geom_smooth(se = FALSE)

plot(mod, which = 6)

ggplot(au, aes(.hat, .cooksd)) +
  geom_vline(xintercept = 0, colour = NA) +
  geom_abline(slope = seq(0, 3, by = 0.5), colour = "white") +
  geom_smooth(se = FALSE) +
  geom_point()

# column-wise models
a <- matrix(rnorm(20), nrow = 10)
b <- a + rnorm(length(a))
result <- lm(b ~ a)

tidy(result)
```

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'lmodel2'
glance(x, ...)
```

Arguments

x	A <code>lmodel2</code> object returned by <code>lmodel2::lmodel2()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

nobs	Number of observations used.
p.value	P-value corresponding to the test statistic.
r.squared	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
theta	Angle between OLS lines <code>'lm(y ~ x)'</code> and <code>'lm(x ~ y)'</code>
H	H statistic for computing confidence interval of major axis slope

See Also

`glance()`, `lmodel2::lmodel2()`

Other `lmodel2` tidiers: `tidy.lmodel2()`

Examples

```
# load libraries for models and data
library(lmodel2)

data(mod2ex2)
Ex2.res <- lmodel2(Prey ~ Predators, data = mod2ex2, "relative", "relative", 99)
Ex2.res

# summarize model fit with tidiers + visualization
tidy(Ex2.res)
glance(Ex2.res)

# this allows coefficient plots with ggplot2
library(ggplot2)

ggplot(tidy(Ex2.res), aes(estimate, term, color = method)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high))
```

glance.lmRob

Glance at a(n) lmRob object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'lmRob'
glance(x, ...)
```

Arguments

- `x` A `lmRob` object returned from `robust::lmRob()`.
- `...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>deviance</code>	Deviance of the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>nobs</code>	Number of observations used.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>sigma</code>	Estimated standard error of the residuals.

See Also

`robust::lmRob()`

Other robust tidiers: `augment.lmRob()`, `glance.glmRob()`, `tidy.glmRob()`, `tidy.lmRob()`

Examples

```
# load modeling library
library(robust)

# fit model
m <- lmRob(mpg ~ wt, data = mtcars)

# summarize model fit with tidiers
tidy(m)
augment(m)
glance(m)
```

glance.lmrob

*Glance at a(n) lmrob object***Description**

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'lmrob'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>lmrob</code> object returned from <code>robustbase::lmrob()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>df.residual</code>	Residual degrees of freedom.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>sigma</code>	Estimated standard error of the residuals.

See Also

[robustbase::lmrob\(\)](#)

Other robustbase tidiers: [augment.glmrob\(\)](#), [augment.lmrob\(\)](#), [tidy.glmrob\(\)](#), [tidy.lmrob\(\)](#)

Examples

```
if (requireNamespace("robustbase", quietly = TRUE)) {

# load libraries for models and data
library(robustbase)

data(coleman)
set.seed(0)

m <- lmrob(Y ~ ., data = coleman)
tidy(m)
augment(m)
glance(m)

data(carrots)

Rfit <- glmrob(cbind(success, total - success) ~ logdose + block,
  family = binomial, data = carrots, method = "Mqle",
  control = glmrobMqle.control(tcc = 1.2)
)

tidy(Rfit)
augment(Rfit)

}
```

glance.margins

Glance at a(n) margins object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'margins'
glance(x, ...)
```

Arguments

`x` A margins object returned from `margins::margins()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>adj.r.squared</code>	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
<code>df</code>	Degrees of freedom used by the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>nobs</code>	Number of observations used.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>sigma</code>	Estimated standard error of the residuals.
<code>statistic</code>	Test statistic.

Examples

```
# load libraries for models and data
library(margins)

# example 1: logit model
mod_log <- glm(am ~ cyl + hp + wt, data = mtcars, family = binomial)

# get tidied "naive" model coefficients
tidy(mod_log)

# convert to marginal effects with margins()
marg_log <- margins(mod_log)
```

```

# get tidied marginal effects
tidy(marg_log)
tidy(marg_log, conf.int = TRUE)

# requires running the underlying model again. quick for this example
glance(marg_log)

# augmenting `margins` outputs isn't supported, but
# you can get the same info by running on the underlying model
augment(mod_log)

# example 2: threeway interaction terms
mod_ie <- lm(mpg ~ wt * cyl * disp, data = mtcars)

# get tidied "naive" model coefficients
tidy(mod_ie)

# convert to marginal effects with margins()
marg_ie0 <- margins(mod_ie)
# get tidied marginal effects
tidy(marg_ie0)
glance(marg_ie0)

# marginal effects evaluated at specific values of a variable (here: cyl)
marg_ie1 <- margins(mod_ie, at = list(cyl = c(4,6,8)))

# summarize model fit with tidiers
tidy(marg_ie1)

# marginal effects of one interaction variable (here: wt), modulated at
# specific values of the two other interaction variables (here: cyl and drat)
marg_ie2 <- margins(mod_ie,
                    variables = "wt",
                    at = list(cyl = c(4,6,8), drat = c(3, 3.5, 4)))

# summarize model fit with tidiers
tidy(marg_ie2)

```

glance.Mclust

Glance at a(n) Mclust object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'Mclust'
glance(x, ...)
```

Arguments

x	An Mclust object return from <code>mclust::Mclust()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

BIC	Bayesian Information Criterion for the model.
df	Degrees of freedom used by the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
model	A string denoting the model type with optimal BIC
G	Number mixture components in optimal model
hypvol	If the other model contains a noise component, the value of the hypervolume parameter. Otherwise 'NA'.

Examples

```
# load library for models and data
library(mclust)

# load data manipulation libraries
library(dplyr)
```

```
library(tibble)
library(purrr)
library(tidyr)

set.seed(27)

centers <- tibble(
  cluster = factor(1:3),
  # number points in each cluster
  num_points = c(100, 150, 50),
  # x1 coordinate of cluster center
  x1 = c(5, 0, -3),
  # x2 coordinate of cluster center
  x2 = c(-1, 1, -2)
)

points <- centers %>%
  mutate(
    x1 = map2(num_points, x1, rnorm),
    x2 = map2(num_points, x2, rnorm)
  ) %>%
  select(-num_points, -cluster) %>%
  unnest(c(x1, x2))

# fit model
m <- Mclust(points)

# summarize model fit with tidiers
tidy(m)
augment(m, points)
glance(m)
```

glance.mfx

Glance at a(n) mfx object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'mfx'
glance(x, ...)

## S3 method for class 'logitmfx'
glance(x, ...)

## S3 method for class 'negbinmfx'
glance(x, ...)

## S3 method for class 'poissonmfx'
glance(x, ...)

## S3 method for class 'probitmfx'
glance(x, ...)
```

Arguments

`x` A `logitmfx`, `negbinmfx`, `poissonmfx`, or `probitmfx` object. (Note that `betamfx` objects receive their own set of tidiers.)

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

This generic `glance` method wraps `glance.glm()` for applicable objects from the `mfx` package.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>AIC</code>	Akaike's Information Criterion for the model.
<code>BIC</code>	Bayesian Information Criterion for the model.
<code>deviance</code>	Deviance of the model.
<code>df.null</code>	Degrees of freedom used by the null model.
<code>df.residual</code>	Residual degrees of freedom.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
<code>nobs</code>	Number of observations used.
<code>null.deviance</code>	Deviance of the null model.

See Also

```
glance.glm(), mfx::logitmfx(), mfx::negbinmfx(), mfx::poissonmfx(), mfx::probitmfx()
Other mfx tidiers: augment.betamfx(), augment.mfx(), glance.betamfx(), tidy.betamfx(),
tidy.mfx()
```

Examples

```
# load libraries for models and data
library(mfx)

# get the marginal effects from a logit regression
mod_logmfx <- logitmfx(am ~ cyl + hp + wt, atmean = TRUE, data = mtcars)

tidy(mod_logmfx, conf.int = TRUE)

# compare with the naive model coefficients of the same logit call
tidy(
  glm(am ~ cyl + hp + wt, family = binomial, data = mtcars), conf.int = TRUE
)

augment(mod_logmfx)
glance(mod_logmfx)

# another example, this time using probit regression
mod_probmfx <- probitmfx(am ~ cyl + hp + wt, atmean = TRUE, data = mtcars)

tidy(mod_probmfx, conf.int = TRUE)
augment(mod_probmfx)
glance(mod_probmfx)
```

glance.mjoint

Glance at a(n) mjoint object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'mjoint'
glance(x, ...)
```

Arguments

`x` An `mjoint` object returned from `joineRML::mjoint()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
sigma2_j	The square root of the estimated residual variance for the <code>j</code> -th longitudinal process

See Also

`glance()`, `joineRML::mjoint()`

Other `mjoint` tidiers: `tidy.mjoint()`

Examples

```
# broom only skips running these examples because the example models take a
# while to generate they should run just fine, though!
## Not run:

# load libraries for models and data
library(joineRML)

# fit a joint model with bivariate longitudinal outcomes
data(heart.valve)

hvd <- heart.valve[!is.na(heart.valve$log.grad) &
```

```

!is.na(heart.valve$log.lvmi) &
heart.valve$num <= 50, ]

fit <- mjoint(
  formLongFixed = list(
    "grad" = log.grad ~ time + sex + hs,
    "lvmi" = log.lvmi ~ time + sex
  ),
  formLongRandom = list(
    "grad" = ~ 1 | num,
    "lvmi" = ~ time | num
  ),
  formSurv = Surv(fuyrs, status) ~ age,
  data = hvd,
  inits = list("gamma" = c(0.11, 1.51, 0.80)),
  timeVar = "time"
)

# extract the survival fixed effects
tidy(fit)

# extract the longitudinal fixed effects
tidy(fit, component = "longitudinal")

# extract the survival fixed effects with confidence intervals
tidy(fit, ci = TRUE)

# extract the survival fixed effects with confidence intervals based
# on bootstrapped standard errors
bSE <- bootSE(fit, nboot = 5, safe.boot = TRUE)
tidy(fit, boot_se = bSE, ci = TRUE)

# augment original data with fitted longitudinal values and residuals
hvd2 <- augment(fit)

# extract model statistics
glance(fit)

## End(Not run)

```

glance.mlogit

Glance at a(n) mlogit object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'mlogit'
glance(x, ...)
```

Arguments

`x` an object returned from `mlogit::mlogit()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
rho2	McFadden's rho squared with respect to a market shares (constants-only) model.
rho20	McFadden's rho squared with respect to an equal shares (no information) model.

See Also

`glance()`, `mlogit::mlogit()`

Other mlogit tidiers: `augment.mlogit()`, `tidy.mlogit()`

Examples

```
# load libraries for models and data
library(mlogit)

data("Fishing", package = "mlogit")
Fish <- dfix(Fishing, varying = 2:9, shape = "wide", choice = "mode")

# fit model
m <- mlogit(mode ~ price + catch | income, data = Fish)

# summarize model fit with tidiers
tidy(m)
augment(m)
glance(m)
```

glance.muhaz

Glance at a(n) muhaz object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'muhaz'
glance(x, ...)
```

Arguments

<code>x</code>	A muhaz object returned by <code>muhaz::muhaz()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>max.hazard</code>	Maximal estimated hazard.
<code>max.time</code>	The maximum observed event or censoring time.
<code>min.hazard</code>	Minimal estimated hazard.
<code>min.time</code>	The minimum observed event or censoring time.
<code>nobs</code>	Number of observations used.

See Also

`glance()`, `mu haz::mu haz()`

Other mu haz tidiers: `tidy.mu haz()`

Examples

```
# load libraries for models and data
library(mu haz)
library(survival)

# fit model
x <- mu haz(ovarian$futime, ovarian$fustat)

# summarize model fit with tidiers
tidy(x)
glance(x)
```

<code>glance.multinom</code>	<i>Glance at a(n) multinom object</i>
------------------------------	---------------------------------------

Description

`Glance` accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

`Glance` never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'multinom'
glance(x, ...)
```

Arguments

x	A <code>multinom</code> object returned from <code>nnet::multinom()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
deviance	Deviance of the model.
edf	The effective degrees of freedom.
nobs	Number of observations used.

See Also

`glance()`, `nnet::multinom()`
Other multinom tidiers: `tidy.multinom()`

Examples

```
# load libraries for models and data
library(nnet)
library(MASS)

example(birthwt)
```

```

bwt.mu <- multinom(low ~ ., bwt)

tidy(bwt.mu)
glance(bwt.mu)

# or, for output from a multinomial logistic regression
fit.gear <- multinom(gear ~ mpg + factor(am), data = mtcars)
tidy(fit.gear)
glance(fit.gear)

```

glance.negbin

Glance at a(n) negbin object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'negbin'
glance(x, ...)

```

Arguments

`x` A negbin object returned by `MASS::glm.nb()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df.null	Degrees of freedom used by the null model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
null.deviance	Deviance of the null model.

See Also

`glance()`, `MASS::glm.nb()`

Other `glm.nb` tidiers: `tidy.negbin()`

Examples

```
# load libraries for models and data
library(MASS)

# fit model
r <- glm.nb(Days ~ Sex/(Age + Eth*Lrn), data = quine)

# summarize model fit with tidiers
tidy(r)
glance(r)
```

`glance.nlrq`

Glance at a(n) nlrq object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'nlrq'
glance(x, ...)
```

Arguments

`x` A `nlrq` object returned from `quantreg::nlrq()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
<code>tau</code>	Quantile.

See Also

`glance()`, `quantreg::nlrq()`

Other `quantreg` tidiers: `augment.nlrq()`, `augment.rqs()`, `augment.rq()`, `glance.rq()`, `tidy.nlrq()`, `tidy.rqs()`, `tidy.rq()`

Examples

```
# load modeling library
library(quantreg)

# build artificial data with multiplicative error
set.seed(1)
dat <- NULL
```

```

dat$x <- rep(1:25, 20)
dat$y <- SSlogis(dat$x, 10, 12, 2) * rnorm(500, 1, 0.1)

# fit the median using nlrq
mod <- nlrq(y ~ SSlogis(x, Asym, mid, scal),
           data = dat, tau = 0.5, trace = TRUE)

# summarize model fit with tidiers
tidy(mod)
glance(mod)
augment(mod)

```

glance.nls

Glance at a(n) nls object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'nls'
glance(x, ...)

```

Arguments

- | | |
|-----|---|
| x | An nls object returned from <code>stats::nls()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df.residual	Residual degrees of freedom.
finTol	The achieved convergence tolerance.
isConv	Whether the fit successfully converged.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
sigma	Estimated standard error of the residuals.

See Also

`tidy`, `stats::nls()`

Other nls tidiers: `augment.nls()`, `tidy.nls()`

Examples

```
# fit model
n <- nls(mpg ~ k * e^wt, data = mtcars, start = list(k = 1, e = 2))

# summarize model fit with tidiers + visualization
tidy(n)
augment(n)
glance(n)

library(ggplot2)

ggplot(augment(n), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))

newdata <- head(mtcars)
newdata$wt <- newdata$wt + 1

augment(n, newdata = newdata)
```

glance.orcutt

Glance at a(n) orcutt object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'orcutt'
glance(x, ...)
```

Arguments

- | | |
|-----|---|
| x | An orcutt object returned from <code>orcutt::cochrane.orcutt()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

- | | |
|-----------------------------|--|
| <code>adj.r.squared</code> | Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account. |
| <code>dw.original</code> | Durbin-Watson statistic of original fit. |
| <code>dw.transformed</code> | Durbin-Watson statistic of transformed fit. |
| <code>nobs</code> | Number of observations used. |

number.interaction	Number of interactions.
p.value.original	P-value of original Durbin-Watson statistic.
p.value.transformed	P-value of autocorrelation after transformation.
r.squared	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
rho	Spearman's rho autocorrelation

See Also

[glance\(\)](#), [orcutt::cochrane.orcutt\(\)](#)
 Other orcutt tidiers: [tidy.orcutt\(\)](#)

Examples

```
# load libraries for models and data
library(orcutt)

# fit model and summarize results
reg <- lm(mpg ~ wt + qsec + disp, mtcars)
tidy(reg)

co <- cochrane.orcutt(reg)
tidy(co)
glance(co)
```

glance.pam

Glance at a(n) pam object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'pam'  
glance(x, ...)
```

Arguments

`x` An pam object returned from `cluster::pam()`

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

```
avg.silhouette.width
```

The average silhouette width for the dataset.

See Also

`glance()`, `cluster::pam()`

Other pam tidiers: `augment.pam()`, `tidy.pam()`

Examples

```
# load libraries for models and data  
library(dplyr)  
library(ggplot2)  
library(cluster)  
library(modeldata)  
data(hpc_data)  
  
x <- hpc_data[, 2:5]  
p <- pam(x, k = 4)  
  
# summarize model fit with tidiers + visualization  
tidy(p)  
glance(p)  
augment(p, x)  
  
augment(p, x) %>%  
  ggplot(aes(compounds, input_fields)) +
```

```
geom_point(aes(color = .cluster)) +
geom_text(aes(label = cluster), data = tidy(p), size = 10)
```

glance.plm

Glance at a(n) plm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'plm'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>plm</code> object returned by <code>plm::plm()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>adj.r.squared</code>	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
----------------------------	--

deviance	Deviance of the model.
df.residual	Residual degrees of freedom.
nobs	Number of observations used.
p.value	P-value corresponding to the test statistic.
r.squared	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
statistic	F-statistic

See Also

[glance\(\)](#), [plm::plm\(\)](#)

Other plm tidiers: [augment.plm\(\)](#), [tidy.plm\(\)](#)

Examples

```
# load libraries for models and data
library(plm)

# load data
data("Produc", package = "plm")

# fit model
zz <- plm(log(gsp) ~ log(pcap) + log(pc) + log(emp) + unemp,
  data = Produc, index = c("state", "year")
)

# summarize model fit with tidiers
summary(zz)

tidy(zz)
tidy(zz, conf.int = TRUE)
tidy(zz, conf.int = TRUE, conf.level = 0.9)

augment(zz)
glance(zz)
```

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'poLCA'
glance(x, ...)
```

Arguments

- | | |
|------------------|---|
| <code>x</code> | A poLCA object returned from <code>poLCA::poLCA()</code> . |
| <code>...</code> | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
<code>chi.squared</code>	The Pearson Chi-Square goodness of fit statistic for multiway tables.
<code>df</code>	Degrees of freedom used by the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
<code>nobs</code>	Number of observations used.
<code>g.squared</code>	The likelihood ratio/deviance statistic

See Also

[glance\(\)](#), [poLCA::poLCA\(\)](#)

Other poLCA tidiers: [augment.poLCA\(\)](#), [tidy.poLCA\(\)](#)

Examples

```
# load libraries for models and data
library(poLCA)
library(dplyr)

# generate data
data(values)

f <- cbind(A, B, C, D) ~ 1

# fit model
M1 <- poLCA(f, values, nclass = 2, verbose = FALSE)

M1

# summarize model fit with tidiers + visualization
tidy(M1)
augment(M1)
glance(M1)

library(ggplot2)

ggplot(tidy(M1), aes(factor(class), estimate, fill = factor(outcome))) +
  geom_bar(stat = "identity", width = 1) +
  facet_wrap(~variable)

# three-class model with a single covariate.
data(election)

f2a <- cbind(
  MORALG, CARESG, KNOWG, LEADG, DISHONG, INTELG,
  MORALB, CARESB, KNOWB, LEADB, DISHONB, INTELB
) ~ PARTY

nes2a <- poLCA(f2a, election, nclass = 3, nrep = 5, verbose = FALSE)

td <- tidy(nes2a)
td

ggplot(td, aes(outcome, estimate, color = factor(class), group = class)) +
  geom_line() +
  facet_wrap(~variable, nrow = 2) +
  theme(axis.text.x = element_text(angle = 90, hjust = 1))

au <- augment(nes2a)
```

```

au

count(au, .class)

# if the original data is provided, it leads to NAs in new columns
# for rows that weren't predicted
au2 <- augment(nes2a, data = election)

au2

dim(au2)

```

glance.polr

Glance at a(n) polr object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'polr'
glance(x, ...)

```

Arguments

- | | |
|-----|---|
| x | A <code>polr</code> object returned from <code>MASS::polr()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df.residual	Residual degrees of freedom.
edf	The effective degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.

See Also

[tidy](#), [MASS::polr\(\)](#)

Other ordinal tidiers: [augment.clm\(\)](#), [augment.polr\(\)](#), [glance.clmm\(\)](#), [glance.clm\(\)](#), [glance.svyolr\(\)](#), [tidy.clmm\(\)](#), [tidy.clm\(\)](#), [tidy.polr\(\)](#), [tidy.svyolr\(\)](#)

Examples

```
# load libraries for models and data
library(MASS)

# fit model
fit <- polr(Sat ~ Infl + Type + Cont, weights = Freq, data = housing)

# summarize model fit with tidiers
tidy(fit, exponentiate = TRUE, conf.int = TRUE)

glance(fit)
augment(fit, type.predict = "class")

fit2 <- polr(factor(gear) ~ am + mpg + qsec, data = mtcars)

tidy(fit, p.values = TRUE)
```


Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'pyears'
glance(x, ...)
```

Arguments

`x` A pyears object returned from `survival::pyears()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>nobs</code>	Number of observations used.
<code>total</code>	total number of person-years tabulated
<code>offtable</code>	total number of person-years off table

See Also

`glance()`, `survival::pyears()`

Other pyears tidiers: `tidy.pyyears()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# generate and format data
temp.yr <- tcut(mgus$dxyr, 55:92, labels = as.character(55:91))
temp.age <- tcut(mgus$age, 34:101, labels = as.character(34:100))
ptime <- ifelse(is.na(mgus$pctime), mgus$futime, mgus$pctime)
pstat <- ifelse(is.na(mgus$pctime), 0, 1)
pfit <- pyears(Surv(ptime / 365.25, pstat) ~ temp.yr + temp.age + sex, mgus,
  data.frame = TRUE
)

# summarize model fit with tidiers
tidy(pfit)
glance(pfit)

# if data.frame argument is not given, different information is present in
# output
pfit2 <- pyears(Surv(ptime / 365.25, pstat) ~ temp.yr + temp.age + sex, mgus)

tidy(pfit2)
glance(pfit2)
```

glance.ridgeIm

Glance at a(n) ridgeIm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'ridgeIm'
glance(x, ...)
```

Arguments

- `x` A `ridgelm` object returned from `MASS::lm.ridge()`.
- `...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

This is similar to the output of `select.ridgelm`, but it is returned rather than printed.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>kHKB</code>	modified HKB estimate of the ridge constant
<code>kLW</code>	modified L-W estimate of the ridge constant
<code>lambdaGCV</code>	choice of lambda that minimizes GCV

See Also

`glance()`, `MASS::select.ridgelm()`, `MASS::lm.ridge()`

Other `ridgelm` tidiers: `tidy.ridgelm()`

Examples

```
# load libraries for models and data
library(MASS)

names(longley)[1] <- "y"

# fit model and summarize results
fit1 <- lm.ridge(y ~ ., longley)
tidy(fit1)

fit2 <- lm.ridge(y ~ ., longley, lambda = seq(0.001, .05, .001))
td2 <- tidy(fit2)
g2 <- glance(fit2)

# coefficient plot
library(ggplot2)
ggplot(td2, aes(lambda, estimate, color = term)) +
```

```

geom_line()

# GCV plot
ggplot(td2, aes(lambda, GCV)) +
  geom_line()

# add line for the GCV minimizing estimate
ggplot(td2, aes(lambda, GCV)) +
  geom_line() +
  geom_vline(xintercept = g2$lambdaGCV, col = "red", lty = 2)

```

glance.rlm

Glance at a(n) rlm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'rlm'
glance(x, ...)

```

Arguments

- | | |
|------------------|---|
| <code>x</code> | An <code>rlm</code> object returned by <code>MASS::rlm()</code> . |
| <code>...</code> | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
converged	Logical indicating if the model fitting procedure was successful and converged.
deviance	Deviance of the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
sigma	Estimated standard error of the residuals.

See Also

`glance()`, `MASS::rlm()`

Other rlm tidiers: `augment.rlm()`, `tidy.rlm()`

Examples

```
# load libraries for models and data
library(MASS)

# fit model
r <- rlm(stack.loss ~ ., stackloss)

# summarize model fit with tidiers
tidy(r)
augment(r)
glance(r)
```

glance.rma

Glance at a(n) rma object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'rma'
glance(x, ...)
```

Arguments

`x` An `rma` object such as those created by `metafor::rma()`, `metafor::rma.uni()`, `metafor::rma.glmm()`, `metafor::rma.mh()`, `metafor::rma.mv()`, or `metafor::rma.peto()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>cochran.qe</code>	In meta-analysis, test statistic for the Cochran's Q_e test of residual heterogeneity.
<code>cochran.qm</code>	In meta-analysis, test statistic for the Cochran's Q_m omnibus test of coefficients.
<code>df.residual</code>	Residual degrees of freedom.
<code>h.squared</code>	Value of the H-Squared statistic.
<code>i.squared</code>	Value of the I-Squared statistic.
<code>measure</code>	The measure used in the meta-analysis.
<code>method</code>	Which method was used.
<code>nobs</code>	Number of observations used.
<code>p.value.cochran.qe</code>	In meta-analysis, p-value for the Cochran's Q_e test of residual heterogeneity.
<code>p.value.cochran.qm</code>	In meta-analysis, p-value for the Cochran's Q_m omnibus test of coefficients.
<code>tau.squared</code>	In meta-analysis, estimated amount of residual heterogeneity.
<code>tau.squared.se</code>	In meta-analysis, standard error of residual heterogeneity.

Examples

```
library(metafor)

df <-
  escalc(
    measure = "RR",
    ai = tpos,
    bi = tneg,
    ci = cpos,
    di = cneg,
    data = dat.bcg
  )

meta_analysis <- rma(yi, vi, data = df, method = "EB")

glance(meta_analysis)
```

glance.rq

Glance at a(n) rq object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'rq'
glance(x, ...)
```

Arguments

x An rq object returned from `quantreg::rq()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

Only models with a single tau value may be passed. For multiple values, please use a `purrr::map()` workflow instead, e.g.

```
taus %>%
  map(function(tau_val) rq(y ~ x, tau = tau_val)) %>%
  map_dfr(glance)
```

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
tau	Quantile.

See Also

[glance\(\)](#), [quantreg::rq\(\)](#)

Other quantreg tidiers: [augment.nlrq\(\)](#), [augment.rqs\(\)](#), [augment.rq\(\)](#), [glance.nlrq\(\)](#), [tidy.nlrq\(\)](#), [tidy.rqs\(\)](#), [tidy.rq\(\)](#)

Examples

```
# load modeling library and data
library(quantreg)

data(stackloss)

# median (l1) regression fit for the stackloss data.
mod1 <- rq(stack.loss ~ stack.x, .5)

# weighted sample median
mod2 <- rq(rnorm(50) ~ 1, weights = runif(50))
```



```

# summarize model fit with tidiers
tidy(mod1)
glance(mod1)
augment(mod1)

tidy(mod2)
glance(mod2)
augment(mod2)

# varying tau to generate an rqs object
mod3 <- rq(stack.loss ~ stack.x, tau = c(.25, .5))

tidy(mod3)
augment(mod3)

# glance cannot handle rqs objects like `mod3`--use a purrr
# `map`-based workflow instead

```

glance.sarlm

Glance at a(n) spatialreg object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```

## S3 method for class 'sarlm'
glance(x, ...)

```

Arguments

x An object returned from `spatialreg::lagsarlm()` or `spatialreg::errorsarlm()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.

See Also

`glance()`, `spatialreg::lagsarlm()`, `spatialreg::errorsarlm()`, `spatialreg::sacsarlm()`

Other `spatialreg` tidiers: `augment.sarlm()`, `tidy.sarlm()`

Examples

```
# load libraries for models and data
library(spatialreg)
library(spdep)

# load data
data(oldcol, package = "spdep")

listw <- nb2listw(COL.nb, style = "W")

# fit model
crime_sar <-
lagsarlm(CRIME ~ INC + HOVAL,
         data = COL.OLD,
         listw = listw,
         method = "eigen")

# summarize model fit with tidiers
tidy(crime_sar)
tidy(crime_sar, conf.int = TRUE)
```

```

glance(crime_sar)
augment(crime_sar)

# fit another model
crime_sem <- errorsarlm(CRIME ~ INC + HOVAL, data = COL.OLD, listw)

# summarize model fit with tidiers
tidy(crime_sem)
tidy(crime_sem, conf.int = TRUE)
glance(crime_sem)
augment(crime_sem)

# fit another model
crime_sac <- sacsarlml(CRIME ~ INC + HOVAL, data = COL.OLD, listw)

# summarize model fit with tidiers
tidy(crime_sac)
tidy(crime_sac, conf.int = TRUE)
glance(crime_sac)
augment(crime_sac)

```

glance.smooth.spline *Tidy a(n) smooth.spline object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'smooth.spline'
glance(x, ...)
```

Arguments

x	A smooth.spline object returned from <code>stats::smooth.spline()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>crit</code>	Minimized criterion
<code>cv.crit</code>	Cross-validation score
<code>df</code>	Degrees of freedom used by the model.
<code>lambda</code>	Choice of lambda corresponding to ‘spar’.
<code>nobs</code>	Number of observations used.
<code>pen.crit</code>	Penalized criterion.
<code>spar</code>	Smoothing parameter.

See Also

`augment()`, `stats::smooth.spline()`

Other smoothing spline tidiers: `augment.smooth.spline()`

Examples

```
# fit model
spl <- smooth.spline(mtcars$wt, mtcars$mpg, df = 4)

# summarize model fit with tidiers
augment(spl, mtcars)

# calls original columns x and y
augment(spl)

library(ggplot2)
ggplot(augment(spl, mtcars), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))
```

`glance.speedglm`

Glance at a(n) speedglm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'speedglm'
glance(x, ...)
```

Arguments

x	A <code>speedglm</code> object returned from <code>speedglm::speedglm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df.null	Degrees of freedom used by the null model.
df.residual	Residual degrees of freedom.
logLik	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
nobs	Number of observations used.
null.deviance	Deviance of the null model.

See Also

[speedglm::speedlm\(\)](#)

Other `speedlm` tidiers: [augment.speedlm\(\)](#), [glance.speedlm\(\)](#), [tidy.speedglm\(\)](#), [tidy.speedlm\(\)](#)

Examples

```
# load libraries for models and data
library(speedglm)

# generate data
clotting <- data.frame(
  u = c(5, 10, 15, 20, 30, 40, 60, 80, 100),
  lot1 = c(118, 58, 42, 35, 27, 25, 21, 19, 18)
)

# fit model
fit <- speedglm(lot1 ~ log(u), data = clotting, family = Gamma(log))

# summarize model fit with tidiers
tidy(fit)
glance(fit)
```

glance.speedlm

Glance at a(n) speedlm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'speedlm'
glance(x, ...)
```

Arguments

x A speedlm object returned from `speedglm::speedlm()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>adj.r.squared</code>	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
<code>AIC</code>	Akaike's Information Criterion for the model.
<code>BIC</code>	Bayesian Information Criterion for the model.
<code>deviance</code>	Deviance of the model.
<code>df</code>	Degrees of freedom used by the model.
<code>df.residual</code>	Residual degrees of freedom.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
<code>nobs</code>	Number of observations used.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>statistic</code>	F-statistic.

See Also

[speedglm::speedlm\(\)](#)

Other `speedlm` tidiers: [augment.speedlm\(\)](#), [glance.speedglm\(\)](#), [tidy.speedglm\(\)](#), [tidy.speedlm\(\)](#)

Examples

```
# load modeling library
library(speedglm)

# fit model
mod <- speedlm(mpg ~ wt + qsec, data = mtcars, fitted = TRUE)

# summarize model fit with tidiers
tidy(mod)
glance(mod)
augment(mod)
```

glance.summary.lm *Glance at a(n) summary.lm object*

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'summary.lm'
glance(x, ...)
```

Arguments

- | | |
|-----|---|
| x | An <code>lm</code> object created by <code>stats::lm()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Details

The `glance.summary.lm()` method is a potentially useful alternative to `glance.lm()`. For instance, if users have already converted large `lm` objects into their leaner `summary.lm` equivalents to conserve memory. Note, however, that this method does not return all of the columns of the non-summary method (e.g. AIC and BIC will be missing.)

Value

A `tibble::tibble()` with exactly one row and columns:

<code>adj.r.squared</code>	Adjusted R squared statistic, which is like the R squared statistic except taking degrees of freedom into account.
<code>df.residual</code>	Residual degrees of freedom.
<code>nobs</code>	Number of observations used.
<code>p.value</code>	P-value corresponding to the test statistic.
<code>r.squared</code>	R squared statistic, or the percent of variation explained by the model. Also known as the coefficient of determination.
<code>sigma</code>	Estimated standard error of the residuals.
<code>statistic</code>	Test statistic.
<code>df</code>	The degrees for freedom from the numerator of the overall F-statistic. This is new in broom 0.7.0. Previously, this reported the rank of the design matrix, which is one more than the numerator degrees of freedom of the overall F-statistic.

See Also

[glance\(\)](#), [glance.summary.lm\(\)](#)

Other lm tidiers: [augment.glm\(\)](#), [augment.lm\(\)](#), [glance.glm\(\)](#), [glance.lm\(\)](#), [glance.svyglm\(\)](#), [tidy.glm\(\)](#), [tidy.lm.beta\(\)](#), [tidy.lm\(\)](#), [tidy.mlm\(\)](#), [tidy.summary.lm\(\)](#)

Examples

```
library(ggplot2)
library(dplyr)

mod <- lm(mpg ~ wt + qsec, data = mtcars)

tidy(mod)
glance(mod)

# coefficient plot
d <- tidy(mod, conf.int = TRUE)

ggplot(d, aes(estimate, term, xmin = conf.low, xmax = conf.high, height = 0)) +
  geom_point() +
  geom_vline(xintercept = 0, lty = 4) +
  geom_errorbarh()

# aside: There are tidy() and glance() methods for lm.summary objects too.
# this can be useful when you want to conserve memory by converting large lm
# objects into their leaner summary.lm equivalents.
s <- summary(mod)
tidy(s, conf.int = TRUE)
glance(s)
```

```

augment(mod)
augment(mod, mtcars, interval = "confidence")

# predict on new data
newdata <- mtcars %>%
  head(6) %>%
  mutate(wt = wt + 1)
augment(mod, newdata = newdata)

# ggplot2 example where we also construct 95% prediction interval

# simpler bivariate model since we're plotting in 2D
mod2 <- lm(mpg ~ wt, data = mtcars)

au <- augment(mod2, newdata = newdata, interval = "prediction")

ggplot(au, aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted)) +
  geom_ribbon(aes(ymin = .lower, ymax = .upper), col = NA, alpha = 0.3)

# predict on new data without outcome variable. Output does not include .resid
newdata <- newdata %>%
  select(-mpg)

augment(mod, newdata = newdata)

au <- augment(mod, data = mtcars)

ggplot(au, aes(.hat, .std.resid)) +
  geom_vline(size = 2, colour = "white", xintercept = 0) +
  geom_hline(size = 2, colour = "white", yintercept = 0) +
  geom_point() +
  geom_smooth(se = FALSE)

plot(mod, which = 6)

ggplot(au, aes(.hat, .cooks)) +
  geom_vline(xintercept = 0, colour = NA) +
  geom_abline(slope = seq(0, 3, by = 0.5), colour = "white") +
  geom_smooth(se = FALSE) +
  geom_point()

# column-wise models
a <- matrix(rnorm(20), nrow = 10)
b <- a + rnorm(length(a))
result <- lm(b ~ a)

tidy(result)

```

glance.survdiff	<i>Glance at a(n) survdiff object</i>
-----------------	---------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'survdiff'
glance(x, ...)
```

Arguments

x	An survdiff object returned from <code>survival::survdiff()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

df	Degrees of freedom used by the model.
p.value	P-value corresponding to the test statistic.
statistic	Test statistic.

See Also

`glance()`, `survival::survdiff()`

Other survdiff tidiers: `tidy.survdiff()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# fit model
s <- survdiff(
  Surv(time, status) ~ pat.karno + strata(inst),
  data = lung
)

# summarize model fit with tidiers
tidy(s)
glance(s)
```

`glance.survexp`

Glance at a(n) survexp object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'survexp'
glance(x, ...)
```

Arguments

- `x` An survexp object returned from `survival::survexp()`.
- `...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>n.max</code>	Maximum number of subjects at risk.
<code>n.start</code>	Initial number of subjects at risk.
<code>timepoints</code>	Number of timepoints.

See Also

`glance()`, `survival::survexp()`

Other survexp tidiers: `tidy.survexp()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# fit model
sexpfit <- survexp(
  futime ~ 1,
  rmap = list(
    sex = "male",
    year = accept.dt,
    age = (accept.dt - birth.dt)
  ),
  method = "conditional",
  data = jasa
)
```

```
# summarize model fit with tidiers
tidy(sexpfitt)
glance(sexpfitt)
```

glance.survfit	<i>Glance at a(n) survfit object</i>
----------------	--------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'survfit'
glance(x, ...)
```

Arguments

x	An survfit object returned from <code>survival::survfit()</code> .
...	Additional arguments passed to <code>summary.survfit()</code> . Important arguments include <code>rmean</code> .

Value

A `tibble::tibble()` with exactly one row and columns:

events	Number of events.
n.max	Maximum number of subjects at risk.
n.start	Initial number of subjects at risk.
nobs	Number of observations used.
records	Number of observations
rmean	Restricted mean (see <code>[survival::print.survfit()]</code>).
rmean.std.error	Restricted mean standard error.

conf.low	lower end of confidence interval on median
conf.high	upper end of confidence interval on median
median	median survival

See Also

[glance\(\)](#), [survival::survfit\(\)](#)

Other cch tidiers: [glance.cch\(\)](#), [tidy.cch\(\)](#)

Other survival tidiers: [augment.coxph\(\)](#), [augment.survreg\(\)](#), [glance.aareg\(\)](#), [glance.cch\(\)](#), [glance.coxph\(\)](#), [glance.pyyears\(\)](#), [glance.survdiff\(\)](#), [glance.survexp\(\)](#), [glance.survreg\(\)](#), [tidy.aareg\(\)](#), [tidy.cch\(\)](#), [tidy.coxph\(\)](#), [tidy.pyyears\(\)](#), [tidy.survdiff\(\)](#), [tidy.survexp\(\)](#), [tidy.survfit\(\)](#), [tidy.survreg\(\)](#)

Examples

```
# load libraries for models and data
library(survival)

# fit model
cfits <- coxph(Surv(time, status) ~ age + sex, lung)
sfit <- survfit(cfits)

# summarize model fit with tidiers + visualization
tidy(sfit)
glance(sfit)

library(ggplot2)

ggplot(tidy(sfit), aes(time, estimate)) +
  geom_line() +
  geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)

# multi-state
fitCI <- survfit(Surv(stop, status * as.numeric(event), type = "mstate") ~ 1,
  data = mgus1, subset = (start == 0)
)

td_multi <- tidy(fitCI)

td_multi

ggplot(td_multi, aes(time, estimate, group = state)) +
  geom_line(aes(color = state)) +
  geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)
```

glance.survreg	<i>Glance at a(n) survreg object</i>
----------------	--------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'survreg'
glance(x, ...)
```

Arguments

x	An survreg object returned from <code>survival::survreg()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
df	Degrees of freedom used by the model.
df.residual	Residual degrees of freedom.
iter	Iterations of algorithm/fitting procedure completed.

logLik	The log-likelihood of the model. [stats::logLik()] may be a useful reference.
nobs	Number of observations used.
p.value	P-value corresponding to the test statistic.
statistic	Chi-squared statistic.

See Also

[glance\(\)](#), [survival::survreg\(\)](#)

Other survreg tidiers: [augment.survreg\(\)](#), [tidy.survreg\(\)](#)

Other survival tidiers: [augment.coxph\(\)](#), [augment.survreg\(\)](#), [glance.aareg\(\)](#), [glance.cch\(\)](#), [glance.coxph\(\)](#), [glance.pyears\(\)](#), [glance.survdiff\(\)](#), [glance.survexp\(\)](#), [glance.survfit\(\)](#), [tidy.aareg\(\)](#), [tidy.cch\(\)](#), [tidy.coxph\(\)](#), [tidy.pyears\(\)](#), [tidy.survdiff\(\)](#), [tidy.survexp\(\)](#), [tidy.survfit\(\)](#), [tidy.survreg\(\)](#)

Examples

```
# load libraries for models and data
library(survival)

# fit model
sr <- survreg(
  Surv(futime, fustat) ~ ecog.ps + rx,
  ovarian,
  dist = "exponential"
)

# summarize model fit with tidiers + visualization
tidy(sr)
augment(sr, ovarian)
glance(sr)

# coefficient plot
td <- tidy(sr, conf.int = TRUE)

library(ggplot2)

ggplot(td, aes(estimate, term)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high), height = 0) +
  geom_vline(xintercept = 0)
```

glance.svyglm	<i>Glance at a(n) svyglm object</i>
---------------	-------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'svyglm'
glance(x, maximal = x, ...)
```

Arguments

x	A svyglm object returned from <code>survey::svyglm()</code> .
maximal	A svyglm object corresponding to the maximal model against which to compute the BIC. See Lumley and Scott (2015) for details. Defaults to x, which is equivalent to not using a maximal model.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.

df.null	Degrees of freedom used by the null model.
df.residual	Residual degrees of freedom.
null.deviance	Deviance of the null model.

References

Lumley T, Scott A (2015). AIC and BIC for modelling with complex survey data. *Journal of Survey Statistics and Methodology*, 3(1).

See Also

[survey::svyglm\(\)](#), [stats::glm\(\)](#), [survey::anova.svyglm](#)

Other lm tidiers: [augment.glm\(\)](#), [augment.lm\(\)](#), [glance.glm\(\)](#), [glance.lm\(\)](#), [glance.summary.lm\(\)](#), [tidy.glm\(\)](#), [tidy.lm.beta\(\)](#), [tidy.lm\(\)](#), [tidy.mlm\(\)](#), [tidy.summary.lm\(\)](#)

Examples

```
# load libraries for models and data
library(survey)

set.seed(123)
data(api)

# survey design
dstrat <-
  svydesign(
    id = ~1,
    strata = ~stype,
    weights = ~pw,
    data = apistrat,
    fpc = ~fpc
  )

# model
m <- svyglm(
  formula = sch.wide ~ ell + meals + mobility,
  design = dstrat,
  family = quasibinomial()
)

glance(m)
```

glance.svyolr

Glance at a(n) svyolr object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'svyolr'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>svyolr</code> object returned from <code>survey::svyolr()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>df.residual</code>	Residual degrees of freedom.
<code>edf</code>	The effective degrees of freedom.
<code>nobs</code>	Number of observations used.

See Also

`tidy`, `survey::svyolr()`

Other ordinal tidiers: `augment.clm()`, `augment.polr()`, `glance.clmm()`, `glance.clm()`, `glance.polr()`, `tidy.clmm()`, `tidy.clm()`, `tidy.polr()`, `tidy.svyolr()`

Examples

```
library(broom)
library(survey)

data(api)
dclus1 <- svydesign(id = ~dnum, weights = ~pw, data = apiclus1, fpc = ~fpc)
dclus1 <- update(dclus1, mealcat = cut(meals, c(0, 25, 50, 75, 100)))

m <- svyolr(mealcat ~ avg.ed + mobility + stype, design = dclus1)

m

tidy(m, conf.int = TRUE)
```

glance.varest

Glance at a(n) varest object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modeling function. This includes the name of the modeling function or any arguments passed to the modeling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Glance returns the same number of columns regardless of whether the model matrix is rank-deficient or not. If so, entries in columns that no longer have a well-defined value are filled in with an NA of the appropriate type.

Usage

```
## S3 method for class 'varest'
glance(x, ...)
```

Arguments

<code>x</code>	A varest object produced by a call to <code>vars::VAR()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>lag.order</code>	Lag order.
<code>logLik</code>	The log-likelihood of the model. [<code>stats::logLik()</code>] may be a useful reference.
<code>n</code>	The total number of observations.
<code>nobs</code>	Number of observations used.

See Also

`glance()`, `vars::VAR()`

Examples

```
# load libraries for models and data
library(vars)

# load data
data("Canada", package = "vars")

# fit models
mod <- VAR(Canada, p = 1, type = "both")

# summarize model fit with tidiers
tidy(mod)
glance(mod)
```

glance_optim

*Tidy a(n) optim object masquerading as list***Description**

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `interp::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, they throw an error.

Usage

```
glance_optim(x, ...)
```

Arguments

<code>x</code>	A list returned from <code>stats::optim()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with exactly one row and columns:

<code>convergence</code>	Convergence code.
<code>function.count</code>	Number of calls to 'fn'.
<code>gradient.count</code>	Number of calls to 'gr'.
<code>value</code>	Minimized or maximized output value.

See Also

`glance()`, `stats::optim()`

Other list tidiers: `list_tidiers`, `tidy_irlba()`, `tidy_optim()`, `tidy_svd()`, `tidy_xyz()`

Examples

```
f <- function(x) (x[1] - 2)^2 + (x[2] - 3)^2 + (x[3] - 8)^2
o <- optim(c(1, 1, 1), f)
```

leveneTest_tidiers *Tidy/glance a(n) leveneTest object*

Description

For models that have only a single component, the `tidy()` and `glance()` methods are identical. Please see the documentation for both of those methods.

Usage

```
## S3 method for class 'leveneTest'
tidy(x, ...)
```

Arguments

<code>x</code>	An object of class <code>anova</code> created by a call to <code>car::leveneTest()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>df</code>	Degrees of freedom used by this term in the model.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>df.residual</code>	Residual degrees of freedom.

See Also

`tidy()`, `glance()`, `car::leveneTest()`

Other car tidiers: `durbinWatsonTest_tidiers`

Examples

```
# load libraries for models and data
library(car)

data(Moore)

lt <- with(Moore, leveneTest(conformity, fcategory))

tidy(lt)
glance(lt)
```

list_tidiers

Tidying methods for lists / returned values that are not S3 objects

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `base::svd()` and `interp::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

Usage

```
## S3 method for class 'list'
tidy(x, ...)

## S3 method for class 'list'
glance(x, ...)
```

Arguments

`x` A list, potentially representing an object that can be tidied.
`...` Additionally, arguments passed to the tidying function.

Details

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are themselves implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, throws an error.

See Also

Other list tidiers: `glance_optim()`, `tidy_irlba()`, `tidy_optim()`, `tidy_svd()`, `tidy_xyz()`

 null_tidiers

Tidiers for NULL inputs

Description

tidy(NULL), glance(NULL) and augment(NULL) all return an empty [tibble::tibble](#). This empty tibble can be treated a tibble with zero rows, making it convenient to combine with other tibbles using functions like [purrr::map_df\(\)](#) on lists of potentially NULL objects.

Usage

```
## S3 method for class ``NULL``
tidy(x, ...)

## S3 method for class ``NULL``
glance(x, ...)

## S3 method for class ``NULL``
augment(x, ...)
```

Arguments

x The value NULL.
 ... Additional arguments (not used).

Value

An empty [tibble::tibble](#).

See Also

[tibble::tibble](#)

 sparse_tidiers

Tidy a sparseMatrix object from the Matrix package

Description

Tidy a sparseMatrix object from the Matrix package into a three-column data frame, row, column, and value (with zeros missing). If there are row names or column names, use those, otherwise use indices

Usage

```
## S3 method for class 'dgTMatrix'
tidy(x, ...)

## S3 method for class 'dgCMatrix'
tidy(x, ...)

## S3 method for class 'sparseMatrix'
tidy(x, ...)
```

Arguments

x	A Matrix object
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

row	Row ID of the original observation.
value	The value/estimate of the component. Results from data reshaping.
column	Column name in the original matrix.

sp_tidiers

Tidy a(n) SpatialPolygonsDataFrame object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Note that the `sf` package now defines tidy spatial objects and is the recommended approach to spatial data. `sp_tidiers` are likely to be deprecated in the near future in favor of `sf::st_as_sf()`. Development of `sp_tidiers` has halted in broom.

Usage

```
## S3 method for class 'SpatialPolygonsDataFrame'
tidy(x, region = NULL, ...)

## S3 method for class 'SpatialPolygons'
tidy(x, ...)

## S3 method for class 'Polygons'
tidy(x, ...)

## S3 method for class 'Polygon'
tidy(x, ...)

## S3 method for class 'SpatialLinesDataFrame'
tidy(x, ...)

## S3 method for class 'Lines'
tidy(x, ...)

## S3 method for class 'Line'
tidy(x, ...)
```

Arguments

x	A SpatialPolygonsDataFrame, SpatialPolygons, Polygons, Polygon, SpatialLinesDataFrame, Lines or Line object.
region	name of variable used to split up regions
...	not used by this method

summary_tidiers *(Deprecated) Tidy summaryDefault objects*

Description

Tidiers for summaryDefault objects have been deprecated as of broom 0.7.0 in favor of `skimr::skim()`.

Usage

```
## S3 method for class 'summaryDefault'
tidy(x, ...)

## S3 method for class 'summaryDefault'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>summaryDefault</code> object, created by calling <code>summary()</code> on a vector.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A one-row `tibble::tibble` with columns:

<code>minimum</code>	Minimum value in original vector.
<code>q1</code>	First quartile of original vector.
<code>median</code>	Median of original vector.
<code>mean</code>	Mean of original vector.
<code>q3</code>	Third quartile of original vector.
<code>maximum</code>	Maximum value in original vector.
<code>na</code>	Number of NA values in original vector. Column present only when original vector had at least one NA entry.

See Also

Other deprecated: `bootstrap()`, `confint_tidy()`, `data.frame_tidiere`, `finish_glance()`, `fix_data_frame()`, `tidy.density()`, `tidy.dist()`, `tidy.ftable()`, `tidy.numeric()`

Other deprecated: `bootstrap()`, `confint_tidy()`, `data.frame_tidiere`, `finish_glance()`, `fix_data_frame()`, `tidy.density()`, `tidy.dist()`, `tidy.ftable()`, `tidy.numeric()`

Examples

```
v <- rnorm(1000)
s <- summary(v)
s

tidy(s)
glance(s)

v2 <- c(v, NA)
tidy(summary(v2))
```

tidy.aareg	<i>Tidy a(n) aareg object</i>
------------	-------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'aareg'
tidy(x, ...)
```

Arguments

x	An aareg object returned from <code>survival::aareg()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

`robust.se` is only present when `x` was created with `dfbeta = TRUE`.

Value

A `tibble::tibble()` with columns:

<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>robust.se</code>	robust version of standard error estimate.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>z</code>	z score.

See Also

`tidy()`, `survival::aareg()`

Other aareg tidiers: `glance.aareg()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# fit model
afit <- aareg(
  Surv(time, status) ~ age + sex + ph.ecog,
  data = lung,
  dfbeta = TRUE
)

# summarize model fit with tidiers
tidy(afit)
```

tidy.acf

Tidy a(n) acf object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'acf'
tidy(x, ...)
```

Arguments

x An acf object created by `stats::acf()`, `stats::pacf()` or `stats::ccf()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>acf</code>	Autocorrelation.
<code>lag</code>	Lag values.

See Also

`tidy()`, `stats::acf()`, `stats::pacf()`, `stats::ccf()`

Other time series tidiers: `tidy.spec()`, `tidy.ts()`, `tidy.zoo()`

Examples

```
tidy(acf(lh, plot = FALSE))
tidy(ccf(mdeaths, fdeaths, plot = FALSE))
tidy(pacf(lh, plot = FALSE))
```

`tidy.anova`

Tidy a(n) anova object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'anova'
tidy(x, ...)
```


Arguments

- `x` An anova object, such as those created by `stats::anova()`, `car::Anova()`, `car::leveneTest()`, or `car::linearHypothesis()`.
- `...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

The term column of an ANOVA table can come with leading or trailing whitespace, which this tidying method trims.

For documentation on the tidier for `car::leveneTest()` output, see `tidy.leveneTest()`

Value

A `tibble::tibble()` with columns:

<code>df</code>	Degrees of freedom used by this term in the model.
<code>meansq</code>	Mean sum of squares. Equal to total sum of squares divided by degrees of freedom.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>sumsq</code>	Sum of squares explained by this term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `stats::anova()`, `car::Anova()`, `car::leveneTest()`

Other anova tidiers: `glance.anova()`, `glance.aov()`, `tidy.TukeyHSD()`, `tidy.aovlist()`, `tidy.aov()`, `tidy.manova()`

Examples

```
# fit models
a <- lm(mpg ~ wt + qsec + disp, mtcars)
b <- lm(mpg ~ wt + qsec, mtcars)

mod <- anova(a, b)
```

```
# summarize model fit with tidiers
tidy(mod)
glance(mod)

# car::linearHypothesis() example
library(car)
mod_lht <- linearHypothesis(a, "wt - disp")
tidy(mod_lht)
glance(mod_lht)
```

tidy.aov

Tidy a(n) aov object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'aov'
tidy(x, ...)
```

Arguments

x	An aov object, such as those created by <code>stats::aov()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The term column of an ANOVA table can come with leading or trailing whitespace, which this tidying method trims.

For documentation on the tidier for `car::leveneTest()` output, see `tidy.leveneTest()`

See Also

[tidy\(\)](#), [stats::aov\(\)](#)

Other anova tidiers: [glance.anova\(\)](#), [glance.aov\(\)](#), [tidy.TukeyHSD\(\)](#), [tidy.anova\(\)](#), [tidy.aovlist\(\)](#), [tidy.manova\(\)](#)

Examples

```
a <- aov(mpg ~ wt + qsec + disp, mtcars)
tidy(a)
```

tidy.aovlist	<i>Tidy a(n) aovlist object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'aovlist'
tidy(x, ...)
```

Arguments

`x` An aovlist objects, such as those created by [stats::aov\(\)](#).

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

The term column of an ANOVA table can come with leading or trailing whitespace, which this tidying method trims.

For documentation on the tidier for [car::leveneTest\(\)](#) output, see [tidy.leveneTest\(\)](#)

Value

A `tibble::tibble()` with columns:

<code>df</code>	Degrees of freedom used by this term in the model.
<code>meansq</code>	Mean sum of squares. Equal to total sum of squares divided by degrees of freedom.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>stratum</code>	The error stratum.
<code>sumsq</code>	Sum of squares explained by this term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `stats::aov()`

Other anova tidiers: `glance.anova()`, `glance.aov()`, `tidy.TukeyHSD()`, `tidy.anova()`, `tidy.aov()`, `tidy.manova()`

Examples

```
a <- aov(mpg ~ wt + qsec + Error(displ / am), mtcars)
tidy(a)
```

`tidy.Arima`

Tidy a(n) Arima object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'Arima'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	An object of class <code>Arima</code> created by <code>stats::arima()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`stats::arima()`

Other Arima tidiers: `glance.Arima()`

Examples

```
# fit model
fit <- arima(1h, order = c(1, 0, 0))

# summarize model fit with tidiers
tidy(fit)
glance(fit)
```

tidy.betamfx

*Tidy a(n) betamfx object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'betamfx'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A betamfx object.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if conf.int = TRUE. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass conf.level = 0.9, all computation will proceed using conf.level = 0.95. Two exceptions here are: <ul style="list-style-type: none"> • tidy() methods will warn when supplied an exponentiate argument if it will be ignored. • augment() methods will warn when supplied a newdata argument if it will be ignored.

Details

The mfx package provides methods for calculating marginal effects for various generalized linear models (GLMs). Unlike standard linear models, estimated model coefficients in a GLM cannot be directly interpreted as marginal effects (i.e., the change in the response variable predicted after a one unit change in one of the regressors). This is because the estimated coefficients are multiplicative, dependent on both the link function that was used for the estimation and any other variables that were included in the model. When calculating marginal effects, users must typically choose whether they want to use i) the average observation in the data, or ii) the average of the sample marginal effects. See vignette("mfxarticle") from the mfx package for more details.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>atmean</code>	TRUE if the marginal effects were originally calculated as the partial effects for the average observation. If FALSE, then these were instead calculated as average partial effects.

See Also

`tidy.betareg()`, `mfx::betamfx()`

Other mfx tidiers: `augment.betamfx()`, `augment.mfx()`, `glance.betamfx()`, `glance.mfx()`, `tidy.mfx()`

Examples

```
library(mfx)

# Simulate some data
set.seed(12345)
n = 1000
x = rnorm(n)

# Beta outcome
y = rbeta(n, shape1 = plogis(1 + 0.5 * x), shape2 = (abs(0.2*x)))
# Use Smithson and Verkuilen correction
y = (y*(n-1)+0.5)/n

d = data.frame(y,x)
mod_betamfx = betamfx(y ~ x | x, data = d)

tidy(mod_betamfx, conf.int = TRUE)

# Compare with the naive model coefficients of the equivalent betareg call (not run)
# tidy(betamfx(y ~ x | x, data = d), conf.int = TRUE)

augment(mod_betamfx)
glance(mod_betamfx)
```

tidy.betareg	<i>Tidy a(n) betareg object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'betareg'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A betareg object produced by a call to <code>betareg::betareg()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The tibble has one row for each term in the regression. The component column indicates whether a particular term was used to model either the "mean" or "precision". Here the precision is the inverse of the variance, often referred to as ϕ . At least one term will have been used to model the precision ϕ .

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.

estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.
component	Whether a particular term was used to model the mean or the precision in the regression. See details.

See Also

[tidy\(\)](#), [betareg::betareg\(\)](#)

Examples

```
# load libraries for models and data
library(betareg)

# load data
data("GasolineYield", package = "betareg")

# fit model
mod <- betareg(yield ~ batch + temp, data = GasolineYield)

mod

# summarize model fit with tidiers
tidy(mod)
tidy(mod, conf.int = TRUE)
tidy(mod, conf.int = TRUE, conf.level = .99)

augment(mod)

glance(mod)
```

tidy.biglm

Tidy a(n) biglm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'biglm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A biglm object created by a call to <code>biglm::biglm()</code> or <code>biglm::bigglm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

`tidy()`, `biglm::biglm()`, `biglm::bigglm()`

Other biglm tidiers: `glance.biglm()`

Examples

```

# load modeling library
library(bigm)

# fit model -- linear regression
bfit <- biglm(mpg ~ wt + disp, mtcars)

# summarize model fit with tidiers
tidy(bfit)
tidy(bfit, conf.int = TRUE)
tidy(bfit, conf.int = TRUE, conf.level = .9)

glance(bfit)

# fit model -- logistic regression
bgfit <- bigglm(am ~ mpg, mtcars, family = binomial())

# summarize model fit with tidiers
tidy(bgfit)
tidy(bgfit, exponentiate = TRUE)
tidy(bgfit, conf.int = TRUE)
tidy(bgfit, conf.int = TRUE, conf.level = .9)
tidy(bgfit, conf.int = TRUE, conf.level = .9, exponentiate = TRUE)

glance(bgfit)

```

tidy.binDesign	<i>Tidy a(n) binDesign object</i>
----------------	-----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'binDesign'
tidy(x, ...)

```

Arguments

x A `binGroup::binDesign()` object.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>n</code>	Number of trials in given iteration.
<code>power</code>	Power achieved for given value of <code>n</code> .

See Also

`tidy()`, `binGroup::binDesign()`

Other binGroup tidiers: `glance.binDesign()`, `tidy.binWidth()`

Examples

```
if (requireNamespace("binGroup", quietly = TRUE)) {

  library(binGroup)
  des <- binDesign(
    nmax = 300, delta = 0.06,
    p.hyp = 0.1, power = .8
  )

  glance(des)
  tidy(des)

  # the ggplot2 equivalent of plot(des)
  library(ggplot2)
  ggplot(tidy(des), aes(n, power)) +
    geom_line()

}
```

tidy.binWidth	<i>Tidy a(n) binWidth object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'binWidth'
tidy(x, ...)
```

Arguments

x	A <code>binGroup::binWidth()</code> object.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

alternative	Alternative hypothesis (character).
ci.width	Expected width of confidence interval.
p	True proportion.
n	Total sample size

See Also

`tidy()`, `binGroup::binWidth()`

Other bingroup tidiers: `glance.binDesign()`, `tidy.binDesign()`

Examples

```
# load libraries
library(binGroup)

# fit model
bw <- binWidth(100, .1)

bw

# summarize model fit with tidiers
tidy(bw)
```

tidy.boot

Tidy a(n) boot object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'boot'
tidy(
  x,
  conf.int = FALSE,
  conf.level = 0.95,
  conf.method = c("perc", "bca", "basic", "norm"),
  exponentiate = FALSE,
  ...
)
```

Arguments

x	A <code>boot::boot()</code> object.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

<code>conf.method</code>	Passed to the type argument of <code>boot::boot.ci()</code> . Defaults to "perc". The allowed types are "perc", "basic", "bca", and "norm". Does not support "stud" or "all".
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

If weights were provided to the `boot` function, an estimate column is included showing the weighted bootstrap estimate, and the standard error is of that estimate.

If there are no original statistics in the "boot" object, such as with a call to `tsboot` with `orig.t = FALSE`, the original and statistic columns are omitted, and only estimate and `std.error` columns shown.

Value

A `tibble::tibble()` with columns:

<code>bias</code>	Bias of the statistic.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>statistic</code>	Original value of the statistic.

See Also

[tidy\(\)](#), [boot::boot\(\)](#), [boot::tsboot\(\)](#), [boot::boot.ci\(\)](#), [rsample::bootstraps\(\)](#)

Examples

```
# load modeling library
library(boot)

clotting <- data.frame(
  u = c(5, 10, 15, 20, 30, 40, 60, 80, 100),
  lot1 = c(118, 58, 42, 35, 27, 25, 21, 19, 18),
  lot2 = c(69, 35, 26, 21, 18, 16, 13, 12, 12)
```

```

)

# fit models
g1 <- glm(lot2 ~ log(u), data = clotting, family = Gamma)

bootfun <- function(d, i) {
  coef(update(g1, data = d[i, ]))
}

bootres <- boot(clotting, bootfun, R = 999)

# summarize model fits with tidiers
tidy(g1, conf.int = TRUE)
tidy(bootres, conf.int = TRUE)

```

tidy.btergm

Tidy a(n) btergm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

This method tidies the coefficients of a bootstrapped temporal exponential random graph model estimated with the **xergm**. It simply returns the coefficients and their confidence intervals.

Usage

```

## S3 method for class 'btergm'
tidy(x, conf.level = 0.95, exponentiate = FALSE, ...)

```

Arguments

x	A <code>btergm:btergm()</code> object.
conf.level	Confidence level for confidence intervals. Defaults to 0.95.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `btergm::btergm()`

Examples

```
library(btergm)
library(network)

set.seed(5)

# create 10 random networks with 10 actors
networks <- list()
for (i in 1:10) {
  mat <- matrix(rbinom(100, 1, .25), nrow = 10, ncol = 10)
  diag(mat) <- 0
  nw <- network(mat)
  networks[[i]] <- nw
}

# create 10 matrices as covariates
covariates <- list()
for (i in 1:10) {
  mat <- matrix(rnorm(100), nrow = 10, ncol = 10)
  covariates[[i]] <- mat
}

# fit the model
mod <- btergm(networks ~ edges + istar(2) + edgescov(covariates), R = 100)

# summarize model fit with tidiers
tidy(mod)
```

tidy.cch

*Tidy a(n) cch object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'cch'
tidy(x, conf.level = 0.95, ...)
```

Arguments

x	An cch object returned from <code>survival::cch()</code> .
conf.level	confidence level for CI
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[tidy\(\)](#), [survival::cch\(\)](#)

Other cch tidiers: [glance.cch\(\)](#), [glance.survfit\(\)](#)

Other survival tidiers: [augment.coxph\(\)](#), [augment.survreg\(\)](#), [glance.aareg\(\)](#), [glance.cch\(\)](#), [glance.coxph\(\)](#), [glance.pyears\(\)](#), [glance.survdiff\(\)](#), [glance.survexp\(\)](#), [glance.survfit\(\)](#), [glance.survreg\(\)](#), [tidy.aareg\(\)](#), [tidy.coxph\(\)](#), [tidy.pyears\(\)](#), [tidy.survdiff\(\)](#), [tidy.survexp\(\)](#), [tidy.survfit\(\)](#), [tidy.survreg\(\)](#)

Examples

```
# load libraries for models and data
library(survival)

# examples come from cch documentation
subcoh <- nwtco$in.subcohort
selccoh <- with(nwtco, rel == 1 | subcoh == 1)
ccoh.data <- nwtco[selccoh, ]
ccoh.data$subcohort <- subcoh[selccoh]

# central-lab histology
ccoh.data$histol <- factor(ccoh.data$histol, labels = c("FH", "UH"))

# tumour stage
ccoh.data$stage <- factor(ccoh.data$stage, labels = c("I", "II", "III", "IV"))
ccoh.data$age <- ccoh.data$age / 12 # age in years

# fit model
fit.ccP <- cch(Surv(edrel, rel) ~ stage + histol + age,
  data = ccoh.data,
  subcoh = ~subcohort, id = ~seqno, cohort.size = 4028
)

# summarize model fit with tidiers + visualization
tidy(fit.ccP)

# coefficient plot
library(ggplot2)

ggplot(tidy(fit.ccP), aes(x = estimate, y = term)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high), height = 0) +
  geom_vline(xintercept = 0)
```

tidy.cld

*Tidy a(n) cld object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'cld'
tidy(x, ...)
```

Arguments

x	A cld object created by calling <code>multcomp::cld()</code> on a <code>glht</code> , <code>confint.glht()</code> or <code>summary.glht()</code> object.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

contrast	Levels being compared.
letters	Compact letter display denoting all pair-wise comparisons.

See Also

`tidy()`, `multcomp::cld()`, `multcomp::summary.glht()`, `multcomp::confint.glht()`, `multcomp::glht()`

Other multcomp tidiers: `tidy.confint.glht()`, `tidy.glht()`, `tidy.summary.glht()`

Examples

```

# load libraries for models and data
library(multcomp)
library(ggplot2)

amod <- aov(breaks ~ wool + tension, data = warpbreaks)
wht <- glht(amod, linfct = mcp(tension = "Tukey"))

tidy(wht)

ggplot(wht, aes(lhs, estimate)) +
  geom_point()

CI <- confint(wht)

tidy(CI)

ggplot(CI, aes(lhs, estimate, ymin = lwr, ymax = upr)) +
  geom_pointrange()

tidy(summary(wht))
ggplot(mapping = aes(lhs, estimate)) +
  geom_linerange(aes(ymin = lwr, ymax = upr), data = CI) +
  geom_point(aes(size = p), data = summary(wht)) +
  scale_size(trans = "reverse")

cld <- cld(wht)
tidy(cld)

```

tidy.clm

Tidy a(n) clm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'clm'
tidy(
  x,
  conf.int = FALSE,
  conf.level = 0.95,

```

```

  conf.type = c("profile", "Wald"),
  exponentiate = FALSE,
  ...
)

```

Arguments

<code>x</code>	A <code>clm</code> object returned from <code>ordinal::clm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>conf.type</code>	Whether to use "profile" or "Wald" confidence intervals, passed to the <code>type</code> argument of <code>ordinal::confint.clm()</code> . Defaults to "profile".
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

In broom 0.7.0 the `coefficient_type` column was renamed to `coef.type`, and the contents were changed as well.

Note that `intercept` type coefficients correspond to alpha parameters, `location` type coefficients correspond to beta parameters, and `scale` type coefficients correspond to zeta parameters.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy`, `ordinal::clm()`, `ordinal::confint.clm()`

Other ordinal tidiers: `augment.clm()`, `augment.polr()`, `glance.clmm()`, `glance.clm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clmm()`, `tidy.polr()`, `tidy.svyolr()`

Examples

```
# load libraries for models and data
library(ordinal)

# fit model
fit <- clm(rating ~ temp * contact, data = wine)

# summarize model fit with tidiers
tidy(fit)
tidy(fit, conf.int = TRUE, conf.level = 0.9)
tidy(fit, conf.int = TRUE, conf.type = "Wald", exponentiate = TRUE)

glance(fit)
augment(fit, type.predict = "prob")
augment(fit, type.predict = "class")

# ...and again with another model specification
fit2 <- clm(rating ~ temp, nominal = ~contact, data = wine)

tidy(fit2)
glance(fit2)
```

tidy.clmm

Tidy a(n) clmm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'clmm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

<code>x</code>	A <code>clmm</code> object returned from <code>ordinal::clmm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

Note

In broom 0.7.0 the `coefficient_type` column was renamed to `coef.type`, and the contents were changed as well.

Note that `intercept` type coefficients correspond to alpha parameters, `location` type coefficients correspond to beta parameters, and `scale` type coefficients correspond to zeta parameters.

See Also

`tidy`, `ordinal::clmm()`, `ordinal::confint.clm()`

Other ordinal tidiers: `augment.clm()`, `augment.polr()`, `glance.clm()`, `glance.clm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clm()`, `tidy.polr()`, `tidy.svyolr()`

Examples

```
# load libraries for models and data
library(ordinal)

# fit model
fit <- clmm(rating ~ temp + contact + (1 | judge), data = wine)

# summarize model fit with tidiers
tidy(fit)
tidy(fit, conf.int = TRUE, conf.level = 0.9)
tidy(fit, conf.int = TRUE, exponentiate = TRUE)

glance(fit)

# ...and again with another model specification
fit2 <- clmm(rating ~ temp + (1 | judge), nominal = ~contact, data = wine)

tidy(fit2)
glance(fit2)
```

tidy.coefstest

*Tidy a(n) coefstest object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'coefstest'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A coefstest object returned from <code>lmtest::coefstest()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

- ...
- Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `lmtest::coefstest()`

Examples

```
# load libraries for models and data
library(lmtest)

m <- lm(dist ~ speed, data = cars)

coefstest(m)
tidy(coefstest(m))
tidy(coefstest(m, conf.int = TRUE))

# a very common workflow is to combine lmtest::coefstest with alternate
# variance-covariance matrices via the sandwich package. The lmtest
# tidiers support this workflow too, enabling you to adjust the standard
# errors of your tidied models on the fly.
library(sandwich)

# "HC3" (default) robust SEs
tidy(coefstest(m, vcov = vcovHC))
```

```
# "HC2" robust SEs
tidy(coeftest(m, vcov = vcovHC, type = "HC2"))

# N-W HAC robust SEs
tidy(coeftest(m, vcov = NeweyWest))

# the columns of the returned tibble for glance.coeftest() will vary
# depending on whether the coeftest object retains the underlying model.
# Users can control this with the "save = TRUE" argument of coeftest().
glance(coeftest(m))
glance(coeftest(m, save = TRUE))
```

tidy.confint.glm *Tidy a(n) confint.glm object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'confint.glm'
tidy(x, ...)
```

Arguments

`x` A `confint.glm` object created by calling `multcomp::confint.glm()` on a `glm` object created with `multcomp::glm()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.

contrast	Levels being compared.
estimate	The estimated value of the regression term.

See Also

`tidy()`, `multcomp::confint.glht()`, `multcomp::glht()`

Other multcomp tidiers: `tidy.cld()`, `tidy.glht()`, `tidy.summary.glht()`

Examples

```
# load libraries for models and data
library(multcomp)
library(ggplot2)

amod <- aov(breaks ~ wool + tension, data = warpbreaks)
wht <- glht(amod, linfct = mcp(tension = "Tukey"))

tidy(wht)

ggplot(wht, aes(lhs, estimate)) +
  geom_point()

CI <- confint(wht)

tidy(CI)

ggplot(CI, aes(lhs, estimate, ymin = lwr, ymax = upr)) +
  geom_pointrange()

tidy(summary(wht))
ggplot(mapping = aes(lhs, estimate)) +
  geom_linerange(aes(ymin = lwr, ymax = upr), data = CI) +
  geom_point(aes(size = p), data = summary(wht)) +
  scale_size(trans = "reverse")

cld <- cld(wht)
tidy(cld)
```

`tidy.confusionMatrix` *Tidy a(n) confusionMatrix object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'confusionMatrix'
tidy(x, by_class = TRUE, ...)
```

Arguments

x	An object of class <code>confusionMatrix</code> created by a call to <code>caret::confusionMatrix()</code> .
by_class	Logical indicating whether or not to show performance measures broken down by class. Defaults to <code>TRUE</code> . When <code>by_class = FALSE</code> only returns a tibble with accuracy, kappa, and McNemar statistics.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

class	The class under consideration.
conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
term	The name of the regression term.
p.value	P-value for accuracy and kappa statistics.

See Also

`tidy()`, `caret::confusionMatrix()`

Examples

```
# load libraries for models and data
library(caret)

set.seed(27)

# generate data
two_class_sample1 <- as.factor(sample(letters[1:2], 100, TRUE))
two_class_sample2 <- as.factor(sample(letters[1:2], 100, TRUE))
```

```

two_class_cm <- confusionMatrix(
  two_class_sample1,
  two_class_sample2
)

# summarize model fit with tidiers
tidy(two_class_cm)
tidy(two_class_cm, by_class = FALSE)

# multiclass example
six_class_sample1 <- as.factor(sample(letters[1:6], 100, TRUE))
six_class_sample2 <- as.factor(sample(letters[1:6], 100, TRUE))

six_class_cm <- confusionMatrix(
  six_class_sample1,
  six_class_sample2
)

# summarize model fit with tidiers
tidy(six_class_cm)
tidy(six_class_cm, by_class = FALSE)

```

tidy.coxph

Tidy a(n) coxph object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'coxph'
tidy(x, exponentiate = FALSE, conf.int = FALSE, conf.level = 0.95, ...)

```

Arguments

x	A coxph object returned from <code>survival::coxph()</code> .
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.

<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.

See Also

[tidy\(\)](#), [survival::coxph\(\)](#)

Other coxph tidiers: [augment.coxph\(\)](#), [glance.coxph\(\)](#)

Other survival tidiers: [augment.coxph\(\)](#), [augment.survreg\(\)](#), [glance.aareg\(\)](#), [glance.cch\(\)](#), [glance.coxph\(\)](#), [glance.pyears\(\)](#), [glance.survdifff\(\)](#), [glance.survexp\(\)](#), [glance.survfit\(\)](#), [glance.survreg\(\)](#), [tidy.aareg\(\)](#), [tidy.cch\(\)](#), [tidy.pyears\(\)](#), [tidy.survdifff\(\)](#), [tidy.survexp\(\)](#), [tidy.survfit\(\)](#), [tidy.survreg\(\)](#)

Examples

```
# load libraries for models and data
library(survival)

# fit model
cfit <- coxph(Surv(time, status) ~ age + sex, lung)

# summarize model fit with tidiers
tidy(cfit)
tidy(cfit, exponentiate = TRUE)

lp <- augment(cfit, lung)
risks <- augment(cfit, lung, type.predict = "risk")
```

```

expected <- augment(cfit, lung, type.predict = "expected")

glance(cfit)

# also works on clogit models
resp <- levels(logan$occupation)
n <- nrow(logan)
indx <- rep(1:n, length(resp))
logan2 <- data.frame(
  logan[indx, ],
  id = indx,
  tocc = factor(rep(resp, each = n))
)

logan2$case <- (logan2$occupation == logan2$tocc)

cl <- clogit(case ~ tocc + tocc:education + strata(id), logan2)

tidy(cl)
glance(cl)

library(ggplot2)

ggplot(lp, aes(age, .fitted, color = sex)) +
  geom_point()

ggplot(risks, aes(age, .fitted, color = sex)) +
  geom_point()

ggplot(expected, aes(time, .fitted, color = sex)) +
  geom_point()

```

tidy.crr

Tidy a(n) cmprsk object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'crr'
tidy(x, exponentiate = FALSE, conf.int = FALSE, conf.level = 0.95, ...)

```


Arguments

<code>x</code>	A <code>crr</code> object returned from <code>cmprsk::crr()</code> .
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.

See Also

`tidy()`, `cmprsk::crr()`

Other `cmprsk` tidiers: `glance.crr()`

Examples

```
library(cmprsk)

# time to loco-regional failure (lrf)
lrf_time <- rexp(100)
lrf_event <- sample(0:2, 100, replace = TRUE)
```

```

trt <- sample(0:1, 100, replace = TRUE)
strt <- sample(1:2, 100, replace = TRUE)

# fit model
x <- crr(lrf_time, lrf_event, cbind(trt, strt))

# summarize model fit with tidiers
tidy(x, conf.int = TRUE)
glance(x)

```

tidy.cv.glmnet

Tidy a(n) cv.glmnet object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'cv.glmnet'
tidy(x, ...)

```

Arguments

x	A cv.glmnet object returned from <code>glmnet::cv.glmnet()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

lambda	Value of penalty parameter lambda.
nzero	Number of non-zero coefficients for the given lambda.
std.error	The standard error of the regression term.
conf.low	lower bound on confidence interval for cross-validation estimated loss.
conf.high	upper bound on confidence interval for cross-validation estimated loss.
estimate	Median loss across all cross-validation folds for a given lambda

See Also`tidy(), glmnet::cv.glmnet()`Other glmnet tidiers: `glance.cv.glmnet(), glance.glmnet(), tidy.glmnet()`**Examples**

```
# load libraries for models and data
library(glmnet)

set.seed(27)

nobs <- 100
nvar <- 50
real <- 5

x <- matrix(rnorm(nobs * nvar), nobs, nvar)
beta <- c(rnorm(real, 0, 1), rep(0, nvar - real))
y <- c(t(beta) %*% t(x)) + rnorm(nvar, sd = 3)

cvfit1 <- cv.glmnet(x, y)

tidy(cvfit1)
glance(cvfit1)

library(ggplot2)

tidied_cv <- tidy(cvfit1)
glance_cv <- glance(cvfit1)

# plot of MSE as a function of lambda
g <- ggplot(tidied_cv, aes(lambda, estimate)) +
  geom_line() +
  scale_x_log10()
g

# plot of MSE as a function of lambda with confidence ribbon
g <- g + geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)
g

# plot of MSE as a function of lambda with confidence ribbon and choices
# of minimum lambda marked
g <- g +
  geom_vline(xintercept = glance_cv$lambda.min) +
  geom_vline(xintercept = glance_cv$lambda.1se, lty = 2)
g

# plot of number of zeros for each choice of lambda
ggplot(tidied_cv, aes(lambda, nzero)) +
  geom_line() +
  scale_x_log10()
```

```
# coefficient plot with min lambda shown
tidied <- tidy(cvfit1$glmnet.fit)

ggplot(tidied, aes(lambda, estimate, group = term)) +
  scale_x_log10() +
  geom_line() +
  geom_vline(xintercept = glance_cv$lambda.min) +
  geom_vline(xintercept = glance_cv$lambda.1se, lty = 2)
```

tidy.density *(Deprecated) Tidy density objects*

Description

(Deprecated) Tidy density objects

Usage

```
## S3 method for class 'density'
tidy(x, ...)
```

Arguments

x A density object returned from `stats::density()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble` with two columns: points `x` where the density is estimated, and estimated density `y`.

See Also

Other deprecated: `bootstrap()`, `confint_tidy()`, `data.frame_tidiers`, `finish_glance()`, `fix_data_frame()`, `summary_tidiers`, `tidy.dist()`, `tidy.ftable()`, `tidy.numeric()`

tidy.dist	<i>(Deprecated) Tidy dist objects</i>
-----------	---------------------------------------

Description

(Deprecated) Tidy dist objects

Usage

```
## S3 method for class 'dist'
tidy(x, diagonal = attr(x, "Diag"), upper = attr(x, "Upper"), ...)
```

Arguments

x	A dist object returned from <code>stats::dist()</code> .
diagonal	Logical indicating whether or not to tidy the diagonal elements of the distance matrix. Defaults to whatever was based to the <code>diag</code> argument of <code>stats::dist()</code> .
upper	Logical indicating whether or not to tidy the upper half of the distance matrix. Defaults to whatever was based to the <code>upper</code> argument of <code>stats::dist()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

If the distance matrix does not include an upper triangle and/or diagonal, the tidied version will not either.

Value

A `tibble::tibble` with one row for each pair of items in the distance matrix, with columns:

item1	First item
item2	Second item
distance	Distance between items

See Also

Other deprecated: `bootstrap()`, `confint_tidy()`, `data.frame_tidiers`, `finish_glance()`, `fix_data_frame()`, `summary_tidiers`, `tidy.density()`, `tidy.ftable()`, `tidy.numeric()`

Examples

```
cars_dist <- dist(t(mtcars[, 1:4]))
cars_dist

tidy(cars_dist)
tidy(cars_dist, upper = TRUE)
tidy(cars_dist, diagonal = TRUE)
```

tidy.drc

Tidy a(n) drc object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'drc'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A drc object produced by a call to <code>drc::drm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The tibble has one row for each curve and term in the regression. The `curveid` column indicates the curve.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>curve</code>	Index identifying the curve.

See Also

`tidy()`, `drc::drm()`

Other drc tidiers: `augment.drc()`, `glance.drc()`

Examples

```
# load libraries for models and data
library(drc)

# fit model
mod <- drm(dead / total ~ conc, type,
  weights = total, data = selenium, fct = LL.2(), type = "binomial"
)

# summarize model fit with tidiers
tidy(mod)
tidy(mod, conf.int = TRUE)

glance(mod)

augment(mod, selenium)
```

tidy.emmGrid

Tidy a(n) emmGrid object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'emmGrid'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	An emmGrid object.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if conf.int = TRUE. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments passed to <code>emmeans::summary.emmGrid()</code> or <code>lsmeans::summary.ref.grid()</code> . Cautionary note: misspecified arguments may be silently ignored!

Details

Returns a data frame with one observation for each estimated marginal mean, and one column for each combination of factors. When the input is a contrast, each row will contain one estimated contrast.

There are a large number of arguments that can be passed on to `emmeans::summary.emmGrid()` or `lsmeans::summary.ref.grid()`.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
df	Degrees of freedom used by this term in the model.
p.value	The two-sided p-value associated with the observed statistic.
std.error	The standard error of the regression term.
estimate	Expected marginal mean
statistic	T-ratio statistic

See Also

`tidy()`, `emmeans::ref_grid()`, `emmeans::emmeans()`, `emmeans::contrast()`

Other emmeans tidiers: `tidy.lsmobj()`, `tidy.ref.grid()`, `tidy.summary_emm()`

Examples

```
# load libraries for models and data
library(emmeans)

# linear model for sales of oranges per day
oranges_lm1 <- lm(sales1 ~ price1 + price2 + day + store, data = oranges)

# reference grid; see vignette("basics", package = "emmeans")
oranges_rg1 <- ref_grid(oranges_lm1)
td <- tidy(oranges_rg1)
td

# marginal averages
marginal <- emmeans(oranges_rg1, "day")
tidy(marginal)

# contrasts
tidy(contrast(marginal))
tidy(contrast(marginal, method = "pairwise"))

# plot confidence intervals
library(ggplot2)

ggplot(tidy(marginal, conf.int = TRUE), aes(day, estimate)) +
  geom_point() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# by multiple prices
by_price <- emmeans(oranges_lm1, "day",
  by = "price2",
  at = list(
    price1 = 50, price2 = c(40, 60, 80),
    day = c("2", "3", "4")
  )
)

by_price

tidy(by_price)

ggplot(tidy(by_price, conf.int = TRUE), aes(price2, estimate, color = day)) +
  geom_line() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# joint_tests
tidy(joint_tests(oranges_lm1))
```

tidy.epi.2by2	<i>Tidy a(n) epi.2by2 object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'epi.2by2'
tidy(x, parameters = c("moa", "stat"), ...)
```

Arguments

x	A epi.2by2 object produced by a call to <code>epiR::epi.2by2()</code>
parameters	Return measures of association (moa) or test statistics (stat), default is moa (measures of association)
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The tibble has a column for each of the measures of association or tests contained in `massoc` or `massoc.detail` when `epiR::epi.2by2()` is called.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
df	Degrees of freedom used by this term in the model.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
term	The name of the regression term.
estimate	Estimated measure of association

See Also

[tidy\(\)](#), [epiR::epi.2by2\(\)](#)

Examples

```
# load libraries for models and data
library(epiR)

# generate data
dat <- matrix(c(13, 2163, 5, 3349), nrow = 2, byrow = TRUE)

rownames(dat) <- c("DF+", "DF-")
colnames(dat) <- c("FUS+", "FUS-")

# fit model
fit <- epi.2by2(
  dat = as.table(dat), method = "cross.sectional",
  conf.level = 0.95, units = 100, outcome = "as.columns"
)

# summarize model fit with tidiers
tidy(fit, parameters = "moa")
tidy(fit, parameters = "stat")
```

tidy.ergm

Tidy a(n) ergm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

The methods should work with any model that conforms to the **ergm** class, such as those produced from weighted networks by the **ergm.count** package.

Usage

```
## S3 method for class 'ergm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	An ergm object returned from a call to <code>ergm::ergm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments to pass to <code>ergm::summary()</code> . Cautionary note: Mis-specified arguments may be silently ignored.

Value

A `tibble::tibble` with one row for each coefficient in the exponential random graph model, with columns:

term	The term in the model being estimated and tested
estimate	The estimated coefficient
std.error	The standard error
mcmc.error	The MCMC error
p.value	The two-sided p-value

References

Hunter DR, Handcock MS, Butts CT, Goodreau SM, Morris M (2008b). **ergm**: A Package to Fit, Simulate and Diagnose Exponential-Family Models for Networks. *Journal of Statistical Software*, 24(3). <https://www.jstatsoft.org/v24/i03/>.

See Also

`tidy()`, `ergm::ergm()`, `ergm::control.ergm()`, `ergm::summary()`

Other ergm tidiers: `glance.ergm()`

Examples

```
# load libraries for models and data
library(ergm)

# load the Florentine marriage network data
data(florentine)

# fit a model where the propensity to form ties between
# families depends on the absolute difference in wealth
```

```

gest <- ergm(flomarriage ~ edges + absdiff("wealth"))

# show terms, coefficient estimates and errors
tidy(gest)

# show coefficients as odds ratios with a 99% CI
tidy(gest, exponentiate = TRUE, conf.int = TRUE, conf.level = 0.99)

# take a look at likelihood measures and other
# control parameters used during MCMC estimation
glance(gest)
glance(gest, deviance = TRUE)
glance(gest, mcmc = TRUE)

```

tidy.factanal	<i>Tidy a(n) factanal object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'factanal'
tidy(x, ...)

```

Arguments

x	A factanal object created by <code>stats::factanal()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

variable	Variable under consideration.
uniqueness	Proportion of residual, or unexplained variance
flX	Factor loading for level X.

See Also

[tidy\(\)](#), [stats::factanal\(\)](#)

Other factanal tidiers: [augment.factanal\(\)](#), [glance.factanal\(\)](#)

Examples

```
set.seed(123)

# generate data
library(dplyr)
library(purrr)

m1 <- tibble(
  v1 = c(1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 3, 3, 3, 3, 3, 4, 5, 6),
  v2 = c(1, 2, 1, 1, 1, 1, 2, 1, 2, 1, 3, 4, 3, 3, 3, 4, 6, 5),
  v3 = c(3, 3, 3, 3, 3, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 5, 4, 6),
  v4 = c(3, 3, 4, 3, 3, 1, 1, 2, 1, 1, 1, 1, 2, 1, 1, 5, 6, 4),
  v5 = c(1, 1, 1, 1, 1, 3, 3, 3, 3, 3, 1, 1, 1, 1, 1, 6, 4, 5),
  v6 = c(1, 1, 1, 2, 1, 3, 3, 3, 4, 3, 1, 1, 1, 2, 1, 6, 5, 4)
)

# new data
m2 <- map_dfr(m1, rev)

# factor analysis objects
fit1 <- factanal(m1, factors = 3, scores = "Bartlett")
fit2 <- factanal(m1, factors = 3, scores = "regression")

# tidying the object
tidy(fit1)
tidy(fit2)

# augmented dataframe
augment(fit1)
augment(fit2)

# augmented dataframe (with new data)
augment(fit1, data = m2)
augment(fit2, data = m2)
```

tidy.felm

Tidy a(n) felm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers

to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'felm'
tidy(
  x,
  conf.int = FALSE,
  conf.level = 0.95,
  fe = FALSE,
  se.type = c("default", "iid", "robust", "cluster"),
  ...
)
```

Arguments

<code>x</code>	A <code>felm</code> object returned from <code>lfe::felm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>fe</code>	Logical indicating whether or not to include estimates of fixed effects. Defaults to <code>FALSE</code> .
<code>se.type</code>	Character indicating the type of standard errors. Defaults to using those of the underlying <code>felm()</code> model object, e.g. clustered errors for models that were provided a cluster specification. Users can override these defaults by specifying an appropriate alternative: "iid" (for homoskedastic errors), "robust" (for Eicker-White robust errors), or "cluster" (for clustered standard errors; if the model object supports it).
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.

estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[tidy\(\)](#), [lfe::felm\(\)](#)

Other felm tidiers: [augment.felm\(\)](#)

Examples

```
# load libraries for models and data
library(lfe)

# use built-in `airquality` dataset
head(airquality)

# no FEs; same as lm()
est0 <- felm(Ozone ~ Temp + Wind + Solar.R, airquality)

# summarize model fit with tidiers
tidy(est0)
augment(est0)

# add month fixed effects
est1 <- felm(Ozone ~ Temp + Wind + Solar.R | Month, airquality)

# summarize model fit with tidiers
tidy(est1)
tidy(est1, fe = TRUE)
augment(est1)
glance(est1)

# the "se.type" argument can be used to switch out different standard errors
# types on the fly. In turn, this can be useful exploring the effect of
# different error structures on model inference.
tidy(est1, se.type = "iid")
tidy(est1, se.type = "robust")

# add clustered SEs (also by month)
est2 <- felm(Ozone ~ Temp + Wind + Solar.R | Month | 0 | Month, airquality)

# summarize model fit with tidiers
tidy(est2, conf.int = TRUE)
tidy(est2, conf.int = TRUE, se.type = "cluster")
```



```
tidy(est2, conf.int = TRUE, se.type = "robust")
tidy(est2, conf.int = TRUE, se.type = "iid")
```

tidy.fitdistr	<i>Tidy a(n) fitdistr object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'fitdistr'
tidy(x, ...)
```

Arguments

x	A fitdistr object returned by <code>MASS::fitdistr()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

`tidy()`, `MASS::fitdistr()`

Other fitdistr tidiers: `glance.fitdistr()`

Examples

```
# load libraries for models and data
library(MASS)

# generate data
set.seed(2015)
x <- rnorm(100, 5, 2)

# fit models
fit <- fitdistr(x, dnorm, list(mean = 3, sd = 1))

# summarize model fit with tidiers
tidy(fit)
glance(fit)
```

tidy.fixest

Tidy a(n) fixest object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'fixest'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A fixest object returned from any of the fixest estimators
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if conf.int = TRUE. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments passed to summary and confint. Important arguments are se and cluster. Other arguments are dof, exact_dof, forceCovariance, and keepBounded. See summary.fixest .

Details

The `fixest` package provides a family of functions for estimating models with arbitrary numbers of fixed-effects, in both an OLS and a GLM context. The package also supports robust (i.e. White) and clustered standard error reporting via the generic `summary.fixest()` command. In a similar vein, the `tidy()` method for these models allows users to specify a desired standard error correction either 1) implicitly via the supplied `fixest` object, or 2) explicitly as part of the `tidy` call. See examples below.

Note that `fixest` confidence intervals are calculated assuming a normal distribution – this assumes infinite degrees of freedom for the CI. (This assumption is distinct from the degrees of freedom used to calculate the standard errors. For more on degrees of freedom with clusters and fixed effects, see <https://github.com/lrberge/fixest/issues/6> and <https://github.com/sgaure/lfe/issues/1#issuecomment-530646990>)

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `fixest::feglm()`, `fixest::fenegbin()`, `fixest::feNmlm()`, `fixest::femlm()`, `fixest::feols()`, `fixest::fepois()`

Other `fixest` tidiers: `augment.fixest()`

Examples

```
# load libraries for models and data
library(fixest)

gravity <-
  feols(
    log(Euros) ~ log(dist_km) | Origin + Destination + Product + Year, trade
  )

tidy(gravity)
glance(gravity)
augment(gravity, trade)
```

```

# to get robust or clustered SEs, users can either:

# 1) specify the arguments directly in the `tidy()` call

tidy(gravity, conf.int = TRUE, cluster = c("Product", "Year"))

tidy(gravity, conf.int = TRUE, se = "threeway")

# 2) or, feed tidy() a summary.fixest object that has already accepted
# these arguments

gravity_summ <- summary(gravity, cluster = c("Product", "Year"))

tidy(gravity_summ, conf.int = TRUE)

# approach (1) is preferred.

```

tidy.ftable	<i>(Deprecated) Tidy ftable objects</i>
-------------	---

Description

This function is deprecated. Please use `tibble::as_tibble()` instead.

Usage

```

## S3 method for class 'ftable'
tidy(x, ...)

```

Arguments

x	An ftable object returned from <code>stats::ftable()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

An ftable contains a "flat" contingency table. This melts it into a `tibble::tibble` with one column for each variable, then a `Freq` column.

See Also

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [data.frame_tidiers](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.numeric\(\)](#)

tidy.Gam	<i>Tidy a(n) Gam object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'Gam'
tidy(x, ...)
```

Arguments

x	A Gam object returned from a call to gam::gam() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

Tidy gam objects created by calls to [mgcv::gam\(\)](#) with [tidy.gam\(\)](#).

Value

A [tibble::tibble\(\)](#) with columns:

df	Degrees of freedom used by this term in the model.
meansq	Mean sum of squares. Equal to total sum of squares divided by degrees of freedom.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
sumsq	Sum of squares explained by this term.
term	The name of the regression term.

See Also

`tidy()`, `gam::gam()`, `tidy.anova()`, `tidy.gam()`

Other gam tidiers: `glance.Gam()`

Examples

```
# load libraries for models and data
library(gam)

# fit model
g <- gam(mpg ~ s(hp, 4) + am + qsec, data = mtcars)

# summarize model fit with tidiers
tidy(g)
glance(g)
```

tidy.gam

Tidy a(n) gam object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'gam'
tidy(
  x,
  parametric = FALSE,
  conf.int = FALSE,
  conf.level = 0.95,
  exponentiate = FALSE,
  ...
)
```

Arguments

`x` A gam object returned from a call to `mgcv::gam()`.

`parametric` Logical indicating if parametric or smooth terms should be tidied. Defaults to FALSE, meaning that smooth terms are tidied by default.

<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

When `parametric = FALSE` return columns `edf` and `ref.df` rather than `estimate` and `std.error`.

Value

A `tibble::tibble()` with columns:

<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>edf</code>	The effective degrees of freedom. Only reported when <code>'parametric = FALSE'</code>
<code>ref.df</code>	The reference degrees of freedom. Only reported when <code>'parametric = FALSE'</code>

See Also

`tidy()`, `mgcv::gam()`

Other mgcv tidiers: `glance.gam()`

Examples

```
# load libraries for models and data
library(mgcv)
```

```
# fit model
g <- gam(mpg ~ s(hp) + am + qsec, data = mtcars)

# summarize model fit with tidiers
tidy(g)
tidy(g, parametric = TRUE)
glance(g)
augment(g)
```

tidy.garch

Tidy a(n) garch object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'garch'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A garch object returned by <code>tseries::garch()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `tseries::garch()`

Other garch tidiers: `glance.garch()`

Examples

```
# load libraries for models and data
library(tseries)

# load data
data(EuStockMarkets)

# fit model
dax <- diff(log(EuStockMarkets))[, "DAX"]
dax.garch <- garch(dax)
dax.garch

# summarize model fit with tidiers
tidy(dax.garch)
glance(dax.garch)
```

`tidy.geeglm`

Tidy a(n) geeglm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'geeglm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A geeglm object returned from a call to <code>geepack::geeglm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

If `conf.int = TRUE`, the confidence interval is computed with the an internal `confint.geeglm()` function.

If you have missing values in your model data, you may need to refit the model with `na.action = na.exclude` or deal with the missingness in the data beforehand.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[tidy\(\)](#), [geepack::geeglm\(\)](#)

Examples

```
# load modeling library
library(geepack)

# load data
data(state)

ds <- data.frame(state.region, state.x77)

# fit model
geefit <- geeglm(Income ~ Frost + Murder,
  id = state.region,
  data = ds, family = gaussian,
  corstr = "exchangeable"
)

# summarize model fit with tidiers
tidy(geefit)
tidy(geefit, conf.int = TRUE)
```

tidy.glht

Tidy a(n) glht object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'glht'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x A glht object returned by [multcomp::glht\(\)](#).

conf.int Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.

<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>contrast</code>	Levels being compared.
<code>estimate</code>	The estimated value of the regression term.
<code>null.value</code>	Value to which the estimate is compared.

See Also

`tidy()`, `multcomp::glht()`

Other multcomp tidiers: `tidy.cld()`, `tidy.confint.glht()`, `tidy.summary.glht()`

Examples

```
# load libraries for models and data
library(multcomp)
library(ggplot2)

amod <- aov(breaks ~ wool + tension, data = warpbreaks)
wht <- glht(amod, linfct = mcp(tension = "Tukey"))

tidy(wht)

ggplot(wht, aes(lhs, estimate)) +
  geom_point()

CI <- confint(wht)

tidy(CI)

ggplot(CI, aes(lhs, estimate, ymin = lwr, ymax = upr)) +
  geom_pointrange()

tidy(summary(wht))
```

```
ggplot(mapping = aes(lhs, estimate)) +
  geom_linerange(aes(ymin = lwr, ymax = upr), data = CI) +
  geom_point(aes(size = p), data = summary(wht)) +
  scale_size(trans = "reverse")

cld <- cld(wht)
tidy(cld)
```

tidy.glm

Tidy a(n) glm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'glm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A glm object returned from <code>stats::glm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

See Also

`stats::glm()`

Other lm tidiers: `augment.glm()`, `augment.lm()`, `glance.glm()`, `glance.lm()`, `glance.summary.lm()`, `glance.svyglm()`, `tidy.lm.beta()`, `tidy.lm()`, `tidy.mlrm()`, `tidy.summary.lm()`

tidy.glmnet

Tidy a(n) glmnet object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'glmnet'
tidy(x, return_zeros = FALSE, ...)
```

Arguments

<code>x</code>	A glmnet object returned from <code>glmnet::glmnet()</code> .
<code>return_zeros</code>	Logical indicating whether coefficients with value zero should be included in the results. Defaults to FALSE.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

Note that while this representation of GLMs is much easier to plot and combine than the default structure, it is also much more memory-intensive. Do not use for large, sparse matrices.

No `augment` method is yet provided even though the model produces predictions, because the input data is not tidy (it is a matrix that may be very wide) and therefore combining predictions with it is not logical. Furthermore, predictions make sense only with a specific choice of lambda.

Value

A `tibble::tibble()` with columns:

<code>dev.ratio</code>	Fraction of null deviance explained at each value of lambda.
<code>estimate</code>	The estimated value of the regression term.
<code>lambda</code>	Value of penalty parameter lambda.
<code>step</code>	Which step of lambda choices was used.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `glmnet::glmnet()`

Other glmnet tidiers: `glance.cv.glmnet()`, `glance.glmnet()`, `tidy.cv.glmnet()`

Examples

```
# load libraries for models and data
library(glmnet)

set.seed(2014)
x <- matrix(rnorm(100 * 20), 100, 20)
y <- rnorm(100)
fit1 <- glmnet(x, y)

# summarize model fit with tidiers + visualization
tidy(fit1)
glance(fit1)

library(dplyr)
library(ggplot2)

tidied <- tidy(fit1) %>% filter(term != "(Intercept)")

ggplot(tidied, aes(step, estimate, group = term)) +
  geom_line()

ggplot(tidied, aes(lambda, estimate, group = term)) +
  geom_line() +
  scale_x_log10()

ggplot(tidied, aes(lambda, dev.ratio)) +
  geom_line()

# works for other types of regressions as well, such as logistic
g2 <- sample(1:2, 100, replace = TRUE)
fit2 <- glmnet(x, g2, family = "binomial")
tidy(fit2)
```

tidy.glmRob

Tidy a(n) glmRob object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'glmRob'
tidy(x, ...)
```

Arguments

`x` A `glmRob` object returned from `robust::glmRob()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

See Also

`robust::glmRob()`

Other robust tidiers: `augment.lmRob()`, `glance.glmRob()`, `glance.lmRob()`, `tidy.lmRob()`

Examples

```
# load libraries for models and data
library(robust)

# fit model
gm <- glmRob(am ~ wt, data = mtcars, family = "binomial")
```



```
# summarize model fit with tidiers
tidy(gm)
glance(gm)
```

tidy.glmrob	<i>Tidy a(n) glmrob object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'glmrob'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A <code>glmrob</code> object returned from <code>robustbase::glmrob()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`robustbase::glmrob()`

Other robustbase tidiers: `augment.glmrob()`, `augment.lmrob()`, `glance.lmrob()`, `tidy.lmrob()`

Examples

```
if (requireNamespace("robustbase", quietly = TRUE)) {

# load libraries for models and data
library(robustbase)

data(coleman)
set.seed(0)

m <- lmrob(Y ~ ., data = coleman)
tidy(m)
augment(m)
glance(m)

data(carrots)

Rfit <- glmrob(cbind(success, total - success) ~ logdose + block,
  family = binomial, data = carrots, method = "Mqle",
  control = glmrobMqle.control(tcc = 1.2)
)

tidy(Rfit)
augment(Rfit)

}
```

tidy.gmm	<i>Tidy a(n) gmm object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'gmm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A gmm object returned from <code>gmm::gmm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.

statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[tidy\(\)](#), [gmm::gmm\(\)](#)

Other gmm tidiers: [glance.gmm\(\)](#)

Examples

```
# load libraries for models and data
library(gmm)

# examples come from the "gmm" package
# CAPM test with GMM
data(Finance)
r <- Finance[1:300, 1:10]
rm <- Finance[1:300, "rm"]
rf <- Finance[1:300, "rf"]

z <- as.matrix(r - rf)
t <- nrow(z)
zm <- rm - rf
h <- matrix(zm, t, 1)
res <- gmm(z ~ zm, x = h)

# tidy result
tidy(res)
tidy(res, conf.int = TRUE)
tidy(res, conf.int = TRUE, conf.level = .99)

# coefficient plot
library(ggplot2)
library(dplyr)

tidy(res, conf.int = TRUE) %>%
  mutate(variable = reorder(term, estimate)) %>%
  ggplot(aes(estimate, variable)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_vline(xintercept = 0, color = "red", lty = 2)

# from a function instead of a matrix
g <- function(theta, x) {
  e <- x[, 2:11] - theta[1] - (x[, 1] - theta[1]) %*% matrix(theta[2:11], 1, 10)
  gmat <- cbind(e, e * c(x[, 1]))
  return(gmat)
}
```

```

}

x <- as.matrix(cbind(rm, r))
res_black <- gmm(g, x = x, t0 = rep(0, 11))

tidy(res_black)
tidy(res_black, conf.int = TRUE)

# APT test with Fama-French factors and GMM

f1 <- zm
f2 <- Finance[1:300, "hml"] - rf
f3 <- Finance[1:300, "smb"] - rf
h <- cbind(f1, f2, f3)
res2 <- gmm(z ~ f1 + f2 + f3, x = h)

td2 <- tidy(res2, conf.int = TRUE)
td2

# coefficient plot
td2 %>%
  mutate(variable = reorder(term, estimate)) %>%
  ggplot(aes(estimate, variable)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_vline(xintercept = 0, color = "red", lty = 2)

```

tidy.htest

Tidy/glance a(n) htest object

Description

For models that have only a single component, the `tidy()` and `glance()` methods are identical. Please see the documentation for both of those methods.

Usage

```

## S3 method for class 'htest'
tidy(x, ...)

## S3 method for class 'htest'
glance(x, ...)

```

Arguments

`x` An `htest` objected, such as those created by `stats::cor.test()`, `stats::t.test()`, `stats::wilcox.test()`, `stats::chisq.test()`, etc.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>alternative</code>	Alternative hypothesis (character).
<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>estimate1</code>	Sometimes two estimates are computed, such as in a two-sample t-test.
<code>estimate2</code>	Sometimes two estimates are computed, such as in a two-sample t-test.
<code>method</code>	Method used.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>parameter</code>	The parameter being modeled.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.

See Also

`tidy()`, `stats::cor.test()`, `stats::t.test()`, `stats::wilcox.test()`, `stats::chisq.test()`

Other htest tidiers: `augment.htest()`, `tidy.pairwise.htest()`, `tidy.power.htest()`

Examples

```
tt <- t.test(rnorm(10))

tidy(tt)

# the glance output will be the same for each of the below tests
glance(tt)

tt <- t.test(mpg ~ am, data = mtcars)

tidy(tt)

wt <- wilcox.test(mpg ~ am, data = mtcars, conf.int = TRUE, exact = FALSE)
```

```

tidy(wt)

ct <- cor.test(mtcars$wt, mtcars$mpg)

tidy(ct)

chit <- chisq.test(xtabs(Freq ~ Sex + Class, data = as.data.frame(Titanic)))

tidy(chit)
augment(chit)

```

tidy.ivreg

Tidy a(n) ivreg object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'ivreg'
tidy(x, conf.int = FALSE, conf.level = 0.95, instruments = FALSE, ...)

```

Arguments

x	An ivreg object created by a call to <code>AER::ivreg()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
instruments	Logical indicating whether to return coefficients from the second-stage or diagnostics tests for each endogenous regressor (F-statistics). Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

This tidier currently only supports ivreg-classed objects outputted by the AER package. The ivreg package also outputs objects of class ivreg, and will be supported in a later release.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>p.value.Sargan</code>	p-value for Sargan test of overidentifying restrictions.
<code>p.value.weakinst</code>	p-value for weak instruments test.
<code>p.value.Wu.Hausman</code>	p-value for Wu-Hausman weak instruments test for endogeneity.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>statistic.Sargan</code>	Statistic for Sargan test of overidentifying restrictions.
<code>statistic.weakinst</code>	Statistic for Wu-Hausman test.
<code>statistic.Wu.Hausman</code>	Statistic for Wu-Hausman weak instruments test for endogeneity.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `AER::ivreg()`

Other ivreg tidiers: `augment.ivreg()`, `glance.ivreg()`

Examples

```
# load libraries for models and data
library(AER)

# load data
data("CigarettesSW", package = "AER")

# fit model
ivr <- ivreg(
  log(packs) ~ income | population,
  data = CigarettesSW,
```



```

  subset = year == "1995"
)

# summarize model fit with tidiers
tidy(ivr)
tidy(ivr, conf.int = TRUE)
tidy(ivr, conf.int = TRUE, instruments = TRUE)

augment(ivr)
augment(ivr, data = CigarettesSW)
augment(ivr, newdata = CigarettesSW)

glance(ivr)

```

tidy.kappa

Tidy a(n) kappa object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'kappa'
tidy(x, ...)

```

Arguments

x A kappa object returned from `psych::cohen.kappa()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

Note that confidence level (alpha) for the confidence interval cannot be set in tidy. Instead you must set the `alpha` argument to `psych::cohen.kappa()` when creating the kappa object.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>type</code>	Either 'weighted' or 'unweighted'.

See Also

`tidy()`, `psych::cohen.kappa()`

Examples

```
# load libraries for models and data
library(psych)

# generate example data
rater1 <- 1:9
rater2 <- c(1, 3, 1, 6, 1, 5, 5, 6, 7)

# fit model
ck <- cohen.kappa(cbind(rater1, rater2))

# summarize model fit with tidiers + visualization
tidy(ck)

# graph the confidence intervals
library(ggplot2)

ggplot(tidy(ck), aes(estimate, type)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high))
```

tidy.kde

Tidy a(n) kde object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'kde'
tidy(x, ...)
```

Arguments

`x` A kde object returned from `ks::kde()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

Returns a data frame in long format with four columns. Use `tidyr::pivot_wider(..., names_from = variable, values_from = value)` on the output to return to a wide format.

Value

A `tibble::tibble()` with columns:

<code>estimate</code>	The estimated value of the regression term.
<code>obs</code>	weighted observed number of events in each group.
<code>value</code>	The value/estimate of the component. Results from data reshaping.
<code>variable</code>	Variable under consideration.

See Also

[tidy\(\)](#), [ks::kde\(\)](#)

Examples

```
# load libraries for models and data
library(ks)

# generate data
dat <- replicate(2, rnorm(100))
k <- kde(dat)

# summarize model fit with tidiers + visualization
td <- tidy(k)
td
```

```

library(ggplot2)
library(dplyr)
library(tidyr)

td %>%
  pivot_wider(c(obs, estimate),
             names_from = variable,
             values_from = value
            ) %>%
  ggplot(aes(x1, x2, fill = estimate)) +
  geom_tile() +
  theme_void()

# also works with 3 dimensions
dat3 <- replicate(3, rnorm(100))
k3 <- kde(dat3)

td3 <- tidy(k3)
td3

```

tidy.Kendall

Tidy a(n) Kendall object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'Kendall'
tidy(x, ...)
```

Arguments

- | | |
|-----|---|
| x | A Kendall object returned from a call to <code>Kendall::Kendall()</code> , <code>Kendall::MannKendall()</code> , or <code>Kendall::SeasonalMannKendall()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with columns:

<code>kendall_score</code>	Kendall score.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>var_kendall_score</code>	Variance of the <code>kendall_score</code> .
<code>statistic</code>	Kendall's tau statistic
<code>denominator</code>	The denominator, which is $\tau = \text{kendall_score} / \text{denominator}$.

See Also

`tidy()`, `Kendall::Kendall()`, `Kendall::MannKendall()`, `Kendall::SeasonalMannKendall()`

Examples

```
# load libraries for models and data
library(Kendall)

A <- c(2.5, 2.5, 2.5, 2.5, 5, 6.5, 6.5, 10, 10, 10, 10, 10, 14, 14, 14, 16, 17)
B <- c(1, 1, 1, 1, 2, 1, 1, 2, 1, 1, 1, 1, 1, 1, 2, 2, 2)

# fit models and summarize results
f_res <- Kendall(A, B)
tidy(f_res)

s_res <- MannKendall(B)
tidy(s_res)

t_res <- SeasonalMannKendall(ts(A))
tidy(t_res)
```

`tidy.kmeans`

Tidy a(n) kmeans object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'kmeans'
tidy(x, col.names = colnames(x$centers), ...)
```

Arguments

<code>x</code>	A kmeans object created by <code>stats::kmeans()</code> .
<code>col.names</code>	Dimension names. Defaults to the names of the variables in <code>x</code> . Set to <code>NULL</code> to get names <code>x1</code> , <code>x2</code> , <code>...</code>
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>cluster</code>	A factor describing the cluster from 1:k.
<code>size</code>	Number of points assigned to cluster.
<code>withinss</code>	The within-cluster sum of squares.

See Also

`tidy()`, `stats::kmeans()`

Other kmeans tidiers: `augment.kmeans()`, `glance.kmeans()`

Examples

```
library(cluster)
library(modeldata)
library(dplyr)

data(hpc_data)

x <- hpc_data[, 2:5]

fit <- pam(x, k = 4)

tidy(fit)
glance(fit)
augment(fit, x)
```

tidy.lavaan	<i>Tidy a(n) lavaan object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lavaan'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A lavaan object, such as those returned from <code>lavaan::cfa()</code> , and <code>lavaan::sem()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments passed to <code>lavaan::parameterEstimates()</code> . Cautionary note: Misspecified arguments may be silently ignored.

Value

A `tibble::tibble()` with one row for each estimated parameter and columns:

term	The result of <code>paste(lhs, op, rhs)</code>
op	The operator in the model syntax (e.g. <code>~~</code> for covariances, or <code>~</code> for regression parameters)
group	The group (if specified) in the lavaan model
estimate	The parameter estimate (may be standardized)
std.error	
statistic	The z value returned by <code>lavaan::parameterEstimates()</code>
p.value	
conf.low	
conf.high	
std.lv	Standardized estimates based on the variances of the (continuous) latent variables only
std.all	Standardized estimates based on both the variances of both (continuous) observed and latent variables.
std.noX	Standardized estimates based on both the variances of both (continuous) observed and latent variables, but not the variances of exogenous covariates.

See Also

`tidy()`, `lavaan::cfa()`, `lavaan::sem()`, `lavaan::parameterEstimates()`

Other lavaan tidiers: `glance.lavaan()`

Examples

```
# load libraries for models and data
library(lavaan)

cfa.fit <- cfa("F =~ x1 + x2 + x3 + x4 + x5 + x6 + x7 + x8 + x9",
  data = HolzingerSwineford1939, group = "school"
)

tidy(cfa.fit)
```

tidy.lm

Tidy a(n) lm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

<code>x</code>	An <code>lm</code> object created by <code>stats::lm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .

- ...
- Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

If the linear model is an `mlm` object (multiple linear model), there is an additional column response. See [tidy.mlm\(\)](#).

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

[tidy\(\)](#), [stats::summary.lm\(\)](#)

Other lm tidiers: [augment.glm\(\)](#), [augment.lm\(\)](#), [glance.glm\(\)](#), [glance.lm\(\)](#), [glance.summary.lm\(\)](#), [glance.svyglm\(\)](#), [tidy.glm\(\)](#), [tidy.lm.beta\(\)](#), [tidy.mlm\(\)](#), [tidy.summary.lm\(\)](#)

Examples

```
library(ggplot2)
library(dplyr)

mod <- lm(mpg ~ wt + qsec, data = mtcars)

tidy(mod)
glance(mod)

# coefficient plot
d <- tidy(mod, conf.int = TRUE)
```

```

ggplot(d, aes(estimate, term, xmin = conf.low, xmax = conf.high, height = 0)) +
  geom_point() +
  geom_vline(xintercept = 0, lty = 4) +
  geom_errorbarh()

# aside: There are tidy() and glance() methods for lm.summary objects too.
# this can be useful when you want to conserve memory by converting large lm
# objects into their leaner summary.lm equivalents.
s <- summary(mod)
tidy(s, conf.int = TRUE)
glance(s)

augment(mod)
augment(mod, mtcars, interval = "confidence")

# predict on new data
newdata <- mtcars %>%
  head(6) %>%
  mutate(wt = wt + 1)
augment(mod, newdata = newdata)

# ggplot2 example where we also construct 95% prediction interval

# simpler bivariate model since we're plotting in 2D
mod2 <- lm(mpg ~ wt, data = mtcars)

au <- augment(mod2, newdata = newdata, interval = "prediction")

ggplot(au, aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted)) +
  geom_ribbon(aes(ymin = .lower, ymax = .upper), col = NA, alpha = 0.3)

# predict on new data without outcome variable. Output does not include .resid
newdata <- newdata %>%
  select(-mpg)

augment(mod, newdata = newdata)

au <- augment(mod, data = mtcars)

ggplot(au, aes(.hat, .std.resid)) +
  geom_vline(size = 2, colour = "white", xintercept = 0) +
  geom_hline(size = 2, colour = "white", yintercept = 0) +
  geom_point() +
  geom_smooth(se = FALSE)

plot(mod, which = 6)

ggplot(au, aes(.hat, .cooks)) +
  geom_vline(xintercept = 0, colour = NA) +
  geom_abline(slope = seq(0, 3, by = 0.5), colour = "white") +
  geom_smooth(se = FALSE) +

```

```

  geom_point()

# column-wise models
a <- matrix(rnorm(20), nrow = 10)
b <- a + rnorm(length(a))
result <- lm(b ~ a)

tidy(result)

```

tidy.lm.beta

Tidy a(n) lm.beta object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'lm.beta'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

```

Arguments

x	An <code>lm.beta</code> object created by <code>lm.beta::lm.beta</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

If the linear model is an `mlm` object (multiple linear model), there is an additional column response. If you have missing values in your model data, you may need to refit the model with `na.action = na.exclude`.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

Other lm tidiers: [augment.glm\(\)](#), [augment.lm\(\)](#), [glance.glm\(\)](#), [glance.lm\(\)](#), [glance.summary.lm\(\)](#), [glance.svyglm\(\)](#), [tidy.glm\(\)](#), [tidy.lm\(\)](#), [tidy.mlm\(\)](#), [tidy.summary.lm\(\)](#)

Examples

```
# load libraries for models and data
library(lm.beta)

# fit models
mod <- stats::lm(speed ~ ., data = cars)
std <- lm.beta(mod)

# summarize model fit with tidiers
tidy(std, conf.int = TRUE)

# generate data
ctl <- c(4.17, 5.58, 5.18, 6.11, 4.50, 4.61, 5.17, 4.53, 5.33, 5.14)
trt <- c(4.81, 4.17, 4.41, 3.59, 5.87, 3.83, 6.03, 4.89, 4.32, 4.69)
group <- gl(2, 10, 20, labels = c("Ctl", "Trt"))
weight <- c(ctl, trt)

# fit models
mod2 <- lm(weight ~ group)
std2 <- lm.beta(mod2)

# summarize model fit with tidiers
tidy(std2, conf.int = TRUE)
```

tidy.lmodel2	<i>Tidy a(n) lmodel2 object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lmodel2'
tidy(x, ...)
```

Arguments

x	A lmodel2 object returned by <code>lmodel2::lmodel2()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

There are always only two terms in an lmodel2: "Intercept" and "Slope". These are computed by four methods: OLS (ordinary least squares), MA (major axis), SMA (standard major axis), and RMA (ranged major axis).

The returned p-value is one-tailed and calculated via a permutation test. A permutational test is used because distributional assumptions may not be valid. More information can be found in `vignette("mod2user", package = "lmodel2")`.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>term</code>	The name of the regression term.
<code>method</code>	Either OLS/MA/SMA/RMA

See Also

[tidy\(\)](#), [lmodel2::lmodel2\(\)](#)

Other lmodel2 tidiers: [glance.lmodel2\(\)](#)

Examples

```
# load libraries for models and data
library(lmodel2)

data(mod2ex2)
Ex2.res <- lmodel2(Prey ~ Predators, data = mod2ex2, "relative", "relative", 99)
Ex2.res

# summarize model fit with tidiers + visualization
tidy(Ex2.res)
glance(Ex2.res)

# this allows coefficient plots with ggplot2
library(ggplot2)

ggplot(tidy(Ex2.res), aes(estimate, term, color = method)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high))
```

tidy.lmRob

Tidy a(n) lmRob object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lmRob'
tidy(x, ...)
```

Arguments

x A lmRob object returned from [robust::lmRob\(\)](#).

- ...
- Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see [tidy.rlm\(\)](#).

See Also

[robust::lmRob\(\)](#)

Other robust tidiers: [augment.lmRob\(\)](#), [glance.glmRob\(\)](#), [glance.lmRob\(\)](#), [tidy.glmRob\(\)](#)

Examples

```
# load modeling library
library(robust)

# fit model
m <- lmRob(mpg ~ wt, data = mtcars)

# summarize model fit with tidiers
tidy(m)
augment(m)
glance(m)
```

tidy.lmrob

Tidy a(n) lmrob object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lmrob'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	A <code>lmrob</code> object returned from <code>robustbase::lmrob()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

See Also

`robustbase::lmrob()`

Other robustbase tidiers: `augment.glmrob()`, `augment.lmrob()`, `glance.lmrob()`, `tidy.glmrob()`

Examples

```
if (requireNamespace("robustbase", quietly = TRUE)) {

# load libraries for models and data
library(robustbase)

data(coleman)
set.seed(0)

m <- lmrob(Y ~ ., data = coleman)
tidy(m)
augment(m)
glance(m)

data(carrots)

Rfit <- glmrob(cbind(success, total - success) ~ logdose + block,
  family = binomial, data = carrots, method = "Mqle",
  control = glmrobMqle.control(tcc = 1.2)
)
```



```

tidy(Rfit)
augment(Rfit)

}

```

tidy.lsmobj

Tidy a(n) lsmobj object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'lsmobj'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

```

Arguments

x	An lsmobj object.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if conf.int = TRUE. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments passed to emmeans::summary.emmGrid() or lsmeans::summary.ref.grid() . Cautionary note: misspecified arguments may be silently ignored!

Details

Returns a data frame with one observation for each estimated marginal mean, and one column for each combination of factors. When the input is a contrast, each row will contain one estimated contrast.

There are a large number of arguments that can be passed on to [emmeans::summary.emmGrid\(\)](#) or [lsmeans::summary.ref.grid\(\)](#).

Value

A [tibble::tibble\(\)](#) with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
contrast	Levels being compared.

df	Degrees of freedom used by this term in the model.
null.value	Value to which the estimate is compared.
p.value	The two-sided p-value associated with the observed statistic.
std.error	The standard error of the regression term.
estimate	Expected marginal mean
statistic	T-ratio statistic

See Also

`tidy()`, `emmeans::ref_grid()`, `emmeans::emmeans()`, `emmeans::contrast()`

Other emmeans tidiers: `tidy.emmGrid()`, `tidy.ref.grid()`, `tidy.summary_emm()`

Examples

```
# load libraries for models and data
library(emmeans)

# linear model for sales of oranges per day
oranges_lm1 <- lm(sales1 ~ price1 + price2 + day + store, data = oranges)

# reference grid; see vignette("basics", package = "emmeans")
oranges_rg1 <- ref_grid(oranges_lm1)
td <- tidy(oranges_rg1)
td

# marginal averages
marginal <- emmeans(oranges_rg1, "day")
tidy(marginal)

# contrasts
tidy(contrast(marginal))
tidy(contrast(marginal, method = "pairwise"))

# plot confidence intervals
library(ggplot2)

ggplot(tidy(marginal, conf.int = TRUE), aes(day, estimate)) +
  geom_point() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# by multiple prices
by_price <- emmeans(oranges_lm1, "day",
  by = "price2",
  at = list(
    price1 = 50, price2 = c(40, 60, 80),
    day = c("2", "3", "4")
  )
)
```

```

by_price

tidy(by_price)

ggplot(tidy(by_price, conf.int = TRUE), aes(price2, estimate, color = day)) +
  geom_line() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# joint_tests
tidy(joint_tests(oranges_lm1))

```

tidy.manova	<i>Tidy a(n) manova object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'manova'
tidy(x, test = "Pillai", ...)

```

Arguments

x	A manova object return from <code>stats::manova()</code> .
test	One of "Pillai" (Pillai's trace), "Wilks" (Wilk's lambda), "Hotelling-Lawley" (Hotelling-Lawley trace) or "Roy" (Roy's greatest root) indicating which test statistic should be used. Defaults to "Pillai".
...	Arguments passed on to <code>stats::summary.manova</code>
object	An object of class "manova" or an aov object with multiple responses.
intercept	logical. If TRUE, the intercept term is included in the table.
tol	tolerance to be used in deciding if the residuals are rank-deficient: see qr .

Details

Depending on which test statistic is specified only one of pillai, wilks, hl or roy is included.

Value

A `tibble::tibble()` with columns:

<code>den.df</code>	Degrees of freedom of the denominator.
<code>num.df</code>	Degrees of freedom.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>term</code>	The name of the regression term.
<code>pillai</code>	Pillai's trace.
<code>wilks</code>	Wilk's lambda.
<code>hl</code>	Hotelling-Lawley trace.
<code>roy</code>	Roy's greatest root.

See Also

`tidy()`, `stats::summary.manova()`

Other anova tidiers: `glance.anova()`, `glance.aov()`, `tidy.TukeyHSD()`, `tidy.anova()`, `tidy.aovlist()`, `tidy.aov()`

Examples

```
npk2 <- within(npk, foo <- rnorm(24))
m <- manova(cbind(yield, foo) ~ block + N * P * K, npk2)
tidy(m)
```

`tidy.map`

Tidy a(n) map object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'map'
tidy(x, ...)
```

Arguments

<code>x</code>	A map object returned from <code>maps::map()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>term</code>	The name of the regression term.
<code>long</code>	Longitude.
<code>lat</code>	Latitude.

Remaining columns give information on geographic attributes and depend on the inputted map object. See `?maps::map` for more information.

See Also

`tidy()`, `maps::map()`

Examples

```
# load libraries for models and data
library(maps)
library(ggplot2)

ca <- map("county", "ca", plot = FALSE, fill = TRUE)

tidy(ca)

qplot(long, lat, data = ca, geom = "polygon", group = group)

tx <- map("county", "texas", plot = FALSE, fill = TRUE)
tidy(tx)
qplot(long, lat,
      data = tx, geom = "polygon", group = group,
      colour = I("white"))
)
```

tidy.margins	<i>Tidy a(n) margins object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'margins'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A margins object returned from <code>margins::margins()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The margins package provides a way to obtain coefficient marginal effects for a variety of (non-linear) models, such as logit or models with multiway interaction terms. Note that the `glance.margins()` method requires rerunning the underlying model again, which can take some time. Similarly, an `augment.margins()` method is not currently supported, but users can simply run the underlying model to obtain the same information.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
-----------	--

conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[tidy\(\)](#), [margins::margins\(\)](#)

Examples

```
# load libraries for models and data
library(margins)

# example 1: logit model
mod_log <- glm(am ~ cyl + hp + wt, data = mtcars, family = binomial)

# get tidied "naive" model coefficients
tidy(mod_log)

# convert to marginal effects with margins()
marg_log <- margins(mod_log)

# get tidied marginal effects
tidy(marg_log)
tidy(marg_log, conf.int = TRUE)

# requires running the underlying model again. quick for this example
glance(marg_log)

# augmenting `margins` outputs isn't supported, but
# you can get the same info by running on the underlying model
augment(mod_log)

# example 2: threeway interaction terms
mod_ie <- lm(mpg ~ wt * cyl * disp, data = mtcars)

# get tidied "naive" model coefficients
tidy(mod_ie)

# convert to marginal effects with margins()
marg_ie0 <- margins(mod_ie)
# get tidied marginal effects
tidy(marg_ie0)
glance(marg_ie0)
```

```

# marginal effects evaluated at specific values of a variable (here: cyl)
marg_ie1 <- margins(mod_ie, at = list(cyl = c(4,6,8)))

# summarize model fit with tidiers
tidy(marg_ie1)

# marginal effects of one interaction variable (here: wt), modulated at
# specific values of the two other interaction variables (here: cyl and drat)
marg_ie2 <- margins(mod_ie,
                    variables = "wt",
                    at = list(cyl = c(4,6,8), drat = c(3, 3.5, 4)))

# summarize model fit with tidiers
tidy(marg_ie2)

```

tidy.Mclust

Tidy a(n) Mclust object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'Mclust'
tidy(x, ...)

```

Arguments

- | | |
|-----|---|
| x | An Mclust object return from <code>mclust::Mclust()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with columns:

proportion	The mixing proportion of each component
size	Number of points assigned to cluster.
mean	The mean for each component. In case of 2+ dimensional models, a column with the mean is added for each dimension. NA for noise component
variance	In case of one-dimensional and spherical models, the variance for each component, omitted otherwise. NA for noise component
component	Cluster id as a factor.

See Also

`tidy()`, `mclust::Mclust()`

Other mclust tidiers: `augment.Mclust()`

Examples

```
# load library for models and data
library(mclust)

# load data manipulation libraries
library(dplyr)
library(tibble)
library(purrr)
library(tidyr)

set.seed(27)

centers <- tibble(
  cluster = factor(1:3),
  # number points in each cluster
  num_points = c(100, 150, 50),
  # x1 coordinate of cluster center
  x1 = c(5, 0, -3),
  # x2 coordinate of cluster center
  x2 = c(-1, 1, -2)
)

points <- centers %>%
  mutate(
    x1 = map2(num_points, x1, rnorm),
    x2 = map2(num_points, x2, rnorm)
  ) %>%
  select(-num_points, -cluster) %>%
  unnest(c(x1, x2))

# fit model
```

```

m <- Mclust(points)

# summarize model fit with tidiers
tidy(m)
augment(m, points)
glance(m)

```

tidy.mediate	<i>Tidy a(n) mediate object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'mediate'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

```

Arguments

x	A mediate object produced by a call to <code>mediation::mediate()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The tibble has four rows. The first two indicate the mediated effect in the control and treatment groups, respectively. And the last two the direct effect in each group.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `mediation::mediate()`

Examples

```
# load libraries for models and data
library(mediation)

data(jobs)

# fit models
b <- lm(job_seek ~ treat + econ_hard + sex + age, data = jobs)
c <- lm(depress2 ~ treat + job_seek + econ_hard + sex + age, data = jobs)
mod <- mediate(b, c, sims = 50, treat = "treat", mediator = "job_seek")

# summarize model fit with tidiers
tidy(mod)
tidy(mod, conf.int = TRUE)
tidy(mod, conf.int = TRUE, conf.level = .99)
```

tidy.mfx

Tidy a(n) mfx object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

The particular functions below provide generic tidy methods for objects returned by the `mfx` package, preserving the calculated marginal effects instead of the naive model coefficients. The returned tidy tibble will also include an additional "atmean" column indicating how the marginal effects were originally calculated (see Details below).

Usage

```
## S3 method for class 'mfx'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

## S3 method for class 'logitmfx'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

## S3 method for class 'negbinmfx'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

## S3 method for class 'poissonmfx'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

## S3 method for class 'probitmfx'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	A <code>logitmfx</code> , <code>negbinmfx</code> , <code>poissonmfx</code> , or <code>probitmfx</code> object. (Note that <code>betamfx</code> objects receive their own set of tidiers.)
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The `mfx` package provides methods for calculating marginal effects for various generalized linear models (GLMs). Unlike standard linear models, estimated model coefficients in a GLM cannot be directly interpreted as marginal effects (i.e., the change in the response variable predicted after a one unit change in one of the regressors). This is because the estimated coefficients are multiplicative, dependent on both the link function that was used for the estimation and any other variables that were included in the model. When calculating marginal effects, users must typically choose whether they want to use i) the average observation in the data, or ii) the average of the sample marginal effects. See `vignette("mfxarticle")` from the `mfx` package for more details.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>atmean</code>	TRUE if the marginal effects were originally calculated as the partial effects for the average observation. If FALSE, then these were instead calculated as average partial effects.

See Also

`tidy()`, `mfx::logitmfx()`, `mfx::negbinmfx()`, `mfx::poissonmfx()`, `mfx::probitmfx()`

Other mfx tidiers: `augment.betamfx()`, `augment.mfx()`, `glance.betamfx()`, `glance.mfx()`, `tidy.betamfx()`

Examples

```
# load libraries for models and data
library(mfx)

# get the marginal effects from a logit regression
mod_logmfx <- logitmfx(am ~ cyl + hp + wt, atmean = TRUE, data = mtcars)

tidy(mod_logmfx, conf.int = TRUE)

# compare with the naive model coefficients of the same logit call
tidy(
  glm(am ~ cyl + hp + wt, family = binomial, data = mtcars), conf.int = TRUE
)

augment(mod_logmfx)
glance(mod_logmfx)

# another example, this time using probit regression
mod_probmfx <- probitmfx(am ~ cyl + hp + wt, atmean = TRUE, data = mtcars)

tidy(mod_probmfx, conf.int = TRUE)
augment(mod_probmfx)
glance(mod_probmfx)
```

tidy.mjoint

*Tidy a(n) mjoint object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'mjoint'
tidy(
  x,
  component = "survival",
  conf.int = FALSE,
  conf.level = 0.95,
  boot_se = NULL,
  ...
)
```

Arguments

x	An mjoint object returned from <code>joineRML::mjoint()</code> .
component	Character specifying whether to tidy the survival or the longitudinal component of the model. Must be either "survival" or "longitudinal". Defaults to "survival".
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
boot_se	Optionally a bootSE object from <code>joineRML::bootSE()</code> . If specified, calculates confidence intervals via the bootstrap. Defaults to NULL, in which case standard errors are calculated from the empirical information matrix.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `joineRML::mjoint()`, `joineRML::bootSE()`

Other mjoint tidiers: `glance.mjoint()`

Examples

```
# broom only skips running these examples because the example models take a
# while to generatethey should run just fine, though!
## Not run:
```

```
# load libraries for models and data
library(joineRML)
```

```
# fit a joint model with bivariate longitudinal outcomes
data(heart.valve)
```

```
hvd <- heart.valve[!is.na(heart.valve$log.grad) &
  !is.na(heart.valve$log.lvmi) &
  heart.valve$num <= 50, ]
```

```
fit <- mjoint(
  formLongFixed = list(
    "grad" = log.grad ~ time + sex + hs,
    "lvmi" = log.lvmi ~ time + sex
  ),
  formLongRandom = list(
    "grad" = ~ 1 | num,
    "lvmi" = ~ time | num
  ),
  formSurv = Surv(fuyrs, status) ~ age,
  data = hvd,
  inits = list("gamma" = c(0.11, 1.51, 0.80)),
  timeVar = "time"
```

```

)

# extract the survival fixed effects
tidy(fit)

# extract the longitudinal fixed effects
tidy(fit, component = "longitudinal")

# extract the survival fixed effects with confidence intervals
tidy(fit, ci = TRUE)

# extract the survival fixed effects with confidence intervals based
# on bootstrapped standard errors
bSE <- bootSE(fit, nboot = 5, safe.boot = TRUE)
tidy(fit, boot_se = bSE, ci = TRUE)

# augment original data with fitted longitudinal values and residuals
hvd2 <- augment(fit)

# extract model statistics
glance(fit)

## End(Not run)

```

tidy.mle2

Tidy a(n) mle2 object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'mle2'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)

```

Arguments

x	An mle2 object created by a call to <code>bbmle::mle2()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

- ...
- Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `bbmle::mle2()`, `tidy_optim()`

Examples

```
# load libraries for models and data
library(bbmle)

# generate data
x <- 0:10
y <- c(26, 17, 13, 12, 20, 5, 9, 8, 5, 4, 8)
d <- data.frame(x, y)

# fit model
fit <- mle2(y ~ dpois(lambda = ymean),
  start = list(ymean = mean(y)), data = d
)

# summarize model fit with tidiers
tidy(fit)
```

tidy.mlm	<i>Tidy a(n) mlm object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'mlm'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	An mlm object created by <code>stats::lm()</code> with a matrix as the response.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

In contrast to `lm` object (simple linear model), tidy output for `mlm` (multiple linear model) objects contain an additional column response.

If you have missing values in your model data, you may need to refit the model with `na.action = na.exclude`.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.

estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[tidy\(\)](#)

Other lm tidiers: [augment.glm\(\)](#), [augment.lm\(\)](#), [glance.glm\(\)](#), [glance.lm\(\)](#), [glance.summary.lm\(\)](#), [glance.svyglm\(\)](#), [tidy.glm\(\)](#), [tidy.lm.beta\(\)](#), [tidy.lm\(\)](#), [tidy.summary.lm\(\)](#)

Examples

```
# fit model
mod <- lm(cbind(mpg, disp) ~ wt, mtcars)

# summarize model fit with tidiers
tidy(mod, conf.int = TRUE)
```

tidy.mlogit

Tidying methods for logit models

Description

These methods tidy the coefficients of mnl and nl models generated by the functions of the mlogit package.

Usage

```
## S3 method for class 'mlogit'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	an object returned from <code>mlogit::mlogit()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `mlogit::mlogit()`

Other mlogit tidiers: `augment.mlogit()`, `glance.mlogit()`

Examples

```
# load libraries for models and data
library(mlogit)

data("Fishing", package = "mlogit")
Fish <- dfix(Fishing, varying = 2:9, shape = "wide", choice = "mode")

# fit model
m <- mlogit(mode ~ price + catch | income, data = Fish)

# summarize model fit with tidiers
tidy(m)
augment(m)
glance(m)
```

tidy.muhas	<i>Tidy a(n) muhas object</i>
------------	-------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'muhas'
tidy(x, ...)
```

Arguments

x	A muhas object returned by <code>muhas::muhas()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

time	Point in time.
estimate	Estimated hazard rate.

See Also

`tidy()`, `muhas::muhas()`

Other muhas tidiers: `glance.muhas()`

Examples

```
# load libraries for models and data
library(muhas)
library(survival)
```

```
# fit model
x <- muhaz(ovarian$futime, ovarian$fustat)

# summarize model fit with tidiers
tidy(x)
glance(x)
```

tidy.multinom

Tidying methods for multinomial logistic regression models

Description

These methods tidy the coefficients of multinomial logistic regression models generated by `multinom` of the `nnet` package.

Usage

```
## S3 method for class 'multinom'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

<code>x</code>	A <code>multinom</code> object returned from <code>nnet::multinom()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>y.value</code>	The response level.

See Also

`tidy()`, `nnet::multinom()`

Other multinom tidiers: `glance.multinom()`

Examples

```
# load libraries for models and data
library(nnet)
library(MASS)

example(birthwt)

bwt.mu <- multinom(low ~ ., bwt)

tidy(bwt.mu)
glance(bwt.mu)

# or, for output from a multinomial logistic regression
fit.gear <- multinom(gear ~ mpg + factor(am), data = mtcars)
tidy(fit.gear)
glance(fit.gear)
```

`tidy.negbin`

Tidy a(n) negbin object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'negbin'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A <code>glm.nb</code> object returned by <code>MASS::glm.nb()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

See Also

[MASS::glm.nb\(\)](#)

Other `glm.nb` tidiers: [glance.negbin\(\)](#)

Examples

```
# load libraries for models and data
library(MASS)

# fit model
r <- glm.nb(Days ~ Sex/(Age + Eth*Lrn), data = quine)

# summarize model fit with tidiers
tidy(r)
glance(r)
```

tidy.nlrq	<i>Tidy a(n) nlrq object</i>
-----------	------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'nlrq'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A nlrq object returned from <code>quantreg::nlrq()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[tidy\(\)](#), [quantreg::nlrq\(\)](#)

Other quantreg tidiers: [augment.nlrq\(\)](#), [augment.rqs\(\)](#), [augment.rq\(\)](#), [glance.nlrq\(\)](#), [glance.rq\(\)](#), [tidy.rqs\(\)](#), [tidy.rq\(\)](#)

Examples

```
# load modeling library
library(quantreg)

# build artificial data with multiplicative error
set.seed(1)
dat <- NULL
dat$x <- rep(1:25, 20)
dat$y <- SSlogis(dat$x, 10, 12, 2) * rnorm(500, 1, 0.1)

# fit the median using nlrq
mod <- nlrq(y ~ SSlogis(x, Asym, mid, scal),
            data = dat, tau = 0.5, trace = TRUE)

# summarize model fit with tidiers
tidy(mod)
glance(mod)
augment(mod)
```

tidy.nls

Tidy a(n) nls object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'nls'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x An nls object returned from [stats::nls\(\)](#).

conf.int Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.

<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy`, `stats::nls()`, `stats::summary.nls()`

Other nls tidiers: `augment.nls()`, `glance.nls()`

Examples

```
# fit model
n <- nls(mpg ~ k * e^wt, data = mtcars, start = list(k = 1, e = 2))

# summarize model fit with tidiers + visualization
tidy(n)
augment(n)
glance(n)

library(ggplot2)

ggplot(augment(n), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))
```

```

newdata <- head(mtcars)
newdata$wt <- newdata$wt + 1

augment(n, newdata = newdata)

```

tidy.numeric

Tidy atomic vectors

Description

Vector tidiers are deprecated and will be removed from an upcoming release of broom.

Usage

```

## S3 method for class 'numeric'
tidy(x, ...)

## S3 method for class 'character'
tidy(x, ...)

## S3 method for class 'logical'
tidy(x, ...)

```

Arguments

x	An object of class "numeric", "integer", "character", or "logical". Most likely a named vector
...	Extra arguments (not used)

Details

Turn atomic vectors into data frames, where the names of the vector (if they exist) are a column and the values of the vector are a column.

See Also

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [data.frame_tidiers](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#)

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [data.frame_tidiers](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#)

Other deprecated: [bootstrap\(\)](#), [confint_tidy\(\)](#), [data.frame_tidiers](#), [finish_glance\(\)](#), [fix_data_frame\(\)](#), [summary_tidiers](#), [tidy.density\(\)](#), [tidy.dist\(\)](#), [tidy.ftable\(\)](#)

Examples

```
## Not run:
x <- 1:5
names(x) <- letters[1:5]
tidy(x)

## End(Not run)
```

tidy.orcutt

Tidy a(n) orcutt object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'orcutt'
tidy(x, ...)
```

Arguments

x	An orcutt object returned from <code>orcutt::cochrane.orcutt()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

[orcutt::cochrane.orcutt\(\)](#)

Other orcutt tidiers: [glance.orcutt\(\)](#)

Examples

```
# load libraries for models and data
library(orcutt)

# fit model and summarize results
reg <- lm(mpg ~ wt + qsec + disp, mtcars)
tidy(reg)

co <- cochrane.orcutt(reg)
tidy(co)
glance(co)
```

`tidy.pairwise.htest` *Tidy a(n) pairwise.htest object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'pairwise.htest'
tidy(x, ...)
```

Arguments

- | | |
|-----|---|
| x | A <code>pairwise.htest</code> object such as those returned from stats::pairwise.t.test() or stats::pairwise.wilcox.test() . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Details

Note that in one-sided tests, the alternative hypothesis of each test can be stated as "group1 is greater/less than group2".

Note also that the columns of group1 and group2 will always be a factor, even if the original input is (e.g.) numeric.

Value

A `tibble::tibble()` with columns:

group1	First group being compared.
group2	Second group being compared.
p.value	The two-sided p-value associated with the observed statistic.

See Also

`stats::pairwise.t.test()`, `stats::pairwise.wilcox.test()`, `tidy()`

Other htest tidiers: `augment.htest()`, `tidy.htest()`, `tidy.power.htest()`

Examples

```
attach(airquality)
Month <- factor(Month, labels = month.abb[5:9])
ptt <- pairwise.t.test(Ozone, Month)
tidy(ptt)

library(modeldata)
data(hpc_data)
attach(hpc_data)
ptt2 <- pairwise.t.test(compounds, class)
tidy(ptt2)

tidy(pairwise.t.test(compounds, class, alternative = "greater"))
tidy(pairwise.t.test(compounds, class, alternative = "less"))

tidy(pairwise.wilcox.test(compounds, class))
```

tidy.pam

Tidy a(n) pam object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'pam'
tidy(x, col.names = paste0("x", 1:ncol(x$medoids)), ...)
```

Arguments

<code>x</code>	An pam object returned from <code>cluster::pam()</code>
<code>col.names</code>	Column names in the input data frame. Defaults to the names of the variables in <code>x</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

For examples, see the pam vignette.

Value

A `tibble::tibble()` with columns:

<code>size</code>	Size of each cluster.
<code>max.diss</code>	Maximal dissimilarity between the observations in the cluster and that cluster's medoid.
<code>avg.diss</code>	Average dissimilarity between the observations in the cluster and that cluster's medoid.
<code>diameter</code>	Diameter of the cluster.
<code>separation</code>	Separation of the cluster.
<code>avg.width</code>	Average silhouette width of the cluster.
<code>cluster</code>	A factor describing the cluster from 1:k.

See Also

`tidy()`, `cluster::pam()`

Other pam tidiers: `augment.pam()`, `glance.pam()`

Examples

```
# load libraries for models and data
library(dplyr)
library(ggplot2)
library(cluster)
library(modeldata)
data(hpc_data)

x <- hpc_data[, 2:5]
p <- pam(x, k = 4)

# summarize model fit with tidiers + visualization
tidy(p)
glance(p)
augment(p, x)

augment(p, x) %>%
  ggplot(aes(compounds, input_fields)) +
  geom_point(aes(color = .cluster)) +
  geom_text(aes(label = cluster), data = tidy(p), size = 10)
```

tidy.plm

*Tidy a(n) plm object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'plm'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A plm object returned by <code>plm::plm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `plm::plm()`, `tidy.lm()`

Other plm tidiers: `augment.plm()`, `glance.plm()`

Examples

```
# load libraries for models and data
library(plm)

# load data
data("Produc", package = "plm")

# fit model
zz <- plm(log(gsp) ~ log(pcap) + log(pc) + log(emp) + unemp,
  data = Produc, index = c("state", "year")
)

# summarize model fit with tidiers
summary(zz)

tidy(zz)
tidy(zz, conf.int = TRUE)
```

```
tidy(zz, conf.int = TRUE, conf.level = 0.9)

augment(zz)
glance(zz)
```

tidy.poLCA

Tidy a(n) poLCA object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'poLCA'
tidy(x, ...)
```

Arguments

x	A poLCA object returned from <code>poLCA::poLCA()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

class	The class under consideration.
outcome	Outcome of manifest variable.
std.error	The standard error of the regression term.
variable	Manifest variable
estimate	Estimated class-conditional response probability

See Also

[tidy\(\)](#), [poLCA::poLCA\(\)](#)

Other poLCA tidiers: [augment.poLCA\(\)](#), [glance.poLCA\(\)](#)

Examples

```
# load libraries for models and data
library(poLCA)
library(dplyr)

# generate data
data(values)

f <- cbind(A, B, C, D) ~ 1

# fit model
M1 <- poLCA(f, values, nclass = 2, verbose = FALSE)

M1

# summarize model fit with tidiers + visualization
tidy(M1)
augment(M1)
glance(M1)

library(ggplot2)

ggplot(tidy(M1), aes(factor(class), estimate, fill = factor(outcome))) +
  geom_bar(stat = "identity", width = 1) +
  facet_wrap(~variable)

# three-class model with a single covariate.
data(election)

f2a <- cbind(
  MORALG, CARESG, KNOWG, LEADG, DISHONG, INTELG,
  MORALB, CARESB, KNOWB, LEADB, DISHONB, INTELB
) ~ PARTY

nes2a <- poLCA(f2a, election, nclass = 3, nrep = 5, verbose = FALSE)

td <- tidy(nes2a)
td

ggplot(td, aes(outcome, estimate, color = factor(class), group = class)) +
  geom_line() +
  facet_wrap(~variable, nrow = 2) +
  theme(axis.text.x = element_text(angle = 90, hjust = 1))

au <- augment(nes2a)
```

```

au

count(au, .class)

# if the original data is provided, it leads to NAs in new columns
# for rows that weren't predicted
au2 <- augment(nes2a, data = election)

au2

dim(au2)

```

tidy.polr

Tidy a(n) polr object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'polr'
tidy(
  x,
  conf.int = FALSE,
  conf.level = 0.95,
  exponentiate = FALSE,
  p.values = FALSE,
  ...
)

```

Arguments

x	A polr object returned from <code>MASS::polr()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.

p.values	Logical. Should p-values be returned, based on chi-squared tests from <code>MASS::dropterm()</code> . Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

In `broom 0.7.0` the `coefficient_type` column was renamed to `coef.type`, and the contents were changed as well. Now the contents are `coefficient` and `scale`, rather than `coefficient` and `zeta`.

Calculating p-values with the `dropterm()` function is the approach suggested by the `MASS` package author. This approach is computationally intensive so that p-values are only returned if requested explicitly. Additionally, it only works for models containing no variables with more than two categories. If this condition is not met, a message is shown and NA is returned instead of p-values.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy`, `MASS::polr()`

Other ordinal tidiers: `augment.clm()`, `augment.polr()`, `glance.clmm()`, `glance.clm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clmm()`, `tidy.clm()`, `tidy.svyolr()`

Examples

```
# load libraries for models and data
library(MASS)
```

```

# fit model
fit <- polr(Sat ~ Infl + Type + Cont, weights = Freq, data = housing)

# summarize model fit with tidiers
tidy(fit, exponentiate = TRUE, conf.int = TRUE)

glance(fit)
augment(fit, type.predict = "class")

fit2 <- polr(factor(gear) ~ am + mpg + qsec, data = mtcars)

tidy(fit, p.values = TRUE)

```

tidy.power.htest	<i>Tidy a(n) power.htest object</i>
------------------	-------------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'power.htest'
tidy(x, ...)

```

Arguments

x	A <code>power.htest</code> object such as those returned from <code>stats::power.t.test()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

delta	True difference in means.
-------	---------------------------

n	Number of observations by component.
power	Power achieved for given value of n.
sd	Standard deviation.
sig.level	Significance level (Type I error probability).

See Also

`stats::power.t.test()`

Other htest tidiers: `augment.htest()`, `tidy.htest()`, `tidy.pairwise.htest()`

Examples

```
ptt <- power.t.test(n = 2:30, delta = 1)
tidy(ptt)

library(ggplot2)

ggplot(tidy(ptt), aes(n, power)) +
  geom_line()
```

`tidy.prcomp`

Tidy a(n) prcomp object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'prcomp'
tidy(x, matrix = "u", ...)
```

Arguments

x	A prcomp object returned by <code>stats::prcomp()</code> .
matrix	Character specifying which component of the PCA should be tidied. <ul style="list-style-type: none"> • "u", "samples", "scores", or "x": returns information about the map from the original space into principle components space. • "v", "rotation", "loadings" or "variables": returns information about the map from principle components space back into the original space. • "d", "eigenvalues" or "pcs": returns information about the eigenvalues.

- ...
- Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

See <https://stats.stackexchange.com/questions/134282/relationship-between-svd-and-pca-how-to-use-svd-to-perform-pca> for information on how to interpret the various tidied matrices. Note that SVD is only equivalent to PCA on centered data.

Value

A `tibble::tibble` with columns depending on the component of PCA being tidied.

If `matrix` is "u", "samples", "scores", or "x" each row in the tidied output corresponds to the original data in PCA space. The columns are:

row	ID of the original observation (i.e. rowname from original data).
PC	Integer indicating a principal component.
value	The score of the observation for that particular principal component. That is, the location of the observation in PCA space.

If `matrix` is "v", "rotation", "loadings" or "variables", each row in the tidied output corresponds to information about the principle components in the original space. The columns are:

row	The variable labels (colnames) of the data set on which PCA was performed.
PC	An integer vector indicating the principal component.
value	The value of the eigenvector (axis score) on the indicated principal component.

If `matrix` is "d", "eigenvalues" or "pcs", the columns are:

PC	An integer vector indicating the principal component.
std.dev	Standard deviation explained by this PC.
percent	Fraction of variation explained by this component (a numeric value between 0 and 1).
cumulative	Cumulative fraction of variation explained by principle components up to this component (a numeric value between 0 and 1).

See Also

[stats::prcomp\(\)](#), [svd_tidiers](#)

Other svd tidiers: [augment.prcomp\(\)](#), [tidy_irlba\(\)](#), [tidy_svd\(\)](#)

Examples

```

pc <- prcomp(USArrests, scale = TRUE)

# information about rotation
tidy(pc)

# information about samples (states)
tidy(pc, "samples")

# information about PCs
tidy(pc, "pcs")

# state map
library(dplyr)
library(ggplot2)
library(maps)

pc %>%
  tidy(matrix = "samples") %>%
  mutate(region = tolower(row)) %>%
  inner_join(map_data("state"), by = "region") %>%
  ggplot(aes(long, lat, group = group, fill = value)) +
  geom_polygon() +
  facet_wrap(~PC) +
  theme_void() +
  ggtitle("Principal components of arrest data")

au <- augment(pc, data = USArrests)

au

ggplot(au, aes(.fittedPC1, .fittedPC2)) +
  geom_point() +
  geom_text(aes(label = .rownames), vjust = 1, hjust = 1)

```

tidy.pyears

Tidy a(n) pyears object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'pyears'
tidy(x, ...)
```

Arguments

`x` A pyears object returned from `survival::pyears()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

`expected` is only present in the output when if a `ratetable` term is present.

If the `data.frame = TRUE` argument is supplied to `pyears`, this is simply the contents of `x$data`.

Value

A `tibble::tibble()` with columns:

<code>expected</code>	Expected number of events.
<code>pyears</code>	Person-years of exposure.
<code>n</code>	number of subjects contributing time
<code>event</code>	observed number of events

See Also

`tidy()`, `survival::pyears()`

Other pyears tidiers: `glance.pyears()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)
```

```

# generate and format data
temp.yr <- tcut(mgus$dxyr, 55:92, labels = as.character(55:91))
temp.age <- tcut(mgus$age, 34:101, labels = as.character(34:100))
ptime <- ifelse(is.na(mgus$pctime), mgus$futime, mgus$pctime)
pstat <- ifelse(is.na(mgus$pctime), 0, 1)
pfit <- pyears(Surv(ptime / 365.25, pstat) ~ temp.yr + temp.age + sex, mgus,
  data.frame = TRUE
)

# summarize model fit with tidiers
tidy(pfit)
glance(pfit)

# if data.frame argument is not given, different information is present in
# output
pfit2 <- pyears(Surv(ptime / 365.25, pstat) ~ temp.yr + temp.age + sex, mgus)

tidy(pfit2)
glance(pfit2)

```

tidy.rcorr

Tidy a(n) rcorr object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'rcorr'
tidy(x, diagonal = FALSE, ...)

```

Arguments

x	An rcorr object returned from <code>Hmisc::rcorr()</code> .
diagonal	Logical indicating whether or not to include diagonal elements of the correlation matrix, or the correlation of a column with itself. For the elements, estimate is always 1 and p.value is always NA. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

Suppose the original data has columns A and B. In the correlation matrix from `rcorr` there may be entries for both the `cor(A, B)` and `cor(B, A)`. Only one of these pairs will ever be present in the tidy output.

Value

A `tibble::tibble()` with columns:

<code>column1</code>	Name or index of the first column being described.
<code>column2</code>	Name or index of the second column being described.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>n</code>	Number of observations used to compute the correlation

See Also

[tidy\(\)](#), [Hmisc::rcorr\(\)](#)

Examples

```
# load libraries for models and data
library(Hmisc)

mat <- replicate(52, rnorm(100))

# add some NAs
mat[sample(length(mat), 2000)] <- NA

# also, column names
colnames(mat) <- c(LETTERS, letters)

# fit model
rc <- rcorr(mat)

# summarize model fit with tidiers + visualization
td <- tidy(rc)
td

library(ggplot2)
ggplot(td, aes(p.value)) +
  geom_histogram(binwidth = .1)
```

```
ggplot(td, aes(estimate, p.value)) +
  geom_point() +
  scale_y_log10()
```

tidy.ref.grid	<i>Tidy a(n) ref.grid object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'ref.grid'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A ref.grid object created by emmeans::ref_grid() .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if conf.int = TRUE. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments passed to emmeans::summary.emmGrid() or lsmeans::summary.ref.grid() . Cautionary note: misspecified arguments may be silently ignored!

Details

Returns a data frame with one observation for each estimated marginal mean, and one column for each combination of factors. When the input is a contrast, each row will contain one estimated contrast.

There are a large number of arguments that can be passed on to [emmeans::summary.emmGrid\(\)](#) or [lsmeans::summary.ref.grid\(\)](#).

Value

A [tibble::tibble\(\)](#) with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.

df	Degrees of freedom used by this term in the model.
p.value	The two-sided p-value associated with the observed statistic.
std.error	The standard error of the regression term.
estimate	Expected marginal mean
statistic	T-ratio statistic

See Also

`tidy()`, `emmeans::ref_grid()`, `emmeans::emmeans()`, `emmeans::contrast()`
 Other emmeans tidiers: `tidy.emmGrid()`, `tidy.lsmobj()`, `tidy.summary_emm()`

Examples

```
# load libraries for models and data
library(emmeans)

# linear model for sales of oranges per day
oranges_lm1 <- lm(sales1 ~ price1 + price2 + day + store, data = oranges)

# reference grid; see vignette("basics", package = "emmeans")
oranges_rg1 <- ref_grid(oranges_lm1)
td <- tidy(oranges_rg1)
td

# marginal averages
marginal <- emmeans(oranges_rg1, "day")
tidy(marginal)

# contrasts
tidy(contrast(marginal))
tidy(contrast(marginal, method = "pairwise"))

# plot confidence intervals
library(ggplot2)

ggplot(tidy(marginal, conf.int = TRUE), aes(day, estimate)) +
  geom_point() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# by multiple prices
by_price <- emmeans(oranges_lm1, "day",
  by = "price2",
  at = list(
    price1 = 50, price2 = c(40, 60, 80),
    day = c("2", "3", "4")
  )
)
by_price
```

```

tidy(by_price)

ggplot(tidy(by_price, conf.int = TRUE), aes(price2, estimate, color = day)) +
  geom_line() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# joint_tests
tidy(joint_tests(oranges_lm1))

```

tidy.regsbsets	<i>Tidy a(n) regssets object</i>
----------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'regssets'
tidy(x, ...)

```

Arguments

x	A regssets object created by <code>leaps::regssets()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

r.squared	R squared statistic, or the percent of variation explained by the model.
adj.r.squared	Adjusted R squared statistic
BIC	Bayesian information criterion for the component.
mallows_cp	Mallow's Cp statistic.

See Also

[tidy\(\)](#), [leaps::regsubsets\(\)](#)

Examples

```
# load libraries for models and data
library(leaps)

# fit model
all_fits <- regsubsets(hp ~ ., mtcars)

# summarize model fit with tidiers
tidy(all_fits)
```

tidy.ridgelm	<i>Tidy a(n) ridgelm object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'ridgelm'
tidy(x, ...)
```

Arguments

x	A <code>ridgelm</code> object returned from MASS::lm.ridge() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

GCV	Generalized cross validation error estimate.
lambda	Value of penalty parameter lambda.
term	The name of the regression term.
estimate	estimate of scaled coefficient using this lambda
scale	Scaling factor of estimated coefficient

See Also

`tidy()`, `MASS::lm.ridge()`

Other `ridgelm` tidiers: `glance.ridgelm()`

Examples

```
# load libraries for models and data
library(MASS)

names(longley)[1] <- "y"

# fit model and summarize results
fit1 <- lm.ridge(y ~ ., longley)
tidy(fit1)

fit2 <- lm.ridge(y ~ ., longley, lambda = seq(0.001, .05, .001))
td2 <- tidy(fit2)
g2 <- glance(fit2)

# coefficient plot
library(ggplot2)
ggplot(td2, aes(lambda, estimate, color = term)) +
  geom_line()

# GCV plot
ggplot(td2, aes(lambda, GCV)) +
  geom_line()

# add line for the GCV minimizing estimate
ggplot(td2, aes(lambda, GCV)) +
  geom_line() +
  geom_vline(xintercept = g2$lambdaGCV, col = "red", lty = 2)
```

tidy.rlm	<i>Tidy a(n) rlm object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'rlm'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	An rlm object returned by MASS::rlm() .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if conf.int = TRUE. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass conf.level = 0.9, all computation will proceed using conf.level = 0.95. Two exceptions here are: <ul style="list-style-type: none"> • tidy() methods will warn when supplied an exponentiate argument if it will be ignored. • augment() methods will warn when supplied a newdata argument if it will be ignored.

See Also

[MASS::rlm\(\)](#)

Other rlm tidiers: [augment.rlm\(\)](#), [glance.rlm\(\)](#)

tidy.rma	<i>Tidy a(n) rma object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'rma'
tidy(
  x,
  conf.int = FALSE,
  conf.level = 0.95,
  exponentiate = FALSE,
  include_studies = FALSE,
  measure = "GEN",
  ...
)
```

Arguments

x	An rma object such as those created by <code>metafor::rma()</code> , <code>metafor::rma.uni()</code> , <code>metafor::rma.glmm()</code> , <code>metafor::rma.mh()</code> , <code>metafor::rma.mv()</code> , or <code>metafor::rma.peto()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
include_studies	Logical. Should individual studies be included in the output? Defaults to FALSE.
measure	Measure type. See <code>metafor::escalc()</code>
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored.

- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the individual study
<code>type</code>	The estimate type (summary vs individual study)

Examples

```
# load libraries for models and data
library(metafor)

df <-
  escalc(
    measure = "RR",
    ai = tpos,
    bi = tneg,
    ci = cpos,
    di = cneg,
    data = dat.bcg
  )

meta_analysis <- rma(yi, vi, data = df, method = "EB")

tidy(meta_analysis)
```

tidy.roc

Tidy a(n) roc object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'roc'
tidy(x, ...)
```

Arguments

`x` An roc object returned from a call to `AUC::roc()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>cutoff</code>	The cutoff used for classification. Observations with predicted probabilities above this value were assigned class 1, and observations with predicted probabilities below this value were assigned class 0.
<code>fpr</code>	False positive rate.
<code>tpr</code>	The true positive rate at the given cutoff.

See Also

`tidy()`, `AUC::roc()`

Examples

```
# load libraries for models and data
library(AUC)

# load data
data(churn)

# fit model
r <- roc(churn$predictions, churn$labels)

# summarize with tidiers + visualization
td <- tidy(r)
td

library(ggplot2)
```

```

ggplot(td, aes(fpr, tpr)) +
  geom_line()

# compare the ROC curves for two prediction algorithms
library(dplyr)
library(tidyr)

rocs <- churn %>%
  pivot_longer(contains("predictions"),
    names_to = "algorithm",
    values_to = "value"
  ) %>%
  nest(data = -algorithm) %>%
  mutate(tidy_roc = purrr::map(data, ~ tidy(roc(.x$value, .x$labels)))) %>%
  unnest(tidy_roc)

ggplot(rocs, aes(fpr, tpr, color = algorithm)) +
  geom_line()

```

tidy.rq

Tidy a(n) rq object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'rq'
tidy(x, se.type = NULL, conf.int = FALSE, conf.level = 0.95, ...)

```

Arguments

<code>x</code>	An <code>rq</code> object returned from <code>quantreg::rq()</code> .
<code>se.type</code>	Character specifying the method to use to calculate standard errors. Passed to <code>quantreg::summary.rq()</code> <code>se</code> argument. Defaults to "rank" if the sample size is less than 1000, otherwise defaults to "nid".
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments passed to <code>quantreg::summary.rq()</code> .

Details

If `se.type = "rank"` confidence intervals are calculated by `summary.rq` and `statistic` and `p.value` values are not returned. When only a single predictor is included in the model, no confidence intervals are calculated and the confidence limits are set to NA.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

[tidy\(\)](#), [quantreg::rq\(\)](#)

Other `quantreg` tidiers: [augment.nlrq\(\)](#), [augment.rqs\(\)](#), [augment.rq\(\)](#), [glance.nlrq\(\)](#), [glance.rq\(\)](#), [tidy.nlrq\(\)](#), [tidy.rqs\(\)](#)

Examples

```
# load modeling library and data
library(quantreg)

data(stackloss)

# median (l1) regression fit for the stackloss data.
mod1 <- rq(stack.loss ~ stack.x, .5)

# weighted sample median
mod2 <- rq(rnorm(50) ~ 1, weights = runif(50))

# summarize model fit with tidiers
tidy(mod1)
glance(mod1)
augment(mod1)

tidy(mod2)
glance(mod2)
augment(mod2)

# varying tau to generate an rqs object
```



```

mod3 <- rq(stack.loss ~ stack.x, tau = c(.25, .5))

tidy(mod3)
augment(mod3)

# glance cannot handle rqs objects like `mod3`--use a purrr
# `map`-based workflow instead

```

tidy.rqs

Tidy a(n) rqs object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'rqs'
tidy(x, se.type = "rank", conf.int = FALSE, conf.level = 0.95, ...)

```

Arguments

x	An rqs object returned from <code>quantreg::rq()</code> .
se.type	Character specifying the method to use to calculate standard errors. Passed to <code>quantreg::summary.rq()</code> se argument. Defaults to "rank".
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments passed to <code>quantreg::summary.rqs()</code>

Details

If `se.type = "rank"` confidence intervals are calculated by `summary.rq`. When only a single predictor is included in the model, no confidence intervals are calculated and the confidence limits are set to NA.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>quantile</code>	Linear conditional quantile.

See Also

`tidy()`, `quantreg::rq()`

Other `quantreg` tidiers: `augment.nlrq()`, `augment.rqs()`, `augment.rq()`, `glance.nlrq()`, `glance.rq()`, `tidy.nlrq()`, `tidy.rq()`

Examples

```
# load modeling library and data
library(quantreg)

data(stackloss)

# median (l1) regression fit for the stackloss data.
mod1 <- rq(stack.loss ~ stack.x, .5)

# weighted sample median
mod2 <- rq(rnorm(50) ~ 1, weights = runif(50))

# summarize model fit with tidiers
tidy(mod1)
glance(mod1)
augment(mod1)

tidy(mod2)
glance(mod2)
augment(mod2)

# varying tau to generate an rqs object
mod3 <- rq(stack.loss ~ stack.x, tau = c(.25, .5))

tidy(mod3)
augment(mod3)
```

```
# glance cannot handle rqs objects like `mod3`--use a purrr
# `map`-based workflow instead
```

tidy.sarlm

*Tidying methods for spatially autoregressive models***Description**

These methods tidy the coefficients of spatial autoregression models generated by functions in the `spatialreg` package.

Usage

```
## S3 method for class 'sarlm'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	An object returned from <code>spatialreg::lagsarlm()</code> or <code>spatialreg::errorsarlm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

[tidy\(\)](#), [spatialreg::lagsarlm\(\)](#), [spatialreg::errorsarlm\(\)](#), [spatialreg::sacsarlm\(\)](#)

Other spatialreg tidiers: [augment.sarlm\(\)](#), [glance.sarlm\(\)](#)

Examples

```
# load libraries for models and data
library(spatialreg)
library(spdep)

# load data
data(oldcol, package = "spdep")

listw <- nb2listw(COL.nb, style = "W")

# fit model
crime_sar <-
lagsarlm(CRIME ~ INC + HOVAL,
         data = COL.OLD,
         listw = listw,
         method = "eigen")

# summarize model fit with tidiers
tidy(crime_sar)
tidy(crime_sar, conf.int = TRUE)
glance(crime_sar)
augment(crime_sar)

# fit another model
crime_sem <- errorsarlm(CRIME ~ INC + HOVAL, data = COL.OLD, listw)

# summarize model fit with tidiers
tidy(crime_sem)
tidy(crime_sem, conf.int = TRUE)
glance(crime_sem)
augment(crime_sem)

# fit another model
crime_sac <- sacsarlm(CRIME ~ INC + HOVAL, data = COL.OLD, listw)

# summarize model fit with tidiers
tidy(crime_sac)
tidy(crime_sac, conf.int = TRUE)
glance(crime_sac)
augment(crime_sac)
```

tidy.spec	<i>Tidy a(n) spec object</i>
-----------	------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'spec'
tidy(x, ...)
```

Arguments

x	A spec object created by <code>stats::spectrum()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

freq	Vector of frequencies at which the spectral density is estimated.
spec	Vector (for univariate series) or matrix (for multivariate series) of estimates of the spectral density at frequencies corresponding to freq.

See Also

`tidy()`, `stats::spectrum()`

Other time series tidiers: `tidy.acf()`, `tidy.ts()`, `tidy.zoo()`

Examples

```

spc <- spectrum(lh)
tidy(spc)

library(ggplot2)
ggplot(tidy(spc), aes(freq, spec)) +
  geom_line()

```

tidy.speedglm

Tidy a(n) speedglm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'speedglm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)

```

Arguments

x	A speedglm object returned from <code>speedglm::speedglm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`speedglm::speedglm()`

Other speedlm tidiers: `augment.speedlm()`, `glance.speedglm()`, `glance.speedlm()`, `tidy.speedlm()`

Examples

```
# load libraries for models and data
library(speedglm)

# generate data
clotting <- data.frame(
  u = c(5, 10, 15, 20, 30, 40, 60, 80, 100),
  lot1 = c(118, 58, 42, 35, 27, 25, 21, 19, 18)
)

# fit model
fit <- speedglm(lot1 ~ log(u), data = clotting, family = Gamma(log))

# summarize model fit with tidiers
tidy(fit)
glance(fit)
```

`tidy.speedlm`

Tidy a(n) speedlm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'speedlm'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	A <code>speedlm</code> object returned from <code>speedglm::speedlm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`speedglm::speedlm()`, `tidy.lm()`

Other `speedlm` tidiers: `augment.speedlm()`, `glance.speedglm()`, `glance.speedlm()`, `tidy.speedglm()`

Examples

```
# load modeling library
library(speedglm)
```



```
# fit model
mod <- speedlm(mpg ~ wt + qsec, data = mtcars, fitted = TRUE)

# summarize model fit with tidiers
tidy(mod)
glance(mod)
augment(mod)
```

tidy.summary.glht *Tidy a(n) summary.glht object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'summary.glht'
tidy(x, ...)
```

Arguments

x	A <code>summary.glht</code> object created by calling <code>multcomp::summary.glht()</code> on a <code>glht</code> object created with <code>multcomp::glht()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

contrast	Levels being compared.
estimate	The estimated value of the regression term.
null.value	Value to which the estimate is compared.
p.value	The two-sided p-value associated with the observed statistic.

statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.

See Also

[tidy\(\)](#), [multcomp::summary.glht\(\)](#), [multcomp::glht\(\)](#)

Other multcomp tidiers: [tidy.cld\(\)](#), [tidy.confint.glht\(\)](#), [tidy.glht\(\)](#)

Examples

```
# load libraries for models and data
library(multcomp)
library(ggplot2)

amod <- aov(breaks ~ wool + tension, data = warpbreaks)
wht <- glht(amod, linfct = mcp(tension = "Tukey"))

tidy(wht)

ggplot(wht, aes(lhs, estimate)) +
  geom_point()

CI <- confint(wht)

tidy(CI)

ggplot(CI, aes(lhs, estimate, ymin = lwr, ymax = upr)) +
  geom_pointrange()

tidy(summary(wht))
ggplot(mapping = aes(lhs, estimate)) +
  geom_linerange(aes(ymin = lwr, ymax = upr), data = CI) +
  geom_point(aes(size = p), data = summary(wht)) +
  scale_size(trans = "reverse")

cld <- cld(wht)
tidy(cld)
```

tidy.summary.lm

Tidy a(n) summary.lm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'summary.lm'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A <code>summary.lm</code> object created by <code>stats::summary.lm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The `tidy.summary.lm()` method is a potentially useful alternative to `tidy.lm()`. For instance, if users have already converted large `lm` objects into their leaner `summary.lm` equivalents to conserve memory.

Value

A `tibble::tibble()` with columns:

conf.high	Upper bound on the confidence interval for the estimate.
conf.low	Lower bound on the confidence interval for the estimate.
estimate	The estimated value of the regression term.
p.value	The two-sided p-value associated with the observed statistic.
statistic	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
std.error	The standard error of the regression term.
term	The name of the regression term.

See Also

`tidy()`, `stats::summary.lm()`

Other `lm` tidiers: `augment.glm()`, `augment.lm()`, `glance.glm()`, `glance.lm()`, `glance.summary.lm()`, `glance.svyglm()`, `tidy.glm()`, `tidy.lm.beta()`, `tidy.lm()`, `tidy.mlml()`

Examples

```
# fit model
mod <- lm(mpg ~ wt + qsec, data = mtcars)
modsumm <- summary(mod)

# summarize model fit with tidiers
tidy(mod, conf.int = TRUE)

# equivalent to the above
tidy(modsumm, conf.int = TRUE)

glance(mod)

# mostly the same, except for a few missing columns
glance(modsumm)
```

tidy.summary_emm	<i>Tidy a(n) summary_emm object</i>
------------------	-------------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'summary_emm'
tidy(x, null.value = NULL, ...)
```

Arguments

x	A summary_emm object.
null.value	Value to which estimate is compared.
...	Additional arguments passed to <code>emmeans::summary.emmGrid()</code> or <code>lsmeans::summary.ref.grid()</code> . Cautionary note: misspecified arguments may be silently ignored!

Details

Returns a data frame with one observation for each estimated marginal mean, and one column for each combination of factors. When the input is a contrast, each row will contain one estimated contrast.

There are a large number of arguments that can be passed on to `emmeans::summary.emmGrid()` or `lsmeans::summary.ref.grid()`.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>contrast</code>	Levels being compared.
<code>den.df</code>	Degrees of freedom of the denominator.
<code>df</code>	Degrees of freedom used by this term in the model.
<code>null.value</code>	Value to which the estimate is compared.
<code>num.df</code>	Degrees of freedom.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>std.error</code>	The standard error of the regression term.
<code>level1</code>	One level of the factor being contrasted
<code>level2</code>	The other level of the factor being contrasted
<code>term</code>	Model term in joint tests
<code>estimate</code>	Expected marginal mean
<code>statistic</code>	T-ratio statistic or F-ratio statistic

See Also

`tidy()`, `emmeans::ref_grid()`, `emmeans::emmeans()`, `emmeans::contrast()`

Other emmeans tidiers: `tidy.emmGrid()`, `tidy.lsmobj()`, `tidy.ref.grid()`

Examples

```
# load libraries for models and data
library(emmeans)

# linear model for sales of oranges per day
oranges_lm1 <- lm(sales1 ~ price1 + price2 + day + store, data = oranges)

# reference grid; see vignette("basics", package = "emmeans")
oranges_rg1 <- ref_grid(oranges_lm1)
td <- tidy(oranges_rg1)
td

# marginal averages
marginal <- emmeans(oranges_rg1, "day")
tidy(marginal)

# contrasts
tidy(contrast(marginal))
tidy(contrast(marginal, method = "pairwise"))
```

```

# plot confidence intervals
library(ggplot2)

ggplot(tidy(marginal, conf.int = TRUE), aes(day, estimate)) +
  geom_point() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# by multiple prices
by_price <- emmeans(oranges_lm1, "day",
  by = "price2",
  at = list(
    price1 = 50, price2 = c(40, 60, 80),
    day = c("2", "3", "4")
  )
)

by_price

tidy(by_price)

ggplot(tidy(by_price, conf.int = TRUE), aes(price2, estimate, color = day)) +
  geom_line() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

# joint_tests
tidy(joint_tests(oranges_lm1))

```

tidy.survdiff

Tidy a(n) survdiff object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'survdiff'
tidy(x, ...)
```

Arguments

x An survdiff object returned from `survival::survdiff()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be

used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>exp</code>	Weighted expected number of events in each group.
<code>N</code>	Number of subjects in each group.
<code>obs</code>	weighted observed number of events in each group.

See Also

[tidy\(\)](#), [survival::survdiff\(\)](#)

Other `survdiff` tidiers: [glance.survdiff\(\)](#)

Other survival tidiers: [augment.coxph\(\)](#), [augment.survreg\(\)](#), [glance.aareg\(\)](#), [glance.cch\(\)](#), [glance.coxph\(\)](#), [glance.pyears\(\)](#), [glance.survdiff\(\)](#), [glance.survexp\(\)](#), [glance.survfit\(\)](#), [glance.survreg\(\)](#), [tidy.aareg\(\)](#), [tidy.cch\(\)](#), [tidy.coxph\(\)](#), [tidy.pyears\(\)](#), [tidy.survexp\(\)](#), [tidy.survfit\(\)](#), [tidy.survreg\(\)](#)

Examples

```
# load libraries for models and data
library(survival)

# fit model
s <- survdiff(
  Surv(time, status) ~ pat.karno + strata(inst),
  data = lung
)

# summarize model fit with tidiers
tidy(s)
glance(s)
```

tidy.survexp

*Tidy a(n) survexp object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'survexp'
tidy(x, ...)
```

Arguments

x	An survexp object returned from <code>survival::survexp()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

n.risk	Number of individuals at risk at time zero.
time	Point in time.
estimate	Estimate survival

See Also

`tidy()`, `survival::survexp()`

Other survexp tidiers: `glance.survexp()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survfit()`, `tidy.survreg()`

Examples

```
# load libraries for models and data
library(survival)

# fit model
sexpfit <- survexp(
  futime ~ 1,
  rmap = list(
    sex = "male",
    year = accept.dt,
    age = (accept.dt - birth.dt)
  ),
  method = "conditional",
  data = jasa
)

# summarize model fit with tidiers
tidy(sexpfit)
glance(sexpfit)
```

tidy.survfit

Tidy a(n) survfit object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'survfit'
tidy(x, ...)
```

Arguments

- | | |
|-----|--|
| x | An survfit object returned from <code>survival::survfit()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. |

- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>n.censor</code>	Number of censored events.
<code>n.event</code>	Number of events at time <code>t</code> .
<code>n.risk</code>	Number of individuals at risk at time zero.
<code>std.error</code>	The standard error of the regression term.
<code>time</code>	Point in time.
<code>estimate</code>	estimate of survival or cumulative incidence rate when multistate
<code>state</code>	state if multistate survfit object input
<code>strata</code>	strata if stratified survfit object input

See Also

[tidy\(\)](#), [survival::survfit\(\)](#)

Other survival tidiers: [augment.coxph\(\)](#), [augment.survreg\(\)](#), [glance.aareg\(\)](#), [glance.cch\(\)](#), [glance.coxph\(\)](#), [glance.pyears\(\)](#), [glance.survdiff\(\)](#), [glance.survexp\(\)](#), [glance.survfit\(\)](#), [glance.survreg\(\)](#), [tidy.aareg\(\)](#), [tidy.cch\(\)](#), [tidy.coxph\(\)](#), [tidy.pyears\(\)](#), [tidy.survdiff\(\)](#), [tidy.survexp\(\)](#), [tidy.survreg\(\)](#)

Examples

```
# load libraries for models and data
library(survival)

# fit model
cfits <- coxph(Surv(time, status) ~ age + sex, lung)
sfit <- survfit(cfits)

# summarize model fit with tidiers + visualization
tidy(sfit)
glance(sfit)

library(ggplot2)

ggplot(tidy(sfit), aes(time, estimate)) +
  geom_line() +
  geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)

# multi-state
```

```

fitCI <- survfit(Surv(stop, status * as.numeric(event), type = "mstate") ~ 1,
  data = mgus1, subset = (start == 0)
)

td_multi <- tidy(fitCI)

td_multi

ggplot(td_multi, aes(time, estimate, group = state)) +
  geom_line(aes(color = state)) +
  geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)

```

tidy.survreg

Tidy a(n) survreg object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'survreg'
tidy(x, conf.level = 0.95, conf.int = FALSE, ...)

```

Arguments

<code>x</code>	An survreg object returned from <code>survival::survreg()</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `survival::survreg()`

Other survreg tidiers: `augment.survreg()`, `glance.survreg()`

Other survival tidiers: `augment.coxph()`, `augment.survreg()`, `glance.aareg()`, `glance.cch()`, `glance.coxph()`, `glance.pyears()`, `glance.survdiff()`, `glance.survexp()`, `glance.survfit()`, `glance.survreg()`, `tidy.aareg()`, `tidy.cch()`, `tidy.coxph()`, `tidy.pyears()`, `tidy.survdiff()`, `tidy.survexp()`, `tidy.survfit()`

Examples

```
# load libraries for models and data
library(survival)

# fit model
sr <- survreg(
  Surv(futime, fustat) ~ ecog.ps + rx,
  ovarian,
  dist = "exponential"
)

# summarize model fit with tidiers + visualization
tidy(sr)
augment(sr, ovarian)
glance(sr)

# coefficient plot
td <- tidy(sr, conf.int = TRUE)

library(ggplot2)

ggplot(td, aes(estimate, term)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high), height = 0) +
```

```
geom_vline(xintercept = 0)
```

tidy.svyglm	<i>Tidy a(n) svyglm object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'svyglm'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A svyglm object returned from <code>survey::svyglm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

See Also

`survey::svyglm()`, `stats::glm()`

tidy.svyolr

Tidy a(n) svyolr object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'svyolr'
tidy(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A svyolr object returned from <code>survey::svyolr()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The `tidy.svyolr()` tidier is a light wrapper around `tidy.polr()`. However, the implementation for p-value calculation in `tidy.polr()` is both computationally intensive and specific to that model, so the `p.values` argument to `tidy.svyolr()` is currently ignored, and will raise a warning when passed.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy`, `survey::svyolr()`

Other ordinal tidiers: `augment.clm()`, `augment.polr()`, `glance.clmm()`, `glance.clm()`, `glance.polr()`, `glance.svyolr()`, `tidy.clmm()`, `tidy.clm()`, `tidy.polr()`

Examples

```
library(broom)
library(survey)

data(api)
dclus1 <- svydesign(id = ~dnum, weights = ~pw, data = apiclus1, fpc = ~fpc)
dclus1 <- update(dclus1, mealcat = cut(meals, c(0, 25, 50, 75, 100)))

m <- svyolr(mealcat ~ avg.ed + mobility + stype, design = dclus1)

m

tidy(m, conf.int = TRUE)
```

`tidy.systemfit`

Tidy a(n) systemfit object

Description

`tidy` summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what `tidy` considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'systemfit'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	A <code>systemfit</code> object produced by a call to <code>systemfit::systemfit()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

This tidy method works with any model objects of class `systemfit`. Default returns a tibble of six columns.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.

See Also

`tidy()`, `systemfit::systemfit()`

Examples

```

set.seed(27)

# load libraries for models and data
library(systemfit)

# generate data
df <- data.frame(
  X = rnorm(100),
  Y = rnorm(100),
  Z = rnorm(100),
  W = rnorm(100)
)

# fit model
fit <- systemfit(formula = list(Y ~ Z, W ~ X), data = df, method = "SUR")

# summarize model fit with tidiers
tidy(fit)
tidy(fit, conf.int = TRUE)

```

tidy.table

Tidy a(n) table object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Deprecated. Please use `tibble::as_tibble()` instead.

Usage

```

## S3 method for class 'table'
tidy(x, ...)

```

Arguments

`x` A `base::table` object.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Details

Directly calls `tibble::as_tibble()` on a `base::table` object.

Value

A `tibble::tibble` in long-form containing frequency information for the table in a `Freq` column. The result is much like what you get from `tidyr::pivot_longer()`.

See Also

`tibble::as_tibble.table()`

tidy.ts

Tidy a(n) ts object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'ts'
tidy(x, ...)
```

Arguments

- | | |
|------------------|---|
| <code>x</code> | A univariate or multivariate <code>ts</code> times series object. |
| <code>...</code> | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Details

series column is only present for multivariate ts objects.

Value

A `tibble::tibble()` with columns:

index	Index (i.e. date or time) for a 'ts' or 'zoo' object.
series	Name of the series (present only for multivariate time series).
value	The value/estimate of the component. Results from data reshaping.

See Also

`tidy()`, `stats::ts()`

Other time series tidiers: `tidy.acf()`, `tidy.spec()`, `tidy.zoo()`

Examples

```
set.seed(678)

tidy(ts(1:10, frequency = 4, start = c(1959, 2)))

z <- ts(matrix(rnorm(300), 100, 3), start = c(1961, 1), frequency = 12)
colnames(z) <- c("Aa", "Bb", "Cc")

tidy(z)
```

tidy.TukeyHSD	<i>Tidy a(n) TukeyHSD object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'TukeyHSD'
tidy(x, ...)
```

Arguments

- `x` A TukeyHSD object return from `stats::TukeyHSD()`.
- `...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:
- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
 - `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>adj.p.value</code>	P-value adjusted for multiple comparisons.
<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>contrast</code>	Levels being compared.
<code>estimate</code>	The estimated value of the regression term.
<code>null.value</code>	Value to which the estimate is compared.
<code>term</code>	The name of the regression term.

See Also

[tidy\(\)](#), [stats::TukeyHSD\(\)](#)

Other anova tidiers: [glance.anova\(\)](#), [glance.aov\(\)](#), [tidy.anova\(\)](#), [tidy.aovlist\(\)](#), [tidy.aov\(\)](#), [tidy.manova\(\)](#)

Examples

```
fm1 <- aov(breaks ~ wool + tension, data = warpbreaks)
thsd <- TukeyHSD(fm1, "tension", ordered = TRUE)
tidy(thsd)

# may include comparisons on multiple terms
fm2 <- aov(mpg ~ as.factor(gear) * as.factor(cyl), data = mtcars)
tidy(TukeyHSD(fm2))
```

tidy.varest	<i>Tidy a(n) varest object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'varest'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A varest object produced by a call to <code>vars::VAR()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

The tibble has one row for each term in the regression. The component column indicates whether a particular term was used to model either the "mean" or "precision". Here the precision is the inverse of the variance, often referred to as ϕ . At least one term will have been used to model the precision ϕ .

The vars package does not include a `confint` method and does not report confidence intervals for varest objects. Setting the tidy argument `conf.int = TRUE` will return a warning.

Value

A `tibble::tibble()` with columns:

<code>conf.high</code>	Upper bound on the confidence interval for the estimate.
<code>conf.low</code>	Lower bound on the confidence interval for the estimate.
<code>estimate</code>	The estimated value of the regression term.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>statistic</code>	The value of a T-statistic to use in a hypothesis that the regression term is non-zero.
<code>std.error</code>	The standard error of the regression term.
<code>term</code>	The name of the regression term.
<code>component</code>	Whether a particular term was used to model the mean or the precision in the regression. See details.

See Also

`tidy()`, `vars::VAR()`

Examples

```
# load libraries for models and data
library(vars)

# load data
data("Canada", package = "vars")

# fit models
mod <- VAR(Canada, p = 1, type = "both")

# summarize model fit with tidiers
tidy(mod)
glance(mod)
```

tidy.zoo

Tidy a(n) zoo object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies across models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'zoo'
tidy(x, ...)
```

Arguments

`x` A zoo object such as those created by `zoo::zoo()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Two exceptions here are:

- `tidy()` methods will warn when supplied an `exponentiate` argument if it will be ignored.
- `augment()` methods will warn when supplied a `newdata` argument if it will be ignored.

Value

A `tibble::tibble()` with columns:

<code>index</code>	Index (i.e. date or time) for a 'ts' or 'zoo' object.
<code>series</code>	Name of the series (present only for multivariate time series).
<code>value</code>	The value/estimate of the component. Results from data reshaping.

See Also

`tidy()`, `zoo::zoo()`

Other time series tidiers: `tidy.acf()`, `tidy.spec()`, `tidy.ts()`

Examples

```
# load libraries for models and data
library(zoo)
library(ggplot2)

set.seed(1071)

# generate data
Z.index <- as.Date(sample(12450:12500, 10))
Z.data <- matrix(rnorm(30), ncol = 3)
colnames(Z.data) <- c("Aa", "Bb", "Cc")
Z <- zoo(Z.data, Z.index)

# summarize model fit with tidiers + visualization
tidy(Z)
```

```

ggplot(tidy(Z), aes(index, value, color = series)) +
  geom_line()

ggplot(tidy(Z), aes(index, value)) +
  geom_line() +
  facet_wrap(~series, ncol = 1)

Zrolled <- rollmean(Z, 5)
ggplot(tidy(Zrolled), aes(index, value, color = series)) +
  geom_line()

```

tidy_irlba

Tidy a(n) irlba object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `interp::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, they throw an error.

Usage

```
tidy_irlba(x, ...)
```

Arguments

- | | |
|------------------|---|
| <code>x</code> | A list returned from <code>irlba::irlba()</code> . |
| <code>...</code> | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Details

A very thin wrapper around `tidy_svd()`.

Value

A `tibble::tibble` with columns depending on the component of PCA being tidied.

If `matrix` is "u", "samples", "scores", or "x" each row in the tidied output corresponds to the original data in PCA space. The columns are:

row	ID of the original observation (i.e. rowname from original data).
PC	Integer indicating a principal component.
value	The score of the observation for that particular principal component. That is, the location of the observation in PCA space.

If `matrix` is "v", "rotation", "loadings" or "variables", each row in the tidied output corresponds to information about the principle components in the original space. The columns are:

row	The variable labels (colnames) of the data set on which PCA was performed.
PC	An integer vector indicating the principal component.
value	The value of the eigenvector (axis score) on the indicated principal component.

If `matrix` is "d", "eigenvalues" or "pcs", the columns are:

PC	An integer vector indicating the principal component.
std.dev	Standard deviation explained by this PC.
percent	Fraction of variation explained by this component (a numeric value between 0 and 1).
cumulative	Cumulative fraction of variation explained by principle components up to this component (a numeric value between 0 and 1).

See Also

`tidy()`, `irlba::irlba()`

Other list tidiers: `glance_optim()`, `list_tidiers`, `tidy_optim()`, `tidy_svd()`, `tidy_xyz()`

Other svd tidiers: `augment.prcomp()`, `tidy.prcomp()`, `tidy_svd()`

Examples

```
library(modeldata)
data(hpc_data)

mat <- scale(as.matrix(hpc_data[, 2:5]))
s <- svd(mat)

tidy_u <- tidy(s, matrix = "u")
tidy_u

tidy_d <- tidy(s, matrix = "d")
tidy_d
```

```

tidy_v <- tidy(s, matrix = "v")
tidy_v

library(ggplot2)
library(dplyr)

ggplot(tidy_d, aes(PC, percent)) +
  geom_point() +
  ylab("% of variance explained")

tidy_u %>%
  mutate(class = hpc_data$class[row]) %>%
  ggplot(aes(class, value)) +
  geom_boxplot() +
  facet_wrap(~PC, scale = "free_y")

```

tidy_optim

Tidy a(n) optim object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `interp::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, they throw an error.

Usage

```
tidy_optim(x, ...)
```

Arguments

- | | |
|-----|---|
| x | A list returned from <code>stats::optim()</code> . |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble()` with columns:

parameter	The parameter being modeled.
std.error	The standard error of the regression term.
value	The value/estimate of the component. Results from data reshaping.

std.error is only provided as a column if the Hessian is calculated.

Note

This function assumes that the provided objective function is a negative log-likelihood function. Results will be invalid if an incorrect function is supplied.

`tidy(o)` `glance(o)`

See Also

`tidy()`, `stats::optim()`

Other list tidiers: `glance_optim()`, `list_tidiers`, `tidy_irlba()`, `tidy_svd()`, `tidy_xyz()`

Examples

```
f <- function(x) (x[1] - 2)^2 + (x[2] - 3)^2 + (x[3] - 8)^2
o <- optim(c(1, 1, 1), f)
```

tidy_svd

Tidy a(n) svd object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `interp::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, they throw an error.

Usage

```
tidy_svd(x, matrix = "u", ...)
```

Arguments

<code>x</code>	A list with components <code>u</code> , <code>d</code> , <code>v</code> returned by <code>base::svd()</code> .
<code>matrix</code>	Character specifying which component of the PCA should be tidied. <ul style="list-style-type: none"> • <code>"u"</code>, <code>"samples"</code>, <code>"scores"</code>, or <code>"x"</code>: returns information about the map from the original space into principle components space. • <code>"v"</code>, <code>"rotation"</code>, <code>"loadings"</code> or <code>"variables"</code>: returns information about the map from principle components space back into the original space. • <code>"d"</code>, <code>"eigenvalues"</code> or <code>"pcs"</code>: returns information about the eigenvalues.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored.

Details

See <https://stats.stackexchange.com/questions/134282/relationship-between-svd-and-pca-how-to-use-svd-to-perform-pca> for information on how to interpret the various tidied matrices. Note that SVD is only equivalent to PCA on centered data.

Value

A `tibble::tibble` with columns depending on the component of PCA being tidied.

If `matrix` is `"u"`, `"samples"`, `"scores"`, or `"x"` each row in the tidied output corresponds to the original data in PCA space. The columns are:

<code>row</code>	ID of the original observation (i.e. <code>rowname</code> from original data).
<code>PC</code>	Integer indicating a principal component.
<code>value</code>	The score of the observation for that particular principal component. That is, the location of the observation in PCA space.

If `matrix` is `"v"`, `"rotation"`, `"loadings"` or `"variables"`, each row in the tidied output corresponds to information about the principle components in the original space. The columns are:

<code>row</code>	The variable labels (<code>colnames</code>) of the data set on which PCA was performed.
<code>PC</code>	An integer vector indicating the principal component.
<code>value</code>	The value of the eigenvector (axis score) on the indicated principal component.

If `matrix` is `"d"`, `"eigenvalues"` or `"pcs"`, the columns are:

<code>PC</code>	An integer vector indicating the principal component.
<code>std.dev</code>	Standard deviation explained by this PC.

percent	Fraction of variation explained by this component (a numeric value between 0 and 1).
cumulative	Cumulative fraction of variation explained by principle components up to this component (a numeric value between 0 and 1).

See Also

[base::svd\(\)](#)

Other svd tidiers: [augment.prcomp\(\)](#), [tidy.prcomp\(\)](#), [tidy_irlba\(\)](#)

Other list tidiers: [glance_optim\(\)](#), [list_tidiers](#), [tidy_irlba\(\)](#), [tidy_optim\(\)](#), [tidy_xyz\(\)](#)

Examples

```
library(modeldata)
data(hpc_data)

mat <- scale(as.matrix(hpc_data[, 2:5]))
s <- svd(mat)

tidy_u <- tidy(s, matrix = "u")
tidy_u

tidy_d <- tidy(s, matrix = "d")
tidy_d

tidy_v <- tidy(s, matrix = "v")
tidy_v

library(ggplot2)
library(dplyr)

ggplot(tidy_d, aes(PC, percent)) +
  geom_point() +
  ylab("% of variance explained")

tidy_u %>%
  mutate(class = hpc_data$class[row]) %>%
  ggplot(aes(class, value)) +
  geom_boxplot() +
  facet_wrap(~PC, scale = "free_y")
```

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `interp::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, they throw an error.

xyz lists (lists where x and y are vectors of coordinates and z is a matrix of values) are typically used by functions such as `graphics::persp()` or `graphics::image()` and returned by interpolation functions such as `interp::interp()`.

Usage

```
tidy_xyz(x, ...)
```

Arguments

- | | |
|-----|---|
| x | A list with component x, y and z, where x and y are vectors and z is a matrix. The length of x must equal the number of rows in z and the length of y must equal the number of columns in z. |
| ... | Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Two exceptions here are: <ul style="list-style-type: none"> • <code>tidy()</code> methods will warn when supplied an <code>exponentiate</code> argument if it will be ignored. • <code>augment()</code> methods will warn when supplied a <code>newdata</code> argument if it will be ignored. |

Value

A `tibble::tibble` with vector columns x, y and z.

See Also

`tidy()`, `graphics::persp()`, `graphics::image()`, `interp::interp()`

Other list tidiers: `glance_optim()`, `list_tidiers`, `tidy_irlba()`, `tidy_optim()`, `tidy_svd()`

Examples

```
A <- list(x = 1:5, y = 1:3, z = matrix(runif(5 * 3), nrow = 5))
image(A)
tidy(A)
```

Index

- * **Arima tidiers**
 - glance.Arima, 109
 - tidy.Arima, 236
- * **aareg tidiers**
 - glance.aareg, 104
 - tidy.aareg, 230
- * **anova tidiers**
 - glance.anova, 106
 - glance.aov, 107
 - tidy.anova, 232
 - tidy.aov, 234
 - tidy.aovlist, 235
 - tidy.manova, 323
 - tidy.TukeyHSD, 403
- * **betareg tidiers**
 - tidy.betareg, 240
- * **biglm tidiers**
 - glance.biglm, 114
 - tidy.biglm, 241
- * **bingroup tidiers**
 - glance.binDesign, 115
 - tidy.binDesign, 243
 - tidy.binWidth, 245
- * **car tidiers**
 - durbinWatsonTest_tidiers, 102
 - leveneTest_tidiers, 224
- * **cch tidiers**
 - glance.cch, 117
 - glance.survfit, 214
 - tidy.cch, 250
- * **cmprsk tidiers**
 - glance.crr, 127
 - tidy.crr, 264
- * **coefstest tidiers**
 - tidy.coefstest, 257
- * **coefstest_tidiers**
 - glance.coefstest, 122
- * **coxph tidiers**
 - augment.coxph, 17
 - glance.coxph, 124
 - tidy.coxph, 262
- * **crr tidiers**
 - glance.crr, 127
- * **decompose tidiers**
 - augment.decomposed.ts, 20
 - augment.stl, 93
- * **deprecated**
 - bootstrap, 98
 - confint_tidy, 99
 - data.frame_tidiers, 100
 - finish_glance, 103
 - fix_data_frame, 104
 - summary_tidiers, 228
 - tidy.density, 268
 - tidy.dist, 269
 - tidy.ftable, 284
 - tidy.numeric, 348
- * **drc tidiers**
 - augment.drc, 23
 - glance.drc, 130
 - tidy.drc, 270
- * **emmeans tidiers**
 - tidy.emmGrid, 271
 - tidy.lsmobj, 321
 - tidy.ref.grid, 366
 - tidy.summary_emm, 388
- * **epiR tidiers**
 - tidy.epi.2by2, 274
- * **ergm tidiers**
 - glance.ergm, 132
 - tidy.ergm, 275
- * **factanal tidiers**
 - augment.factanal, 25
 - glance.factanal, 133
 - tidy.factanal, 277
- * **felm tidiers**
 - augment.felm, 27
 - tidy.felm, 278

- * **fitdistr tidiers**
 - glance.fitdistr, 137
 - tidy.fitdistr, 281
- * **fixest tidiers**
 - augment.fixest, 29
 - tidy.fixest, 282
- * **gam tidiers**
 - glance.Gam, 140
 - tidy.Gam, 285
- * **garch tidiers**
 - glance.garch, 143
 - tidy.garch, 288
- * **geepack tidiers**
 - glance.geeglm, 144
- * **glm.nb tidiers**
 - glance.negbin, 179
 - tidy.negbin, 343
- * **glmnet tidiers**
 - glance.cv.glmnet, 128
 - glance.glmnet, 148
 - tidy.cv.glmnet, 266
 - tidy.glmnet, 294
- * **gmm tidiers**
 - glance.gmm, 151
 - tidy.gmm, 299
- * **htest tidiers**
 - augment.htest, 39
 - tidy.htest, 301
 - tidy.pairwise.htest, 350
 - tidy.power.htest, 359
- * **ivreg tidiers**
 - augment.ivreg, 41
 - glance.ivreg, 153
 - tidy.ivreg, 303
- * **kmeans tidiers**
 - augment.kmeans, 43
 - glance.kmeans, 155
 - tidy.kmeans, 309
- * **lavaan tidiers**
 - glance.lavaan, 157
 - tidy.lavaan, 311
- * **list tidiers**
 - glance_optim, 223
 - list_tidiers, 225
 - tidy_irlba, 408
 - tidy_optim, 410
 - tidy_svd, 411
 - tidy_xyz, 413
- * **lm tidiers**
 - augment.glm, 34
 - augment.lm, 45
 - glance.glm, 146
 - glance.lm, 159
 - glance.summary.lm, 208
 - glance.svyglm, 218
 - tidy.glm, 293
 - tidy.lm, 312
 - tidy.lm.beta, 315
 - tidy.mlm, 338
 - tidy.summary.lm, 386
- * **lmodel2 tidiers**
 - glance.lmodel2, 161
 - tidy.lmodel2, 317
- * **margins tidiers**
 - tidy.margins, 326
- * **mclust tidiers**
 - augment.Mclust, 55
 - tidy.Mclust, 328
- * **mediate tidiers**
 - tidy.mediate, 330
- * **mfx tidiers**
 - augment.betamfx, 10
 - augment.mfx, 57
 - glance.betamfx, 110
 - glance.mfx, 170
 - tidy.betamfx, 238
 - tidy.mfx, 331
- * **mgcv tidiers**
 - glance.gam, 142
 - tidy.gam, 286
- * **mjoint tidiers**
 - glance.mjoint, 172
 - tidy.mjoint, 334
- * **mlogit tidiers**
 - augment.mlogit, 63
 - glance.mlogit, 174
 - tidy.mlogit, 339
- * **muhaz tidiers**
 - glance.muhaz, 176
 - tidy.muhaz, 341
- * **multcomp tidiers**
 - tidy.cld, 252
 - tidy.confint.glht, 259
 - tidy.glht, 291
 - tidy.summary.glht, 385
- * **multinom tidiers**

- glance.multinom, 177
- tidy.multinom, 342
- * **nls tidiers**
 - augment.nls, 66
 - glance.nls, 182
 - tidy.nls, 346
- * **orcutt tidiers**
 - glance.orcutt, 184
 - tidy.orcutt, 349
- * **ordinal tidiers**
 - augment.clm, 15
 - augment.polr, 75
 - glance.clm, 119
 - glance.clmm, 121
 - glance.polr, 191
 - glance.svyolr, 220
 - tidy.clm, 253
 - tidy.clmm, 255
 - tidy.polr, 357
 - tidy.svyolr, 398
- * **pam tidiers**
 - augment.pam, 68
 - glance.pam, 185
 - tidy.pam, 351
- * **plm tidiers**
 - augment.plm, 70
 - glance.plm, 187
 - tidy.plm, 353
- * **poLCA tidiers**
 - augment.poLCA, 72
 - glance.poLCA, 188
 - tidy.poLCA, 355
- * **pyears tidiers**
 - glance.pyears, 192
 - tidy.pyears, 362
- * **quantreg tidiers**
 - augment.nlrq, 65
 - augment.rq, 83
 - augment.rqs, 85
 - glance.nlrq, 180
 - glance.rq, 199
 - tidy.nlrq, 345
 - tidy.rq, 375
 - tidy.rqs, 377
- * **ridgelm tidiers**
 - glance.ridgelm, 194
 - tidy.ridgelm, 369
- * **rlm tidiers**
 - augment.rlm, 79
 - glance.rlm, 196
 - tidy.rlm, 371
- * **robust tidiers**
 - augment.lmRob, 49
 - glance.glmRob, 149
 - glance.lmRob, 163
 - tidy.glmRob, 296
 - tidy.lmRob, 318
- * **robustbase tidiers**
 - augment.glmrob, 37
 - augment.lmrob, 51
 - glance.lmrob, 165
 - tidy.glmrob, 297
 - tidy.lmrob, 319
- * **smoothing spline tidiers**
 - augment.smooth.spline, 90
 - glance.smooth.spline, 203
- * **spatialreg tidiers**
 - augment.sarlm, 88
 - glance.sarlm, 201
 - tidy.sarlm, 379
- * **speedlm tidiers**
 - augment.speedlm, 91
 - glance.speedglm, 204
 - glance.speedlm, 206
 - tidy.speedglm, 382
 - tidy.speedlm, 383
- * **survdiff tidiers**
 - glance.survdiff, 211
 - tidy.survdiff, 390
- * **survexp tidiers**
 - glance.survexp, 212
 - tidy.survexp, 392
- * **survey tidiers**
 - tidy.svyglm, 397
- * **survfit tidiers**
 - tidy.survfit, 393
- * **survival tidiers**
 - augment.coxph, 17
 - augment.survreg, 95
 - glance.aareg, 104
 - glance.cch, 117
 - glance.coxph, 124
 - glance.pyears, 192
 - glance.survdiff, 211
 - glance.survexp, 212
 - glance.survfit, 214

- glance.survreg, 216
- tidy.aareg, 230
- tidy.cch, 250
- tidy.coxph, 262
- tidy.pyears, 362
- tidy.survdiff, 390
- tidy.survexp, 392
- tidy.survfit, 393
- tidy.survreg, 395
- * **survreg tidiers**
 - augment.survreg, 95
 - glance.survreg, 216
 - tidy.survreg, 395
- * **svd tidiers**
 - augment.prcomp, 77
 - tidy.prcomp, 360
 - tidy_irlba, 408
 - tidy_svd, 411
- * **systemfit tidiers**
 - tidy.systemfit, 399
- * **time series tidiers**
 - tidy.acf, 231
 - tidy.spec, 381
 - tidy.ts, 402
 - tidy.zoo, 406
- * **vars tidiers**
 - tidy.varest, 405
- aareg_tidiers(tidy.aareg), 230
- AER::ivreg(), 42, 43, 154, 155, 303, 304
- aer_tidiers(tidy.ivreg), 303
- Arima_tidiers(tidy.Arima), 236
- AUC::roc(), 374
- auc_tidiers(tidy.roc), 373
- augment, 84, 87
- augment(), 15, 19, 22, 24, 26, 28, 30, 33, 40, 43, 45, 47, 54, 56, 64, 66, 70, 72, 74, 89, 91, 95–97, 204
- augment.betamfx, 10, 60, 111, 172, 239, 333
- augment.betareg, 13
- augment.betareg(), 12
- augment.clm, 15, 76, 120, 122, 192, 221, 255, 256, 358, 399
- augment.coxph, 17, 96, 105, 118, 126, 193, 212, 213, 215, 217, 231, 251, 263, 363, 391, 392, 394, 396
- augment.data.frame
 - (data.frame_tidiers), 100
- augment.decomposed.ts, 20, 95
- augment.drc, 23, 131, 271
- augment.factanal, 25, 134, 278
- augment.felm, 27, 280
- augment.fixest, 29, 283
- augment.gam, 31
- augment.glm, 34, 47, 147, 160, 209, 219, 294, 313, 316, 339, 387
- augment.glm(), 59, 60
- augment.glmRob, 36
- augment.glmrob, 37, 52, 166, 298, 320
- augment.htest, 39, 302, 351, 360
- augment.ivreg, 41, 155, 304
- augment.kmeans, 43, 156, 310
- augment.lm, 36, 45, 147, 160, 209, 219, 294, 313, 316, 339, 387
- augment.lmRob, 49, 150, 164, 296, 319
- augment.lmrob, 38, 51, 166, 298, 320
- augment.loess, 53
- augment.logitmfx(augment.mfx), 57
- augment.Mclust, 55, 329
- augment.mfx, 12, 57, 111, 172, 239, 333
- augment.mjoint, 60
- augment.mlogit, 63, 175, 340
- augment.negbinmfx(augment.mfx), 57
- augment.nlrq, 65, 84, 87, 181, 200, 346, 376, 378
- augment.nls, 66, 183, 347
- augment.NULL(null_tidiers), 226
- augment.pam, 68, 186, 352
- augment.plm, 70, 188, 354
- augment.poissonmfx(augment.mfx), 57
- augment.polCA, 72, 190, 356
- augment.polr, 17, 75, 120, 122, 192, 221, 255, 256, 358, 399
- augment.prcomp, 77, 361, 409, 413
- augment.probitmfx(augment.mfx), 57
- augment.rlm, 79, 197, 371
- augment.rma, 81
- augment.rq, 66, 83, 87, 181, 200, 346, 376, 378
- augment.rqs, 66, 84, 85, 181, 200, 346, 376, 378
- augment.sarlm, 88, 202, 380
- augment.smooth.spline, 90, 204
- augment.speedlm, 91, 205, 207, 383, 384
- augment.stl, 22, 93
- augment.survreg, 19, 95, 105, 118, 126, 193, 212, 213, 215, 217, 231, 251, 263,

- 363, 391, 392, 394, 396
 augment_columns, 97
- base::data.frame, 11, 14, 16, 18, 24, 26, 27, 30, 32, 35, 38, 42, 44, 46, 50, 51, 53, 55, 59, 61, 65, 67, 69, 71, 73, 76, 78, 79, 83, 86, 90, 92, 96
 base::data.frame(), 12, 14, 16, 18, 24, 30, 32, 35, 38, 42, 46, 50, 52, 53, 59, 65, 67, 76, 78, 80, 84, 86, 92, 96
 base::svd(), 225, 412, 413
 base::table, 401, 402
 bbmle::mle2(), 336, 337
 bbmle_tidiers (tidy.mle2), 336
 betareg::betareg(), 14, 15, 112, 113, 240, 241
 betareg::predict.betareg(), 12
 betareg::residuals.betareg(), 12
 betareg_tidiers (tidy.betareg), 240
 biglm::bigglm(), 114, 115, 242
 biglm::biglm(), 114, 115, 242
 bindesign_tidiers (tidy.binDesign), 243
 binGroup::binDesign, 116
 binGroup::binDesign(), 116, 243, 244
 binGroup::binWidth(), 245
 binwidth_tidiers (tidy.binWidth), 245
 boot::boot(), 246, 247
 boot::boot.ci(), 247
 boot::tsboot(), 247
 boot_tidiers (tidy.boot), 246
 bootstrap, 98, 99, 101, 103, 104, 229, 268, 269, 285, 348
 btergm::btergm(), 248, 249
 btergm_tidiers (tidy.btergm), 248
- car::Anova(), 106, 233
 car::durbinWatsonTest(), 102
 car::leveneTest(), 106, 224, 233–235
 car::linearHypothesis(), 106, 233
 caret::confusionMatrix(), 261
 caret_tidiers (tidy.confusionMatrix), 260
 cch_tidiers (tidy.cch), 250
 cfa_tidiers (tidy.lavaan), 311
 cluster::pam(), 69, 70, 186, 352
 cmprsk::crr(), 127, 128, 265
 cmprsk_tidiers (tidy.crr), 264
 coeftest_tidiers (tidy.coeftest), 257
 confint(), 99
 confint_tidy, 98, 99, 101, 103, 104, 229, 268, 269, 285, 348
 confusionMatrix_tidiers (tidy.confusionMatrix), 260
 coxph_tidiers (tidy.coxph), 262
- data.frame_tidiers, 98, 99, 100, 103, 104, 229, 268, 269, 285, 348
 decompose_tidiers (augment.decomposed.ts), 20
 drc::drm(), 24, 131, 270, 271
 drc_tidiers (tidy.drc), 270
 durbinWatsonTest_tidiers, 102, 224
- emmeans::contrast(), 272, 322, 367, 389
 emmeans::emmeans(), 272, 322, 367, 389
 emmeans::ref_grid(), 272, 322, 366, 367, 389
 emmeans::summary.emmGrid(), 272, 321, 366, 388
 emmeans_tidiers (tidy.lsmobj), 321
 epiR::epi.2by2(), 274, 275
 epiR_tidiers (tidy.epi.2by2), 274
 ergm::control.ergm(), 276
 ergm::ergm(), 132, 133, 276
 ergm::summary(), 133, 276
 ergm::summary.ergm(), 133
 ergm_tidiers (tidy.ergm), 275
- factanal_tidiers (tidy.factanal), 277
 felm_tidiers (tidy.felm), 278
 finish_glance, 98, 99, 101, 103, 104, 229, 268, 269, 285, 348
 fitdistr_tidiers (tidy.fitdistr), 281
 fix_data_frame, 98, 99, 101, 103, 104, 229, 268, 269, 285, 348
 fixest::feglm(), 30, 283
 fixest::felm(), 30, 283
 fixest::fenegbin(), 30, 283
 fixest::feNmlm(), 30, 283
 fixest::feols(), 30, 283
 fixest::fepois(), 30, 283
- gam::gam(), 141, 142, 285, 286
 Gam_tidiers (tidy.Gam), 285
 gam_tidiers (tidy.gam), 286
 garch_tidiers (tidy.garch), 288
 geeglm_tidiers (tidy.geeglm), 289
 geopack::geeglm(), 145, 290, 291

- geepack_tidiers (tidy.geeglm), 289
 glance(), 102, 105, 107, 108, 113, 115, 116,
 118, 124, 126, 128, 129, 131, 133,
 134, 142–145, 149, 152, 155, 156,
 158, 160, 162, 173, 175, 177, 178,
 180, 181, 185, 186, 188, 190, 193,
 195, 197, 200, 202, 209, 212, 213,
 215, 217, 222–224, 301
 glance.aareg, 19, 96, 104, 118, 126, 193,
 212, 213, 215, 217, 231, 251, 263,
 363, 391, 392, 394, 396
 glance.anova, 106, 108, 233, 235, 236, 324,
 404
 glance.aov, 107, 107, 233, 235, 236, 324, 404
 glance.Arima, 109, 237
 glance.betamfx, 12, 60, 110, 172, 239, 333
 glance.betareg, 112
 glance.betareg(), 111
 glance.biglm, 114, 242
 glance.binDesign, 115, 244, 245
 glance.cch, 19, 96, 105, 117, 126, 193, 212,
 213, 215, 217, 231, 251, 263, 363,
 391, 392, 394, 396
 glance.clm, 17, 76, 119, 122, 192, 221, 255,
 256, 358, 399
 glance.clm, 17, 76, 120, 121, 192, 221, 255,
 256, 358, 399
 glance.coeftest, 122
 glance.coxph, 19, 96, 105, 118, 124, 193,
 212, 213, 215, 217, 231, 251, 263,
 363, 391, 392, 394, 396
 glance.crr, 127, 265
 glance.cv.glmnet, 128, 149, 267, 295
 glance.data.frame (data.frame_tidiers),
 100
 glance.drc, 24, 130, 271
 glance.durbinWatsonTest
 (durbinWatsonTest_tidiers), 102
 glance.ergm, 132, 276
 glance.factanal, 26, 133, 278
 glance.felm, 135
 glance.fitdistr, 137, 281
 glance.fixest, 139
 glance.Gam, 140, 286
 glance.gam, 142, 287
 glance.gam(), 141
 glance.garch, 143, 289
 glance.geeglm, 144
 glance.glm, 36, 47, 146, 160, 209, 219, 294,
 313, 316, 339, 387
 glance.glm(), 171, 172
 glance.glmnet, 129, 148, 267, 295
 glance.glmRob, 50, 149, 164, 296, 319
 glance.gmm, 151, 300
 glance.htest (tidy.htest), 301
 glance.ivreg, 43, 153, 304
 glance.kmeans, 45, 155, 310
 glance.lavaan, 157, 312
 glance.list (list_tidiers), 225
 glance.lm, 36, 47, 147, 159, 209, 219, 294,
 313, 316, 339, 387
 glance.lm(), 208
 glance.lmodel2, 161, 318
 glance.lmRob, 50, 150, 163, 296, 319
 glance.lmrob, 38, 52, 165, 298, 320
 glance.logitmfx (glance.mfx), 170
 glance.margins, 166
 glance.Mclust, 168
 glance.mfx, 12, 60, 111, 170, 239, 333
 glance.mjoint, 172, 335
 glance.mlogit, 64, 174, 340
 glance.muhaz, 176, 341
 glance.multinom, 177, 343
 glance.negbin, 179, 344
 glance.negbinmfx (glance.mfx), 170
 glance.nlrq, 66, 84, 87, 180, 200, 346, 376,
 378
 glance.nls, 68, 182, 347
 glance.NULL (null_tidiers), 226
 glance.optim (glance_optim), 223
 glance.orcutt, 184, 350
 glance.pam, 70, 185, 352
 glance.plm, 72, 187, 354
 glance.poissonmfx (glance.mfx), 170
 glance.poLCA, 74, 188, 356
 glance.polr, 17, 76, 120, 122, 191, 221, 255,
 256, 358, 399
 glance.probitmfx (glance.mfx), 170
 glance.pyears, 19, 96, 105, 118, 126, 192,
 212, 213, 215, 217, 231, 251, 263,
 363, 391, 392, 394, 396
 glance.ridge, 194, 370
 glance.rlm, 80, 196, 371
 glance.rma, 197
 glance.rq, 66, 84, 87, 181, 199, 346, 376, 378
 glance.sarlm, 89, 201, 380

- glance.smooth.spline, [91](#), [203](#)
 glance.speedglm, [93](#), [204](#), [207](#), [383](#), [384](#)
 glance.speedlm, [93](#), [205](#), [206](#), [383](#), [384](#)
 glance.summary.lm, [36](#), [47](#), [147](#), [160](#), [208](#),
 [219](#), [294](#), [313](#), [316](#), [339](#), [387](#)
 glance.summary.lm(), [160](#), [209](#)
 glance.summaryDefault
 (summary_tidiers), [228](#)
 glance.survdiff, [19](#), [96](#), [105](#), [118](#), [126](#), [193](#),
 [211](#), [213](#), [215](#), [217](#), [231](#), [251](#), [263](#),
 [363](#), [391](#), [392](#), [394](#), [396](#)
 glance.surveysp, [19](#), [96](#), [105](#), [118](#), [126](#), [193](#),
 [212](#), [212](#), [215](#), [217](#), [231](#), [251](#), [263](#),
 [363](#), [391](#), [392](#), [394](#), [396](#)
 glance.survfit, [19](#), [96](#), [105](#), [118](#), [126](#), [193](#),
 [212](#), [213](#), [214](#), [217](#), [231](#), [251](#), [263](#),
 [363](#), [391](#), [392](#), [394](#), [396](#)
 glance.survreg, [19](#), [96](#), [105](#), [118](#), [126](#), [193](#),
 [212](#), [213](#), [215](#), [216](#), [231](#), [251](#), [263](#),
 [363](#), [391](#), [392](#), [394](#), [396](#)
 glance.svyglm, [36](#), [47](#), [147](#), [160](#), [209](#), [218](#),
 [294](#), [313](#), [316](#), [339](#), [387](#)
 glance.svyolr, [17](#), [76](#), [120](#), [122](#), [192](#), [220](#),
 [255](#), [256](#), [358](#), [399](#)
 glance.varest, [221](#)
 glance_optim, [223](#), [225](#), [409](#), [411](#), [413](#), [414](#)
 glm.nb_tidiers (glance.negbin), [179](#)
 glmnet::cv.glmnet(), [129](#), [266](#), [267](#)
 glmnet::glmnet(), [148](#), [149](#), [294](#), [295](#)
 glmnet_tidiers (tidy.glmnet), [294](#)
 gmm::gmm(), [151](#), [152](#), [299](#), [300](#)
 gmm_tidiers (tidy.gmm), [299](#)
 graphics::image(), [414](#)
 graphics::persp(), [414](#)

 Hmisc::rcorr(), [364](#), [365](#)
 Hmisc_tidiers (tidy.rcorr), [364](#)
 htest_tidiers (tidy.htest), [301](#)

 interp::interp(), [223](#), [225](#), [408](#), [410](#), [411](#),
 [414](#)
 irlba::irlba(), [408](#), [409](#)
 irlba_tidiers (tidy_irlba), [408](#)
 ivreg_tidiers (tidy.ivreg), [303](#)

 joinerML::bootSE(), [334](#), [335](#)
 joinerML::fitted.mjoint(), [62](#)
 joinerML::mjoint(), [61](#), [173](#), [334](#), [335](#)
 joinerML::residuals.mjoint(), [62](#)

 joinerML_tidiers (tidy.mjoint), [334](#)

 kappa_tidiers (tidy.kappa), [305](#)
 kde_tidiers (tidy.kde), [306](#)
 Kendall::Kendall(), [308](#), [309](#)
 Kendall::MannKendall(), [308](#), [309](#)
 Kendall::SeasonalMannKendall(), [308](#),
 [309](#)
 Kendall_tidiers (tidy.Kendall), [308](#)
 kendall_tidiers (tidy.Kendall), [308](#)
 kmeans_tidiers (tidy.kmeans), [309](#)
 ks::kde(), [307](#)
 ks_tidiers (tidy.kde), [306](#)

 lavaan::cfa(), [157](#), [158](#), [311](#), [312](#)
 lavaan::fitmeasures(), [158](#)
 lavaan::parameterEstimates(), [311](#), [312](#)
 lavaan::sem(), [157](#), [158](#), [311](#), [312](#)
 lavaan_tidiers (tidy.lavaan), [311](#)
 leaps::regsubsets(), [368](#), [369](#)
 leaps_tidiers (tidy.regsubsets), [368](#)
 leveneTest_tidiers, [102](#), [224](#)
 lfe::felm(), [27](#), [28](#), [136](#), [279](#), [280](#)
 lfe_tidiers (tidy.felm), [278](#)
 list_tidiers, [223](#), [225](#), [409](#), [411](#), [413](#), [414](#)
 lm.beta::lm.beta, [315](#)
 lm_tidiers (tidy.lm), [312](#)
 lmodel2::lmodel2(), [162](#), [317](#), [318](#)
 lmodel2_tidiers (tidy.lmodel2), [317](#)
 lmtest::coefstest(), [123](#), [124](#), [257](#), [258](#)
 lmtest_tidiers (tidy.coefstest), [257](#)
 loess_tidiers (augment.loess), [53](#)
 lsmeans::summary.ref.grid(), [272](#), [321](#),
 [366](#), [388](#)

 maps::map(), [325](#)
 maps_tidiers (tidy.map), [324](#)
 margins::margins(), [167](#), [326](#), [327](#)
 margins_tidiers (tidy.margins), [326](#)
 MASS::dropterm(), [358](#)
 MASS::fitdistr(), [137](#), [138](#), [281](#)
 MASS::glm.nb(), [179](#), [180](#), [344](#)
 MASS::lm.ridge(), [195](#), [369](#), [370](#)
 MASS::polr(), [76](#), [191](#), [192](#), [357](#), [358](#)
 MASS::rlm(), [79](#), [80](#), [196](#), [197](#), [371](#)
 MASS::select.ridge.lm(), [195](#)
 mclust::Mclust(), [55](#), [56](#), [169](#), [328](#), [329](#)
 mclust_tidiers (tidy.Mclust), [328](#)
 mean, [100](#)

- mediate_tidiers (tidy.mediate), 330
 mediation::mediate(), 330, 331
 metafor::escalc(), 372
 metafor::rma(), 81, 198, 372
 metafor::rma.glm(), 81, 198, 372
 metafor::rma.mh(), 81, 198, 372
 metafor::rma.mv(), 81, 198, 372
 metafor::rma.peto(), 81, 198, 372
 metafor::rma.uni(), 81, 198, 372
 mfx::betamfx(), 12, 111, 239
 mfx::logitmfx(), 60, 172, 333
 mfx::negbinmfx(), 60, 172, 333
 mfx::poissonmfx(), 60, 172, 333
 mfx::probitmfx(), 60, 172, 333
 mgcv::gam(), 32, 33, 141–143, 285–287
 mgcv_tidiers (tidy.gam), 286
 mjoint_tidiers (tidy.mjoint), 334
 mle2_tidiers (tidy.mle2), 336
 mlogit::mlogit(), 64, 175, 339, 340
 mlogit_tidiers (tidy.mlogit), 339
 muhaz::muhaz(), 176, 177, 341
 muhaz_tidiers (tidy.muhaz), 341
 multcomp::cld(), 252
 multcomp::confint.glm(), 252, 259, 260
 multcomp::glm(), 252, 259, 260, 291, 292, 385, 386
 multcomp::summary.glm(), 252, 385, 386
 multcomp_tidiers (tidy.glm), 291
 multinom_tidiers (tidy.multinom), 342

 nlrq_tidiers (tidy.nlrq), 345
 nls_tidiers (tidy.nls), 346
 nnet::multinom(), 178, 342, 343
 nnet_tidiers (tidy.multinom), 342
 null_tidiers, 226

 optim_tidiers (tidy.optim), 410
 orcutt::cochrane.orcutt(), 184, 185, 349, 350
 orcutt_tidiers (tidy.orcutt), 349
 ordinal::clm(), 16, 17, 119, 120, 254, 255
 ordinal::clmm(), 121, 122, 256
 ordinal::confint.clm(), 254–256
 ordinal::predict.clm(), 16, 17
 ordinal_tidiers (tidy.clm), 253

 pam_tidiers (tidy.pam), 351
 plm::plm(), 71, 72, 187, 188, 353, 354
 plm_tidiers (tidy.plm), 353

 polCA::polCA(), 73, 74, 189, 190, 355, 356
 polCA_tidiers (tidy.polCA), 355
 polr_tidiers (tidy.polr), 357
 prcomp_tidiers (tidy.prcomp), 360
 predict.fixest, 30
 psych::cohen.kappa(), 305, 306
 psych_tidiers (tidy.kappa), 305
 purrr::map(), 200
 purrr::map_df(), 226
 pyyears_tidiers (tidy.pyyears), 362

 qr, 323
 quantreg::nlrq(), 65, 66, 181, 345, 346
 quantreg::predict.rq, 84, 86
 quantreg::predict.rq(), 84
 quantreg::predict.rqs(), 87
 quantreg::rq(), 83, 84, 86, 87, 199, 200, 375–378
 quantreg::summary.rq(), 375, 377
 quantreg::summary.rqs(), 377
 quantreg_tidiers (tidy.rq), 375

 rcorr_tidiers (tidy.rcorr), 364
 ridgelm_tidiers (tidy.ridgelm), 369
 rlm_tidiers (glance.rlm), 196
 robust::glmRob(), 150, 296
 robust::lmRob(), 50, 164, 318, 319
 robust_tidiers (tidy.lmRob), 318
 robustbase::glmrob(), 38, 297, 298
 robustbase::lmrob(), 51, 52, 165, 166, 320
 robustbase_tidiers (tidy.lmrob), 319
 roc_tidiers (tidy.roc), 373
 rq_tidiers (tidy.rq), 375
 rqs_tidiers (tidy.rqs), 377
 rsample::bootstraps(), 247

 sem_tidiers (tidy.lavaan), 311
 sexpfit_tidiers (tidy.survexp), 392
 smooth.spline_tidiers
 (augment.smooth.spline), 90
 sp_tidiers, 227
 sparse_tidiers, 226
 spatialreg::errorsarlm(), 88, 201, 202, 379, 380
 spatialreg::lagsarlm(), 88, 201, 202, 379, 380
 spatialreg::sacsarlm(), 202, 380
 spatialreg_tidiers (tidy.sarlm), 379
 speedglm::speedglm(), 205, 382, 383

- speedglm::speedlm(), 92, 93, 205–207, 384
- speedglm_tidiers (tidy.speedglm), 382
- speedlm_tidiers (tidy.speedlm), 383
- splines::ns(), 11, 13, 16, 18, 21, 23, 25, 27, 29, 32, 34, 36, 37, 40, 42, 44, 46, 49, 51, 55, 57, 61, 64, 67, 69, 71, 73, 76, 77, 79, 81, 83, 86, 88, 92, 94, 95
- stats::acf(), 231, 232
- stats::anova(), 106, 233
- stats::aov(), 108, 234–236
- stats::arima(), 109, 110, 237
- stats::ccf(), 231, 232
- stats::chisq.test(), 40, 301, 302
- stats::cooks.distance(), 14, 33
- stats::cor.test(), 40, 301, 302
- stats::decompose(), 21, 22
- stats::density(), 268
- stats::dist(), 269
- stats::factanal(), 26, 134, 277, 278
- stats::ftable(), 284
- stats::glm(), 35, 36, 147, 219, 293, 294, 397
- stats::kmeans(), 44, 45, 156, 310
- stats::lm(), 26, 46, 159, 208, 312, 338
- stats::loess(), 53, 54
- stats::manova(), 323
- stats::na.action, 19, 47, 54
- stats::nls(), 67, 68, 182, 183, 346, 347
- stats::optim(), 223, 225, 408, 410, 411, 414
- stats::pacf(), 231, 232
- stats::pairwise.t.test(), 350, 351
- stats::pairwise.wilcox.test(), 350, 351
- stats::poly(), 11, 13, 16, 18, 21, 23, 25, 27, 29, 32, 34, 36, 37, 40, 42, 44, 46, 49, 51, 55, 57, 61, 64, 67, 69, 71, 73, 76, 77, 79, 81, 83, 86, 88, 92, 94, 95
- stats::power.t.test(), 359, 360
- stats::prcomp(), 78, 360, 361
- stats::predict(), 14, 18, 32, 38, 96
- stats::predict.glm(), 35, 59
- stats::predict.lm(), 47
- stats::predict.loess(), 54
- stats::predict.nls(), 68
- stats::predict.smooth.spline(), 91
- stats::residuals(), 14, 18, 32, 38, 96
- stats::residuals.glm(), 35, 59
- stats::rstandard.glm(), 35, 59
- stats::smooth.spline(), 90, 91, 203, 204
- stats::spectrum(), 381
- stats::stl(), 94, 95
- stats::summary.lm(), 313, 387
- stats::summary.manova, 323
- stats::summary.manova(), 324
- stats::summary.nls(), 347
- stats::t.test(), 40, 301, 302
- stats::ts(), 403
- stats::TukeyHSD(), 404
- stats::wilcox.test(), 40, 301, 302
- summary(), 229
- summary.fixest, 30, 139, 282
- summary.survfit(), 214
- summary_tidiers, 98, 99, 101, 103, 104, 228, 268, 269, 285, 348
- survdiff_tidiers (tidy.survdiff), 390
- survexp_tidiers (tidy.survexp), 392
- survey::anova.svyglm, 219
- survey::svyglm(), 218, 219, 397
- survey::svyolr(), 220, 221, 398, 399
- survfit_tidiers (tidy.survfit), 393
- survival::aareg(), 105, 230, 231
- survival::cch(), 117, 118, 250, 251
- survival::coxph(), 18, 19, 125, 126, 262, 263
- survival::pyears(), 193, 363
- survival::Surv(), 11, 13, 16, 18, 21, 23, 25, 27, 29, 32, 34, 36, 37, 40, 42, 44, 46, 49, 51, 55, 57, 61, 64, 67, 69, 71, 73, 76, 77, 79, 81, 83, 86, 88, 92, 94, 95
- survival::survdiff(), 211, 212, 390, 391
- survival::survexp(), 213, 392
- survival::survfit(), 214, 215, 393, 394
- survival::survreg(), 96, 216, 217, 395, 396
- survreg_tidiers (tidy.survreg), 395
- svd(), 223, 408, 410, 411, 414
- svd_tidiers, 78, 361
- svd_tidiers (tidy_svd), 411
- svyolr_tidiers (tidy.svyolr), 398
- systemfit::systemfit(), 400
- systemfit_tidiers (tidy.systemfit), 399
- tibble::as_tibble(), 284, 401, 402
- tibble::as_tibble.table(), 402
- tibble::tibble, 11, 13, 16, 18, 21, 23, 25, 27, 29, 32, 34, 36, 37, 40, 42, 44, 45, 49, 51, 55, 57, 61, 64, 67, 69, 71, 73, 75, 77–79, 81, 83, 86, 88, 92, 94, 95,

- 157, 226, 229, 268, 269, 276, 284, 361, 402, 409, 412, 414
- `tibble::tibble()`, 11, 12, 14, 16, 18, 19, 24, 26–28, 30, 32, 33, 35, 38, 40, 42, 44, 46, 47, 50–56, 59, 61, 62, 64, 65, 67–74, 76, 78–80, 82–84, 86, 89–93, 96, 102, 104–123, 125, 127–129, 131–139, 141, 142, 144–157, 159, 162–187, 189, 191–202, 204–209, 211–214, 216, 218, 220–224, 227, 230, 232, 233, 236, 237, 239, 240, 242, 244, 245, 247, 249, 250, 252, 254, 256, 258, 259, 261, 263, 265, 266, 271, 272, 274, 277, 279, 281, 283, 285, 287, 289, 290, 292, 295, 298, 299, 302, 304, 306, 307, 309–311, 313, 316, 317, 321, 324–326, 329, 331, 333, 335, 337, 338, 340, 341, 343, 345, 347, 349, 351, 352, 354, 355, 358, 359, 363, 365, 366, 368, 370, 373, 374, 376, 378, 379, 381, 383–385, 387, 389, 391, 392, 394, 396, 399, 400, 403, 404, 406, 407, 411
- `tidy`, 17, 68, 120, 122, 183, 192, 221, 255, 256, 347, 358, 399
- `tidy()`, 76, 102, 138, 224, 231–233, 235, 236, 241, 242, 244, 245, 247, 249, 251, 252, 258, 260, 261, 263, 265, 267, 271, 272, 275, 276, 278, 280, 281, 283, 286, 287, 289, 291, 292, 295, 300–302, 304, 306, 307, 309, 310, 312, 313, 318, 322, 324, 325, 327, 329, 331, 333, 335, 337, 339–341, 343, 346, 351, 352, 354, 356, 363, 365, 367, 369, 370, 374, 376, 378, 380, 381, 386, 387, 389, 391, 392, 394, 396, 400, 403, 404, 406, 407, 409, 411, 414
- `tidy.aareg`, 19, 96, 105, 118, 126, 193, 212, 213, 215, 217, 230, 251, 263, 363, 391, 392, 394, 396
- `tidy.acf`, 231, 381, 403, 407
- `tidy.anova`, 107, 108, 232, 235, 236, 324, 404
- `tidy.anova()`, 286
- `tidy.aov`, 107, 108, 233, 234, 236, 324, 404
- `tidy.aovlist`, 107, 108, 233, 235, 235, 324, 404
- `tidy.Arima`, 110, 236
- `tidy.betamfx`, 12, 60, 111, 172, 238, 333
- `tidy.betareg`, 240
- `tidy.betareg()`, 239
- `tidy.biglm`, 115, 241
- `tidy.binDesign`, 116, 243, 245
- `tidy.binWidth`, 116, 244, 245
- `tidy.boot`, 246
- `tidy.btergm`, 248
- `tidy.cch`, 19, 96, 105, 118, 126, 193, 212, 213, 215, 217, 231, 250, 263, 363, 391, 392, 394, 396
- `tidy.character` (`tidy.numeric`), 348
- `tidy.cld`, 252, 260, 292, 386
- `tidy.clm`, 17, 76, 120, 122, 192, 221, 253, 256, 358, 399
- `tidy.clm`, 17, 76, 120, 122, 192, 221, 255, 255, 358, 399
- `tidy.coefstest`, 257
- `tidy.confint.glm`, 252, 259, 292, 386
- `tidy.confusionMatrix`, 260
- `tidy.coxph`, 19, 96, 105, 118, 126, 193, 212, 213, 215, 217, 231, 251, 262, 363, 391, 392, 394, 396
- `tidy.crr`, 128, 264
- `tidy.cv.glmnet`, 129, 149, 266, 295
- `tidy.data.frame` (`data.frame_tidiers`), 100
- `tidy.density`, 98, 99, 101, 103, 104, 229, 268, 269, 285, 348
- `tidy.dgCMatrix` (`sparse_tidiers`), 226
- `tidy.dgTMatrix` (`sparse_tidiers`), 226
- `tidy.dist`, 98, 99, 101, 103, 104, 229, 268, 269, 285, 348
- `tidy.drc`, 24, 131, 270
- `tidy.durbinWatsonTest` (`durbinWatsonTest_tidiers`), 102
- `tidy.emmGrid`, 271, 322, 367, 389
- `tidy.epi.2by2`, 274
- `tidy.ergm`, 133, 275
- `tidy.factanal`, 26, 134, 277
- `tidy.felm`, 28, 278
- `tidy.fitdistr`, 138, 281
- `tidy.fixest`, 30, 282
- `tidy.ftable`, 98, 99, 101, 103, 104, 229, 268, 269, 284, 348
- `tidy.Gam`, 142, 285
- `tidy.gam`, 143, 286

- tidy.gam(), 285, 286
- tidy.garch, 144, 288
- tidy.geeglm, 289
- tidy.glht, 252, 260, 291, 386
- tidy.glm, 36, 47, 147, 160, 209, 219, 293, 313, 316, 339, 387
- tidy.glmnet, 129, 149, 267, 294
- tidy.glmRob, 50, 150, 164, 296, 319
- tidy.glmrob, 38, 52, 166, 297, 320
- tidy.gmm, 152, 299
- tidy.htest, 40, 301, 351, 360
- tidy.irlba (tidy_irlba), 408
- tidy.ivreg, 43, 155, 303
- tidy.kappa, 305
- tidy.kde, 306
- tidy.Kendall, 308
- tidy.kmeans, 45, 156, 309
- tidy.lavaan, 158, 311
- tidy.leveneTest (leveneTest_tidiers), 224
- tidy.leveneTest(), 233–235
- tidy.Line (sp_tidiers), 227
- tidy.Lines (sp_tidiers), 227
- tidy.list (list_tidiers), 225
- tidy.lm, 36, 47, 147, 160, 209, 219, 294, 312, 316, 339, 387
- tidy.lm(), 354, 384, 387
- tidy.lm.beta, 36, 47, 147, 160, 209, 219, 294, 313, 315, 339, 387
- tidy.lmodel2, 162, 317
- tidy.lmRob, 50, 150, 164, 296, 318
- tidy.lmrob, 38, 52, 166, 298, 319
- tidy.logical (tidy.numeric), 348
- tidy.logitmfx (tidy.mfx), 331
- tidy.lsmobj, 272, 321, 367, 389
- tidy.manova, 107, 108, 233, 235, 236, 323, 404
- tidy.map, 324
- tidy.margins, 326
- tidy.Mclust, 56, 328
- tidy.mediate, 330
- tidy.mfx, 12, 60, 111, 172, 239, 331
- tidy.mjoint, 173, 334
- tidy.mle2, 336
- tidy.mlm, 36, 47, 147, 160, 209, 219, 294, 313, 316, 338, 387
- tidy.mlm(), 313
- tidy.mlogit, 64, 175, 339
- tidy.muhaz, 177, 341
- tidy.multinom, 178, 342
- tidy.negbin, 180, 343
- tidy.negbinmfx (tidy.mfx), 331
- tidy.nlrq, 66, 84, 87, 181, 200, 345, 376, 378
- tidy.nls, 68, 183, 346
- tidy.NULL (null_tidiers), 226
- tidy.numeric, 98, 99, 101, 103, 104, 229, 268, 269, 285, 348
- tidy.optim (tidy_optim), 410
- tidy.orcutt, 185, 349
- tidy.pairwise.htest, 40, 302, 350, 360
- tidy.pam, 70, 186, 351
- tidy.plm, 72, 188, 353
- tidy.poissonmfx (tidy.mfx), 331
- tidy.polCA, 74, 190, 355
- tidy.polr, 17, 76, 120, 122, 192, 221, 255, 256, 357, 399
- tidy.polr(), 398
- tidy.Polygon (sp_tidiers), 227
- tidy.Polygons (sp_tidiers), 227
- tidy.power.htest, 40, 302, 351, 359
- tidy.prcomp, 78, 360, 409, 413
- tidy.probitmfx (tidy.mfx), 331
- tidy.pyears, 19, 96, 105, 118, 126, 193, 212, 213, 215, 217, 231, 251, 263, 362, 391, 392, 394, 396
- tidy.rcorr, 364
- tidy.ref.grid, 272, 322, 366, 389
- tidy.regsubsets, 368
- tidy.ridgelm, 195, 369
- tidy.rlm, 80, 197, 371
- tidy.rlm(), 38, 50, 52, 165, 296, 297, 319, 320
- tidy.rma, 372
- tidy.roc, 373
- tidy.rq, 66, 84, 87, 181, 200, 346, 375, 378
- tidy.rqs, 66, 84, 87, 181, 200, 346, 376, 377
- tidy.sarlm, 89, 202, 379
- tidy.sparseMatrix (sparse_tidiers), 226
- tidy.SpatialLinesDataFrame (sp_tidiers), 227
- tidy.SpatialPolygons (sp_tidiers), 227
- tidy.SpatialPolygonsDataFrame (sp_tidiers), 227
- tidy.spec, 232, 381, 403, 407
- tidy.speedglm, 93, 205, 207, 382, 384
- tidy.speedlm, 93, 205, 207, 383, 383

`tidy.summary.glm`, 252, 260, 292, 385
`tidy.summary.lm`, 36, 47, 147, 160, 209, 219,
294, 313, 316, 339, 386
`tidy.summary.emm`, 272, 322, 367, 388
`tidy.summaryDefault(summary_tidiers)`,
228
`tidy.survdif`, 19, 96, 105, 118, 126, 193,
212, 213, 215, 217, 231, 251, 263,
363, 390, 392, 394, 396
`tidy.survexp`, 19, 96, 105, 118, 126, 193,
212, 213, 215, 217, 231, 251, 263,
363, 391, 392, 394, 396
`tidy.survfit`, 19, 96, 105, 118, 126, 193,
212, 213, 215, 217, 231, 251, 263,
363, 391, 392, 393, 396
`tidy.survreg`, 19, 96, 105, 118, 126, 193,
212, 213, 215, 217, 231, 251, 263,
363, 391, 392, 394, 395
`tidy.svyglm`, 397
`tidy.svyolr`, 17, 76, 120, 122, 192, 221, 255,
256, 358, 398
`tidy.systemfit`, 399
`tidy.table`, 401
`tidy.ts`, 232, 381, 402, 407
`tidy.TukeyHSD`, 107, 108, 233, 235, 236, 324,
403
`tidy.varest`, 405
`tidy.zoo`, 232, 381, 403, 406
`tidy_irlba`, 78, 223, 225, 361, 408, 411, 413,
414
`tidy_optim`, 223, 225, 409, 410, 413, 414
`tidy_optim()`, 337
`tidy_svd`, 78, 223, 225, 361, 409, 411, 411,
414
`tidy_svd()`, 408
`tidy_xyz`, 223, 225, 409, 411, 413, 413
`tidyr::pivot_longer()`, 402
`tseries::garch()`, 144, 288, 289

`vars::VAR()`, 222, 405, 406
`vars_tidiers(tidy.varest)`, 405

`xyz_tidiers(tidy_xyz)`, 413

`zoo::zoo()`, 407
`zoo_tidiers(tidy.zoo)`, 406