

Package ‘mailtoR’

June 25, 2020

Type Package

Title Creates a Friendly User Interface for Emails Sending in 'shiny'

Version 0.1.0

Author Mohamed El Fodil Ihaddaden

Maintainer Mohamed El Fodil Ihaddaden <ihaddaden.fodeil@gmail.com>

Description Allows the user to generate a friendly user interface for emails sending.
The user can choose from the most popular free email services ('Gmail', 'Outlook', 'Yahoo') and his default email application.
The package is a wrapper for the 'Mailtoui' 'JavaScript' library. See <<https://mailtoui.com/#menu>> for more information.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports htmltools, glue, utils

RoxygenNote 7.1.0

URL <https://github.com/feddelegrand7/mailtoR>

BugReports <https://github.com/feddelegrand7/mailtoR/issues>

NeedsCompilation no

Repository CRAN

Date/Publication 2020-06-25 11:50:05 UTC

R topics documented:

mailtoR	2
use_mailtoR	3
Index	4

`mailtoR`*Create a friendly user interface for sending emails*

Description

Create a friendly user interface for sending emails

Usage

```
mailtoR(email, text, subject = NULL, cc = NULL, bcc = NULL, body = NULL)
```

Arguments

<code>email</code>	the emails of the recipients
<code>text</code>	the link text that will be displayed on the ui
<code>subject</code>	the subject of the email. Defaults to NULL
<code>cc</code>	the emails of the CC (carbon copy) recipients. Defaults to NULL
<code>bcc</code>	the emails of the BCC (blind carbon copy) recipients. Defaults to NULL
<code>body</code>	the body of the email. Defaults to NULL

Value

a user interface for sending emails

Examples

```
if (interactive()) {  
  
  ui <- fluidPage(  
    mailtoR(email = "",  
            text = "click here to send an email"),  
            use_mailtoR()  
  )  
  
  server <- function(input, output){  
  
  }  
  
  shinyApp(ui, server)
```

```
}
```

use_mailtoR

Enable the MailtoUI javascript library

Description

The function activates the capabilities of the MailtoUI javascript library. The user needs to set it at the end of the shiny ui.

Usage

```
use_mailtoR()
```

Value

called for the side effect of activating the MailtoUI library

Examples

```
# Put the function at the bottom of the ui  
  
use_mailtoR()
```

Index

`mailtoR`, 2

`use_mailtoR`, 3